

16

Composite Steel-Concrete Construction

16.1 HISTORICAL BACKGROUND

Steel framing supporting cast-in-place reinforced concrete slab construction was historically designed on the assumption that the concrete slab acts independently of the steel in resisting loads. No consideration was given to the composite effect of the steel and concrete acting together. This neglect was justified on the basis that the bond between the concrete floor or deck and the top of the steel beam could not be depended upon. However, with the advent of welding, it became practical to provide mechanical shear connectors to resist the horizontal shear which develops during bending.

Steel beams encased in concrete were widely used from the early 1900s until the development of lightweight materials for fire protection in the past 50 years. Some such beams were designed compositely and some were not. In the early 1930s bridge construction began to use composite sections. Not until the early 1960s was it economical to use composite construction for buildings. However, current practice (2008) utilizes composite action in nearly all situations where concrete and steel are in contact, both on bridges and buildings.

Composite construction, as treated in this chapter, consists either of a solid cast-in-place concrete slab placed upon and interconnected to a steel rolled W section or welded I-shaped girder, as shown in Fig. 16.1.1, or most commonly, the concrete slab is cast upon





Figure 16.1.1
Conventional composite
steel-concrete beam.



Shear stud connectors on flanges of bridge girders to be embedded in the concrete slab in order to make steel section and concrete slab act as a unit (i.e., compositely). (Photo by C. G. Salmon)

cold-formed steel deck (Fig. 16.1.2), which itself is supported on a steel I-shaped section. The corrugations (ribs) may be either parallel to or perpendicular to the supporting beam. When the ribs are parallel to the beam, the behavior is essentially that of a variable thickness slab supported directly on the steel beam. When the ribs are perpendicular to the steel W section, special treatment is required. The many varieties of composite steel-concrete construction are discussed in the State-of-the Art Report [16.1].

The composite beam is one having a wide flange (concrete slab), typically spanning 8 to 15 ft between parallel beams. Ordinary beam theory, where the stress is assumed constant across the width of a beam at a given distance from the neutral axis, *does not apply*. Plate theory indicates the stress decreases the more distant a point is from the stiff part (steel section in this case) of the beam. Similarly to the treatment of T-sections in reinforced concrete, an *equivalent width* is used in place of the actual width, so that ordinary





Figure 16.1.2
Composite section using
formed steel deck. Steel
beam supporting deck and
slab may be parallel to ribs of
formed deck (as in b.) or
perpendicular to the ribs.
(AISC-I3.2c)(Adapted from
AISC Commentary [1.14])

beam theory can be used. An excellent summary of the factors involved in obtaining an effective width is given by Brendel [16.2] and Heins and Fan [16.3]. Vallenilla and Bjorhovde [16.4] have reviewed the effective width in the context of LRFD and the use of steel deck to support the slab.

Viest [16.5], in his 1960 review of research, notes that the important factor in composite action is that the bond between concrete and steel remain unbroken. As designers began to place slabs on top of supporting steel beams, investigators began to study the behavior of mechanical shear connectors. The shear connectors provided the interaction necessary for the concrete slab and steel beam to act as a unit; i.e., no slip between the concrete and steel beam parallel to the beam. For the earlier encased beams there had been sufficient contact area between concrete and steel so that friction provided the necessary interaction between the two materials.

The State-of-the-Art Report of 1974 [16.1] provides an overall survey of the subject of composite construction, including bibliography. Hansell, Galambos, Ravindra, and Viest [16.6] have provided the background for Load and Resistance Factor Design. Iyengar and Iqbal [16.7] have provided a modern review of composite construction in building design, and Lorenz and Stockwell [16.8] and Lorenz [16.9] have provided treatment of basic design concepts for Load and Resistance Factor Design.

A thorough treatment of steel-concrete composite construction in the context of *Eurocode 4* has been developed by IABSE [16.42].

16.2 COMPOSITE ACTION

Composite action is developed when two load-carrying structural members such as a concrete floor system and the supporting steel beam (Fig. 16.2.1a) are integrally connected and deflect as a single unit as in Fig. 16.2.1b. The extent to which composite action is developed depends on the provisions made to insure a single linear strain from the top of the concrete slab to the bottom of the steel section.

In developing the concept of composite behavior, consider first the noncomposite beam of Fig. 16.2.1a, wherein if friction between the slab and beam is neglected, the beam and slab each carry separately a part of the load. This is further shown in Fig. 16.2.2a. When the slab deforms under vertical load, its lower surface is in tension and elongates; while the upper surface of the beam is in compression and shortens. Thus a discontinuity will occur at the plane of contact. Since friction is neglected, only vertical internal forces act between the slab and beam.




Figure 16.2.1
Comparison of deflected
beams with and without
composite action.




Figure 16.2.2
Strain variation in composite
beams.

When a system acts compositely (Fig. 16.2.1b and 16.2.2c) no relative slip occurs between the slab and beam. Horizontal forces (shears) are developed that act on the lower surface of the slab to compress and shorten it, while simultaneously they act on the upper surface of the beam to elongate it.

By an examination of the strain distribution when there is no interaction between the concrete slab and the steel beam (Fig. 16.2.2a), it is seen that the total resisting moment is equal to

$$\Sigma M = M_{\text{slab}} + M_{\text{beam}} \quad (16.2.1)$$

It is noted that for this case there are two neutral axes; one at the center of gravity of the slab and the other at the center of gravity of the beam. The horizontal slip resulting from the bottom of the slab in tension and the top of the beam in compression is also indicated.

Consider next the case where only partial interaction is present, Fig. 16.2.2b. The neutral axis of the slab is closer to the beam and that of the beam closer to the slab. Due to the partial interaction, the horizontal slip has now decreased. The result of the partial interaction is the partial development of the maximum compressive and tensile forces C' and T' , in the concrete slab and steel beam, respectively. The resisting moment of the section would then be increased by the amount $T'e'$ or $C'e'$.

When complete interaction (known as full composite action) between the slab and the beam is developed, no slip occurs and the resulting strain diagram is shown in Fig. 16.2.2c. Under this condition, a single neutral axis occurs which lies below that of the slab and above that of the beam. In addition, the compressive and tensile forces C'' and T'' , respectively, are larger than the C' and T' existing with partial interaction. The resisting moment of the fully developed composite section then becomes

$$\Sigma M = T''e'' \quad \text{or} \quad C''e'' \quad (16.2.2)$$

16.3 ADVANTAGES AND DISADVANTAGES

The basic advantages resulting from composite design are

1. Reduction in the weight of steel
2. Shallower steel beams
3. Increased floor stiffness
4. Increased span length for a given number

A weight savings in steel of 20 to 30% is often possible by taking full advantage of a composite system. Such a weight reduction in the supporting steel beams usually permits the use of a shallower as well as a lighter member. This advantage may reduce the height of a multistoried building significantly so as to provide savings in other building materials such as outside walls and stairways. The overall economy of using composite construction when considering total building cost appears to be increasingly favorable [16.10, 16.11].

The stiffness of a composite floor is substantially greater than that of a concrete floor with its supporting beams acting independently. Normally the concrete slab acts as a one-way plate spanning between the supporting beams. In composite design, an additional use is made of the slab by its action in a direction parallel to and in combination with the supporting steel beams. The net effect is to greatly increase the moment of inertia of the floor system in the direction of the steel beams. The increased stiffness considerably reduces the live load deflections and, if shoring is provided during construction, also reduces dead load deflections. Assuming full composite action, the nominal strength of the section greatly exceeds the sum of the strengths of the slab and the beam considered separately, providing high overload capacity.

While there are no major disadvantages, some limitations should be recognized. In continuous construction, the negative moment region will have a different stiffness because the concrete slab in tension is expected to be cracked and not participating. In general, it is considered acceptable to assume the moment of inertia to be constant through both positive and negative moment regions, using the positive moment composite section moment of inertia AISC-II. Tension in the concrete is neglected.

Long-term deflection caused by concrete creep and shrinkage could be important when the composite section resists a substantial part of the dead load, or when the live load is of long duration. This is discussed in Sec. 16.12.

16.4 EFFECTIVE WIDTH

The concept of *effective width* is useful in design when strength must be determined for an element subject to nonuniform distribution of stress. Referring to Fig. 16.4.1, the concrete slab of a composite section is considered to be infinitely wide. The intensity of extreme fiber stress f_c is a maximum over the steel beam and decreases nonlinearly as the distance from the supporting beam increases.

The effective width b_E of a flange for a composite member may be expressed

$$b_E = b_f + 2b' \quad (16.4.1)$$

where $2b'$ times the maximum stress f_c equals the area under the curves for f_c . Various investigators, including Timoshenko and Goodier [16.12] and von Kármán [16.13], have derived expressions for the effective width of homogeneous beams having wide flanges; and Johnson and Lewis [16.14] have shown such expressions are valid for beams in which the flange and web are of different materials.

The analysis for effective width involves theory of elasticity applied to plates, using an infinitely long continuous beam on equidistant supports, with an infinitely wide flange




Figure 16.4.1
Actual and equivalent stress distribution over flange width.

having a small thickness compared to the beam depth. The total compression force carried by the equivalent system must be the same as that carried by the real system.

The practical simplifications for design purposes are given by AISC-I3.1a the same for service load calculations as for nominal strength calculations when failure is imminent.

1. For an interior girder, referring to Fig. 16.4.2,

$$b_E \leq \frac{L}{4} \tag{16.4.2a}$$

$$b_E \leq b_0 \quad (\text{for equal beam spacing}) \tag{16.4.2b}$$

2. For an exterior girder.

$$b_E \leq \frac{L}{8} - \left(\begin{array}{l} \text{distance from beam center} \\ \text{to edge of slab} \end{array} \right) \tag{16.4.3a}$$

$$b_E \leq \frac{1}{2} b_0 - \left(\begin{array}{l} \text{distance from beam center} \\ \text{to edge of slab} \end{array} \right) \tag{16.4.3b}$$




Figure 16.4.2
Dimensions governing effective width b_E on composite steel-concrete beams.

The American Concrete Institute (ACI) Code [16.15] has long used the following effective flange widths for *T*-sections:

1. For an *interior girder*, referring to Fig. 16.4.2,

$$b_E \leq \frac{L}{4} \quad (16.4.4a)$$

$$b_E \leq b_0 \quad (\text{for equal beam spacing}) \quad (16.4.4b)$$

$$b_E \leq b_f + 16t_s \quad (16.4.4c)$$

2. For an *exterior girder*,

$$b_E \leq b_f + \frac{L}{12} \quad (16.4.5a)$$

$$b_E \leq b_f + 6t_s \quad (16.4.5b)$$

$$b_E \leq b_f + 0.5(\text{clear distance to next beam}) \quad (16.4.5c)$$

These 2008 *ACI Code* effective widths are identical to AISC effective widths used prior to the 1986 LRFD Specification. The present AISC rules are simpler, eliminating the beam flange width b_f and the slab thickness t_s as variables.

16.5 COMPUTATION OF ELASTIC SECTION PROPERTIES

The elastic section properties of a composite section can be computed by the transformed section method. In contrast to reinforced concrete, where the reinforcing bar steel is transformed into an equivalent concrete area, the concrete slab in the composite section is transformed into equivalent steel. As a result, the concrete area is reduced by using a slab width equal to b_E/n , where n is the modulus of elasticity ratio E_s/E_c . E_s is the modulus of elasticity of steel, taken as 29,000 ksi, and E_c in psi is given by the ACI Code [16.15], as follows:

$$E_c = 33(w^{1.5})\sqrt{f'_c}, \text{ psi} \quad (16.5.1)^*$$

where w is the density of concrete in pcf and f'_c is in psi. Since the *AISC Specification* uses stress in ksi for all formulas, AISC-I2.1b converts Eq. 16.5.1 approximately to the following for E_c in ksi:

$$E_c = w^{1.5}\sqrt{f'_c}, \text{ ksi} \quad (16.5.2)^*$$

Note that $\sqrt{1000}$ is 31.6; thus, Eq. 16.5.2 gives E_c about 4% lower than the ACI Code. For normal-weight concrete, weighing approximately 145 pcf, Eq. 16.5.2 gives E_c in ksi as

$$E_c = 1750\sqrt{f'_c}, \text{ ksi} \quad (16.5.3)^*$$

Within the accuracy that the modulus of elasticity of concrete may be predicted, either the *ACI Code* [16.15] value or the suggested value of AISC-I2.1b is acceptable. The modulus of elasticity ratio n is commonly taken to the nearest whole number. Table 16.5.1 indicates practical values usually used in computing elastic section properties.

*For SI units, giving E_c in MPa,

$$E_c = w^{1.5}(0.043)\sqrt{f'_c} \quad (16.5.1)$$

$$E_c = w^{1.5}(0.041)\sqrt{f'_c} \quad (16.5.2)$$

$$E_c = 4600\sqrt{f'_c} \quad (16.5.3)$$

where w is in kg/m^3 and f'_c is in MPa.

TABLE 16.5.1 Practical Values for Modular Ratio n

f'_c (psi)	Modular ratio $n = E_s/E_c$	f'_c (MPa)
3000	9	21
3500	$8\frac{1}{2}$	24
4000	8	28
4500	$7\frac{1}{2}$	31
5000	7	35
6000	$6\frac{1}{2}$	42

Effective Elastic Section Modulus

A complete beam may be considered as a steel member to which has been added a cover plate on the top flange. This “cover plate” being concrete is considered to be effective only when the top flange is in compression. In continuous beams, the concrete slab is usually ignored in regions of negative moment. If the neutral axis falls within the concrete slab, present practice is to consider only that portion of the concrete slab which is in compression.

AISC-I3.2 permits reinforcement parallel to the steel beam and lying within the effective slab width to be included in computing properties of composite sections. These reinforcing bars usually make little difference to the composite section modulus in the positive moment region and their effect is frequently neglected.

EXAMPLE 16.5.1

Compute the elastic section properties of the composite section shown in Fig. 16.5.1 assuming $f'_c = 3000$ psi and $n = 9$. Use the effective flange width according to AISC-I3.1a.

Solution:

First, determine effective width (AISC-I3.1a).

$$b_E = L/4 = 0.25(30)12 = 90 \text{ in. controls}$$

$$b_E = b_0 = 8(12) = 96 \text{ in.}$$

The width of equivalent steel is $b_E/n = 10.0$ in. The computation of the moment of inertia I_x about the center of gravity of the W21×62 is shown, as follows:

Element	Transformed Area A (sq in.)	Moment Arm from Centroid y (in.)	Ay (in. ³)	Ay^2 (in. ⁴)	I_0 (in. ⁴)
Slab	40.0	+12.495	+500	6245	53
W21×62	18.3	0	0	0	1330
Cover plate	<u>7.0</u>	-10.995	<u>-77</u>	<u>846</u>	<u>1</u>
	65.3		+423	7091	1384

$$I_x = I_0 + Ay^2 = 1384 + 7091 = 8475 \text{ in.}^4$$

$$\bar{y} = \frac{+423}{65.3} = +6.48 \text{ in.}$$

$$I_{tr} = I_x - A\bar{y}^2 = 8475 - 65.3 (6.48)^2 = 5737 \text{ in.}^4$$

$$y_t = 10.50 - 6.48 + 4.0 = 8.02 \text{ in.}$$

$$y_b = 10.50 + 6.48 + 1.0 = 17.98 \text{ in.}$$

The symbol I_{tr} is used for the *fully composite uncracked transformed section* moment of inertia. The elastic section modulus S_{conc} referred to the top fiber of the concrete slab is

$$S_{conc} = I_{tr}/y_t = 5737/8.02 = 715 \text{ in.}^3$$

The elastic section modulus S_{tr} referred to the extreme fiber at the tension flange of the steel section (in this case the cover plate) is

$$S_{tr} = I_{tr}/y_b = 5737/17.98 = 319 \text{ in.}^3$$

The addition of a cover plate at the tension flange brings the neutral axis down and permits more economical use of the composite section. However, the cost of welding a cover plate to the rolled section usually exceeds any material saving; thus, a cover plate is rarely used. ■




Figure 16.5.1
Composite section for
Example 16.5.1.

16.6 SERVICE LOAD STRESSES WITH AND WITHOUT SHORING

The actual stresses that result due to a given loading on a composite member are dependent upon the manner of construction.

The simplest construction occurs when the steel beams are placed first and used to support the concrete slab formwork. In this case the steel beam acting noncompositely (i.e., by itself) supports the weight of the forms, the wet concrete, and its own weight. Once forms are removed and concrete has cured, the section will act compositely to resist all dead and live loads placed after the curing of concrete. Such construction is said to be *without temporary shoring* (i.e., unshored).

Alternatively, to reduce the service load stresses, the steel beams may be supported on temporary shoring; in which case, the steel beam, forms, and wet concrete, are carried by the shores. After curing of the concrete, the shores are removed and the section acts compositely to resist all loads. This system is called *shored construction*.

The following example illustrates the difference in service load stresses under the two systems of construction.

EXAMPLE 16.6.1

For the steel W21×62 with the 1 by 7-in. plate of Fig. 16.5.1, determine the service load stresses considering that (a) construction is without temporary shoring, and (b) construction uses temporary shores. The dead- and live-load moment M_L to be superimposed on the system after the concrete has cured is 560 ft-kips.

Solution:

The composite section properties as computed in Example 16.5.2 are

$$S_{\text{top}} = 715 \text{ in.}^3 \quad (\text{top of concrete})$$

$$S_{\text{bottom}} = S_{\text{tr}} = 319 \text{ in.}^3 \quad (\text{bottom of steel})$$

The noncomposite properties for the steel section alone (see Fig. 16.6.1) are computed as follows:

$$\bar{y} = \frac{7.0(10.995)}{7.0 + 18.3} = 3.04 \text{ in.}$$

$$y_b = 10.495 - 3.04 + 1.00 = 8.45 \text{ in.}$$




Figure 16.6.1
Steel section for
Example 16.6.1.

$$\begin{aligned}
 I_s &= I_0 (\text{W21} \times 62) + A_p y^2 - A \bar{y}^2 \\
 &= 1330 + 7.0(10.995)^2 - 25.3(3.04)^2 \\
 &= 1330 + 846 - 234 = 1942 \text{ in.}^4 \\
 S_{st} &= \frac{1942}{13.55} = 143 \text{ in.}^3 \quad (\text{top}) \\
 S_{sb} &= \frac{1942}{8.45} = 230 \text{ in.}^3 \quad (\text{bottom})
 \end{aligned}$$

(a) *Without Temporary Shores.* Weight due to the concrete slab and steel beam,

$$w \text{ (concrete slab), } (4/12)(8)0.15 = 0.40$$

$$w \text{ (steel beam)} = 0.06$$

$$0.46 \text{ kips/ft}$$

$$M_D \text{ (DL on noncomposite)} = \frac{1}{8}(0.46)(30)^2 = 51.8 \text{ ft-kips}$$

$$f_{\text{top}} = \frac{M_D}{S_{st}(\text{steel section})} = \frac{51.8(12)}{143} = 4.3 \text{ ksi}$$

$$f_{\text{bottom}} = \frac{M_D}{S_{sb}(\text{steel section})} = \frac{51.8(12)}{230} = 2.7 \text{ ksi}$$

The additional stresses after the concrete has cured are

$$f_{\text{top}} = \frac{M_L}{nS_{\text{top}}(\text{composite})} = \frac{560(12)}{9(715)} = 1.04 \text{ ksi (concrete stress)}$$

where the stress in the concrete is $1/n$ times the stress on equivalent steel (transformed section).

$$f_{\text{bottom}} = \frac{M_L}{S_{tr}} = \frac{560(12)}{319} = 21.1 \text{ ksi}$$

The total maximum tensile stress in the steel is

$$f = f(\text{noncomposite}) + f(\text{composite}) = 2.7 + 21.1 = 23.8 \text{ ksi}$$

(b) *With Temporary Shores.* Under this condition all loads are resisted by the composite section.

$$f_{\text{top}} = \frac{M_D + M_L}{S_{\text{top}}(\text{composite})} = \frac{(560 + 51.8)12}{715(9)} = 1.14 \text{ ksi on concrete}$$

$$f_{\text{bottom}} = \frac{M_D + M_L}{S_{tr}} = \frac{(560 + 51.8)12}{319} = 23.0 \text{ ksi}$$

Stress distributions for both with and without shores are given in Fig. 16.6.2. Since the dead load was small in this example, use of shores gave insignificant reduction in service load stress. Where thicker slabs are used, the dead load stresses may become as high as 30%, in which case using or not using shores will make a significant difference. ■




Figure 16.6.2
Service load stresses for
example 16.6.1.

6.7 NOMINAL MOMENT STRENGTH OF FULLY COMPOSITE SECTIONS

The nominal strength M_n of a composite section having its slab in compression (positive moment) depends on the yield stress F_y and section properties (including slenderness $\lambda = h/t_w$ for the web) for the steel beam, the concrete slab strength f'_c , and the strength of shear connectors providing the interface shear transfer between slab and beam.

The nominal strength (commonly called *ultimate strength*) concepts were first applied to design practice as recommended by the ASCE-ACI Joint Committee on Composite Construction [16.16], and further modified by Slutter and Driscoll [16.17]. Ultimate strength was reviewed in the State-of-the-Art Report [16.1], and treated in the context of Load and Resistance Factor Design by Hansell et al. [16.6].

Traditionally, since the Joint Committee Report [16.16] the design of composite beams has been based on nominal moment strength even though Allowable Stress Design was used. Load and Resistance Factor Design is particularly adapted to using composite flexural members since the concepts of strength are easier to understand without trying to convert them into a service load based Allowable Stress Design.

The nominal moment strength M_n when the slab is in compression (positive moment) is divided into two categories according to AISC-13.2a, depending on web slenderness, as follows:

1. For $h/t_w \leq [3.76\sqrt{E/F_y} = 640/\sqrt{F_y}]$

M_n = nominal moment strength based on plastic stress distribution on the composite section (plastic moment)

$$\phi_b = 0.90$$

2. For $h/t_w > [3.76\sqrt{E/F_y} = 640/\sqrt{F_y}]$

M_n = nominal moment strength based on superposition of elastic stresses (shown in Sec. 16.6), considering the effects of shoring, for the limit state of yielding (yielding moment)

$$\phi_b = 0.90$$

Since the elastic properties and effects of shoring have been treated in Sec. 16.6, this section focuses on strength based on plastic stress distribution. It is noted that all current ASTM A6 W shapes satisfy the limit for Case 1.

The nominal strength M_n based on plastic stress distribution may be divided into two general categories: (1) the plastic neutral axis (PNA) occurs in the slab; and (2) the plastic neutral axis occurs in the steel section. When the PNA occurs in the steel section, the nominal strength M_n calculation will differ depending on whether the PNA is in the flange or the web.

The concrete is assumed to develop only compression forces. Although concrete is able to sustain a limited amount of tension, the tensile strength is negligible at the strains occurring when nominal strength is reached.

Case 1—Plastic Neutral Axis (PNA) in the Slab

Referring to Fig. 16.7.1b and assuming the Whitney rectangular stress distribution* (uniform stress of $0.85f'_c$ acting over a depth a), the compressive force C is

$$C = 0.85 f'_c a b_E \tag{16.7.1}$$

The tensile force T is the yield stress on the beam times its area:

$$T = A_s F_y \tag{16.7.2}$$

Equating the compressive force C to the tensile force T gives

$$a = \frac{A_s F_y}{0.85 f'_c b_E} \tag{16.7.3}$$

According to the ACI-accepted [16.15, Sec. 10.2.7] rectangular stress distribution, the neutral axis distance x , as shown in Fig. 16.7.1d, equals $a/0.85$ for $f'_c \leq 4000$ psi. The nominal moment strength M_n , from Fig. 16.7.1b, becomes

$$M_n = C d_1 \quad \text{or} \quad T d_1 \tag{16.7.4}$$

When the slab is capable of developing a compressive force at least equal to the full yield strength of the steel beam, the PNA will be in the slab, the common situation for fully composite sections. Expressing the nominal strength in terms of the steel force gives

$$M_n = A_s F_y \left(\frac{d}{2} + t_s - \frac{a}{2} \right) \tag{16.7.5}$$

The usual procedure for computing nominal strength is to assume the depth a for the rectangular stress distribution will not exceed t_s ; i.e., use Eq. 16.7.3. If a is verified to not exceed t_s , Eq. 16.7.5 can be used to obtain nominal strength M_n .

In the past, Case 1 has been referred to as “slab adequate”; meaning that the slab is capable of developing in compression the full nominal strength of the steel beam in tension.




Figure 16.7.1
Plastic stress distribution at nominal moment strength M_n . (PNA = plastic neutral axis)

*For the development of the concept of replacing the true distribution of compressive stress by a rectangular stress distribution, see for example, Chu-Kia Wang, Charles G. Salmon, and José Pinchiera. *Reinforced Concrete Design*, 7th ed. (Wiley, 2006, Chap. 3).

Case 2—Plastic Neutral Axis (PNA) in the Steel Beam

If the depth a of the stress block as determined in Eq. 16.7.3 exceeds the slab thickness, the stress distribution will be as shown in Fig. 16.7.1c. The compressive force C_c in the slab is

$$C_c = 0.85 f'_c b_E t_s \quad (16.7.6)$$

The compressive force in the steel beam resulting from the portion of the beam above the neutral axis is shown in Fig. 16.7.1c as C_s .

The tensile force T' which is now less than $A_s F_y$ must equal the sum of the compressive forces:

$$T' = C_c + C_s \quad (16.7.7)$$

Also,

$$T' = A_s F_y - C_s \quad (16.7.8)$$

Equating Eqs. 16.7.7 and 16.7.8, C_s becomes

$$C_s = \frac{A_s F_y - C_c}{2}$$

or

$$C_s = \frac{A_s F_y - 0.85 f'_c b_E t_s}{2} \quad (16.7.9)$$

Considering the compressive forces C_c and C_s , the nominal moment strength M_n for Case 2 is

$$M_n = C_c d'_2 + C_s d''_2 \quad (16.7.10)$$

where the moment arms d'_2 and d''_2 are as shown in Fig. 16.7.1c.

When the Case 2 situation occurs, the steel beam must be capable of accommodating plastic strain in both tension and compression to achieve the nominal strength condition. The lower the PNA occurs in the steel section the more local buckling may influence the behavior. As indicated earlier in this section, in order to use the plastic stress distribution at all, AISC-I3.2a requires the web $\lambda \leq \lambda_p$.

When the flange of the steel section adjacent to the slab is in compression, there might be concern regarding flange local buckling. The combination of concrete bearing against the compression flange and the shear connectors used to attach the slab and steel beam together eliminates flange local buckling as well as lateral-torsional buckling as controlling limit states. AISC-I3.2 addresses only the issue of web local buckling; it is silent regarding flange local buckling.

EXAMPLE 16.7.1

Determine the nominal moment strength M_n of the composite section shown in Fig. 16.7.2. Use A992 steel, $f'_c = 4000$ psi, and $n = 8$.

Solution:

Assume the plastic neutral axis (PNA) is within the slab; i.e., that $a \leq t_s$ (Case 1),

$$a = \frac{A_s F_y}{0.85 f'_c b_E} = \frac{10.6(50)}{0.85(4)60} = 2.60 \text{ in.} < t_s \quad \text{OK}$$

$$C = 0.85 f'_c a b_E = 0.85(4)(2.6)60 = 530 \text{ kips}$$




Figure 16.7.2
Example 16.7.1.

$$T = A_s F_y = 10.6(50) = 530 \text{ kips (checks)}$$

$$\text{Arm } d_1 = \frac{d}{2} + t - \frac{a}{2} = 7.925 + 4.0 - 1.30 = 10.63 \text{ in.}$$

The nominal moment strength M_n is then

$$M_n = C d_1 = 530(10.63) \frac{1}{12} = 470 \text{ ft-kips}$$

EXAMPLE 16.7.2

Determine the nominal moment strength M_n of the composite section shown in Fig. 16.7.3. Use A992 steel, $f'_c = 4000$ psi, and $n = 8$.

Solution:

Referring to Fig. 16.7.3, assume the plastic neutral axis (PNA) is within the flange (i.e., Case 1),

$$a = \frac{A_s F_y}{0.85 f'_c b_E} = \frac{47.0(50)}{0.85(4)(72)} = 9.60 \text{ in.} > \left[t_s = 7.0 \text{ in.} \right] \quad \text{NG}$$

Since the concrete slab is only 7 in. thick, the slab cannot develop enough strength to balance the tension force $A_s F_y$ capable of developing in the steel section; thus the PNA will be within the steel section; thus, Case 2 applies. Using Eq. 16.7.6,

$$C_c = 0.85 f'_c b_E t_s = 0.85(4)72(7) = 1714 \text{ kips}$$




Figure 16.7.3
Example 16.7.2.

Using Eq. 16.7.9.

$$C_s = \frac{A_s F_y - 0.85 f'_c b_f t_s}{2} = \frac{47.0(50) - 1714}{2} = 318 \text{ kips}$$

Assuming only the flange of the W36×160 ($b_f = 12.00$ in.) is in compression, the portion of the flange d_f to the neutral axis is

$$d_f = \frac{318}{50(12.00)} = 0.53 \text{ in.} < [t_f = 1.020 \text{ in.}]$$

Thus, the PNA is within the flange. The location of the centroid of the tension portion of the steel beam from the bottom is

$$\bar{y} = \frac{47.0(18) - 0.53(12)35.76}{47.0 - 0.53(12)} = 15.22 \text{ in.}$$

Referring to Fig. 16.7.3, the nominal composite moment strength M_n from Eq. 16.7.10 is

$$\begin{aligned} M_n &= C_c d'_2 + C_s d''_2 \\ &= [1714(23.95) + 318(20.18)]/12 = 3960 \text{ ft-kips} \quad \blacksquare \end{aligned}$$

The nominal strength M_n has inherently assumed that shear connectors will provide sufficient shear transfer at the slab-to-flange interface to develop however much of the slab compressive strength that is required to balance the tension force developed in the steel beam. Shear connectors are treated in Sec. 16.8.

The nominal strength M_n is *independent* of whether or not the system is shored during construction. Even though service load stresses are different, as illustrated in Sec. 16.6, the nominal strength is the same, shored or unshored.

16.8 SHEAR CONNECTORS

The horizontal shear that develops between the concrete slab and the steel beam during loading must be resisted so that the slip shown in Fig. 16.2.2 will be restrained. A fully composite section will have no slip at the concrete-steel interface. Although some bond may develop between the steel and the concrete, it is not sufficiently predictable to provide the required interface shear strength. Neither can friction between the concrete slab and the steel beam develop such strength.

Instead, mechanical shear connectors are *required* (AISC-I3.2d), except for the totally concrete-encased steel beam. Some mechanical shear connectors are shown in Fig. 16.8.1. The only connectors specifically provided for in the *AISC Specification* are stud shear connectors [AISC-I3.2d(3)] and channel connectors [AISC-I3.2d(4)]. Currently (2008), nearly all shear connectors are headed studs.

Ideally, to obtain a *fully composite section* the shear connectors should be stiff enough to provide the complete interaction (i.e., no slip at the interface) shown in Fig. 16.2.2c. This, however, would require that the connectors be infinitely rigid. Also, by referring to the shear diagram for a uniformly loaded beam as shown in Fig. 16.8.2, it would be inferred, theoretically at least, that more shear connectors are required near the ends of the span where the shear is high, than near midspan where the shear is low.

Consider the shear stress distribution of Fig. 16.8.2b wherein the stress v_1 must be developed by the connection between the slab and beam. Under elastic conditions the shear stress at any point in the cross-section will vary from a maximum at the support to zero at




Figure 16.8.1
Shear connectors.





Figure 16.8.2
Shear variation for uniform loading and distribution of shear stress over the depth of a steel-concrete composite section.

midspan. Next, examine the equilibrium of an elemental slice of the beam, as in Fig. 16.8.3. The shear force per unit distance along the span is $dC/dx = v_1 b_E = V(\int y dA)/I$. (The $\int y dA$ is commonly given the symbol Q in elastic beam theory; this should not be confused with the nominal connector strength Q_n used below.) Thus, if a given connector has an allowable service load capacity q (kips), the maximum spacing p to provide the required strength is

$$p = \frac{q}{V(\int y dA)/I} \quad (16.8.1)$$

where $\int y dA$ is the statical moment of the transformed compressive concrete area (the slab) taken about the neutral axis of the composite section. Equation 16.8.1 is based on elastic beam theory and a fully composite section.

Figure 16.8.3
Force required from shear
connectors at service load
level.



Until recent years, Eq. 16.8.1 was used to space shear connectors. AASHTO-6.10.10.1.2 [1.3] requires using Eq. 16.8.1 to design for fatigue, a service load limit state related to the range of force applied, in this case the range of shear V_r resulting from live load (and impact). AASHTO also requires a strength limit state check.

According to the strength limit state, the shear connectors at nominal moment strength share equally in transmitting the shear at the interface between concrete slab and steel beam. This means, referring to Fig. 16.8.2a, that shear connectors are required to transfer the compressive force developed in the slab at midspan to the steel beam in the distance $L/2$, since no compressive force can exist in the slab at the end of the span where zero moment exists. The nominal shear transfer strength cannot exceed the maximum force the concrete can develop, namely

$$V' = C_{\max} = 0.85f'_c b_E t_s \quad (16.8.2)$$

where b_E is the effective slab width and t_s is the slab thickness. When the maximum force T_{\max} that can develop in the steel is less than C_{\max} , the maximum shear transfer strength will be

$$V' = T_{\max} = A_s F_y \quad (16.8.3)$$

where A_s is the cross-sectional area of the steel section.

Thus, when the nominal strength Q_n of one shear connector is known, the total number N of shear connectors required between points of maximum and zero bending moment is

$$N = \frac{C_{\max}}{Q_n} \quad \text{or} \quad \frac{T_{\max}}{Q_n}, \quad \text{whichever is smaller} \quad (16.8.4)$$

Thus, the strength is achieved when the total number N of shear connectors is placed between the maximum moment and zero moment locations. Uniform spacing will be the simplest procedure, because the number of connectors rather than the spacings affects the strength.

The determination of the connector capacity analytically is complex, since the shear connector deforms under load and the concrete which surrounds it is also a deformable material. Moreover, the amount of deformation a shear connector undergoes is dependent upon factors such as its own shape and size, its location along the beam, the location of the maximum moment, and the manner in which it is attached to the top flange of the steel beam. In addition, any particular shear connector may yield sufficiently to cause slip between the beam and the slab. In the latter case the adjacent shear connectors pick up the additional shear.

As a result of the complex behavior of shear connectors, their capacities are not based solely on a theoretical analysis. In order to develop a rational approach, a number of research programs, summarized by Viest [16.1, 16.5], were undertaken to develop the strengths of the various types of shear connectors.

Investigators determined that shear connectors will not fail when the average load per connector is below that causing 0.003 in. (0.076 mm) residual slip between concrete

and steel. The amount of slip is also a function of the strength of the concrete that surrounds the shear connector. Relating connector capacity to a specified slip may be realistic for bridge design where fatigue strength is important, but it is overly conservative with respect to failure loads. So-called “ultimate” capacities used prior to 1965 [16.17] were based on slip limitation, giving values about one-third of the strengths obtained when failure of a connector is the criterion.

When flexural strength of the composite section is the basis for design, the connectors must be adequate to satisfy equilibrium of the concrete slab between the points of maximum and zero moment, as discussed in the development of Eqs. 16.8.2, 16.8.3, and 16.8.4. Slip is not a criterion for this equilibrium requirement. As stated by Slutter and Driscoll [16.17], “the magnitude of slip will not reduce the ultimate moment provided that (1) the equilibrium condition is satisfied, and (2) the magnitude of slip is no greater than the lowest value of slip at which an individual connector might fail.” Studies by Ollgaard, Slutter, and Fisher [16.19] and McGarraugh and Baldwin [16.20] included the effect of lightweight concrete on stud connector capacity.

All research work cited above was based on experimental work that used solid slabs or steel decks from flat steel plates. Most of composite steel floor decks used in buildings today are formed and have a stiffening rib in the middle of each deck flute. Recent research by Rambo-Roddenberry and others [16.47] concluded that shear stud strength equations in past AISC Specifications are unconservative. The stud strength whether the deck was perpendicular or parallel to the beams, is higher than those derived from either pushout or beam tests for studs embedded in modern steel decks. Also, because of the stiffener, studs must be welded off-center in the deck rib. Rambo-Roddenberry et al [16.47] have shown that shear studs behave differently depending upon their position within the deck rib. The “weak” (unfavorable) and “strong” (favorable) positions are shown in Figure 16.8.4.

Two currently accepted expressions for the nominal strength Q_n of shear connectors are as follows:

1. *Headed steel stud connectors welded to flange* (Fig. 16.8.1a). Load and Resistance Factor Design (AISC-I3.2) gives essentially the expression developed at Lehigh [16.19], and subsequently modified at Virginia Tech [16.47]

$$Q_n = 0.5A_{sc}\sqrt{f'_cE_c} \leq R_gR_pA_{sc}F_u \tag{16.8.5}$$

where A_{sc} = cross-sectional area of stud shear connector, sq in.

F_u = specified minimum tensile strength of a stud shear connector, ksi

$R_g = 1.0$;

- (a) for one stud welded in a steel deck rib with the deck oriented perpendicular to the steel shape;
- (b) for any number of studs welded in a row directly to the steel shape;
- (c) for any number of studs welded in a row through steel deck with the deck oriented parallel to the steel shape and the ratio of the average rib width to rib depth ≥ 1.5




Figure 16.8.4 Weak and strong stud positions [16.47]

$R_g = 0.85$;

- (a) for two studs welded in a steel deck rib with the deck oriented perpendicular to the steel shape;
- (b) for one stud welded through steel deck with the deck oriented parallel to the steel shape and the ratio of the average rib width to rib depth < 1.5

$R_g = 0.7$ for three or more studs welded in a steel deck rib with the deck oriented perpendicular to the steel shape

$R_p = 1.0$ for studs welded directly to the steel shape (in other words, not through steel deck or sheet) and having a haunch detail with not more than 50 percent of the top flange covered by deck or sheet steel closures

$R_p = 0.75$;

- (a) for studs welded in a composite slab with the deck oriented perpendicular to the beam and $e_{mid-ht} \geq 2$ in.;
- (b) for studs welded through steel deck, or steel sheet used as girder filler material, and embedded in a composite slab with the deck oriented parallel to the beam

$R_p = 0.6$ for studs welded in a composite slab with deck oriented perpendicular to the beam and $e_{mid-ht} < 2$ in.

e_{mid-ht} = distance from the edge of stud shank to the steel deck web, measured at mid-height of the deck rib, and in the load bearing direction of the stud (in other words, in the direction of maximum moment for a simply supported beam), in.

w_c = weight of concrete per unit volume ($90 \text{ pcf} \leq w_c \leq 155 \text{ pcf}$)

E_c = modulus of elasticity of concrete, ksi

= $(w^{1.5})\sqrt{f'_c}$, according to AISC-I2.1b, using f'_c in ksi. For normal-weight concrete having density $w = 145 \text{ pcf}$. $E_c = 1746\sqrt{f'_c}$. Note that the ACI Code [16.15] gives slightly different values using $E_c = w^{1.5}33\sqrt{f'_c}$, with f'_c in psi instead of ksi.

2. *Channel connectors* (Fig. 16.8.1b). AISC-I3.2D(4) gives for the nominal connector strength Q_n ,

$$Q_n = 0.3(t_f - 0.5t_w)L_c\sqrt{f'_cE_c} \tag{16.8.6}$$

where Q_n = nominal strength of one channel, kips

t_f = channel flange thickness (Fig. 16.8.1), in.

t_w = channel web thickness, in.

L_c = length of channel, in.

f'_c = 28-day compressive strength of concrete, ksi

E_c = modulus of elasticity of concrete (defined following Eq. 16.5.5), ksi

Connector Design—AISC LRFD Method

The nominal strength Q_n of the connectors is directly used in the AISC Design Methods. AISC-I3.2d requires "... the entire horizontal shear at the interface between the steel beam and the concrete slab shall be assumed to be transferred by shear connectors." For fully composite sections, the nominal horizontal shear strength V_{nh} to be provided by connectors is the smaller of Eqs. 16.8.2 and 16.8.3.

The section may also be designed as *partially composite*, where the forces utilized of the internal couple are less than either the nominal compression strength available from the concrete, or the nominal tension strength available from the steel section. In partially

composite sections, the strength ΣQ_n of the shear connectors determines the magnitude of the forces of the internal couple and nominal moment strength M_n , and correspondingly the required nominal horizontal shear strength V_{nh} . Lorenz and Stockwell [16.8] have discussed stresses in partial composite beams. Bradford and Gilbert [16.44] have provided recent work on partial interaction under sustained loads.

For the positive moment situations (i.e., compression in the concrete slab), the shear strength V_{nh} required is, therefore, the *smallest* of the following:

$$1. V_{nh} \text{ required} = 0.85 f'_c b_E t_s \quad [16.8.2]$$

$$2. V_{nh} \text{ required} = A_s F_y \quad [16.8.3]$$

$$3. V_{nh} \text{ required} = \Sigma Q_n \text{ provided}$$

When 3. applies, the number of connectors controls the nominal strength M_n of the section.

As stated earlier, and as specifically stated in AISC-I3.2d(6), the strength V_{nh} must be provided "... each side of the point of maximum moment ..." to the points of zero moment. Further, AISC-I3.2d(6) states that the connectors *shall* be distributed uniformly between the point of maximum moment and the point of zero moment. This is "unless otherwise specified", whatever that may mean. As long as adequate strength is provided, the spacing of the connectors is not important.

The nominal strengths Q_n for stud and channel connectors from AISC-I3.2d(3) and (4) are given by Eqs. 16.8.5 and 16.8.6; values for common stud diameters and some channels are given in Table 16.8.1.

When a formed steel deck is used (see Fig. 16.1.2) with shear studs embedded in the supported concrete slab, reduction factors must be applied to Q_n in accordance with AISC-I3.2d(3).

In the case of continuous beams (also see Sec. 16.13), the longitudinal reinforcing bar steel within the effective width of the concrete slab is permitted (AISC-I3.2d(2)) to be assumed to act compositely with the steel beam in the areas of negative moment. The total nominal horizontal strength V_{nh} needed from shear connectors between the interior support and each adjacent point of inflection (zero moment) equals the tension force available from the reinforcement (since the tension in the concrete is neglected),

$$T_{\text{slab}} = A_r F_{yr} \quad (16.8.7)$$

where A_r = total area of adequately developed longitudinal reinforcing steel within the effective width b_E of the concrete slab

F_{yr} = minimum specified yield stress of the reinforcing steel

EXAMPLE 16.8.1

Determine the number of $\frac{3}{4}$ -in.-diam \times 3-in. shear stud connectors required to develop the fully composite section of Fig. 16.8.5. Assume the applied loading is uniform and the beam is simply supported. Use A992 steel, $f'_c = 4000$ psi, $n = 8$, and Load and Resistance Factor Design.

Solution:

Using Eqs. 16.8.2 and 16.8.3,

$$V_{nh} = C_{\text{max}} = 0.85 f'_c b_E t_s = 0.85(4.0)(72)7 = 1714 \text{ kips}$$

or

$$V_{nh} = T_{\text{max}} = A_s F_y = 47.0(50) = 2350 \text{ kips}$$

TABLE 16.8.1 Nominal Strength Q_n (kips) for Stud and Channel Shear Connectors Used with No Decking ($R_g = R_p = 1.0$) and Normal-Weight Concrete[†]

Connector	Concrete strength f'_c (ksi)		
	3.0	3.5	4.0
1/2" diam × 2" headed stud	9.4	10.5	11.6
5/8" diam × 2-1/2" headed stud	14.6	16.4	18.1
3/4" diam × 3" headed stud	21.0	23.6	26.1
7/8" diam × 3-1/2" headed stud	28.6	32.1	35.5
Channel C3×4.1	10.2 L_c *	11.5 L_c	12.7 L_c
Channel C4×5.4	11.1 L_c	12.4 L_c	13.8 L_c
Channel C5×6.7	11.9 L_c	13.3 L_c	14.7 L_c

[†]AISC Formula (I3-3), Eq. 16.8.5, used for studs and AISC Formula (I3-4), Eq. 16.8.6, used for channels. Studs, A108 Type 2, $F_u^b = 60$ ksi.

* L_c = Length of channel, in.




Figure 16.8.5
Example 16.8.1.

As found from the analysis in Example 16.7.2, the neutral axis is located within the steel section; thus, $C_{max} < T_{max}$. The force in the concrete to be carried by shear connectors is 1714 kips.

The nominal strength Q_n per connector, from Eq. 16.8.5 or Table 16.8.1, is 26.1 kips. The number N of shear connectors required for each half span is

$$N = \frac{1714}{26.1} = 66$$

Use 66— $\frac{3}{4}$ -in.-diam × 3-in. studs per half span.

Connector Design—Elastic Concept for Fatigue Strength

The 1992 AASHTO Specification [1.3] requirements for fatigue are based largely on the work of Slutter and Fisher [16.21]. For fatigue, the *range* of service load shear rather than strength under overload is the major concern. Fatigue strength may be expressed

$$\log N = A + BS_r \quad (16.8.8)$$

where S_r is the range of service load horizontal shear; N is the number of cycles to failure; and A and B are empirical constants. The equation used for design is shown in Fig. 16.8.6.




Figure 16.8.6
Fatigue strength of stud shear
connectors. (From Ref. 16.21)

Since the magnitude of shear force transmitted by individual connectors when service loads act agrees well with prediction by elastic theory, the horizontal shear is calculated by the elastic relation VQ/I . Fatigue is critical under repeated application of service load; thus it is reasonable to determine variation in shear using elastic theory. The spacing of the connectors will vary along the span in accordance with V .

For cyclical load, Eq. 16.8.1 gives

$$V_{sr} = \frac{(V_{\max} - V_{\min})Q}{I} = \frac{\text{Allowable range } \Sigma Z_r}{p} \quad (16.8.9)$$

where p is the connector spacing. AASHTO-6.10.10.1.2 [1.3] gives Eq. 16.8.9 as

$$p \leq \frac{\Sigma Z_r}{V_{sr}} \quad (16.8.10)$$

where V_{sr} = horizontal fatigue shear range per unit length, kip/in.

Z_r = allowable range of load per connector, lb/stud connector

$$= \alpha d^2 \geq \frac{5.5d^2}{2} \quad (\text{AASHTO 6.10.10.2})$$

Σ = indicates the sum of Z_r for connectors at the section is to be used.

d = stud diameter, in.

$$\alpha = 34.5 - 4.28 \log N$$

EXAMPLE 16.8.2

Redesign the shear connectors for the beam of Example 16.8.1 (Fig 16.8.5) using the service load stress fatigue requirement of AASHTO with $\frac{3}{4}$ -in.-diam \times 3-in. stud connectors. Design for 500,000 cycles of loading of live load. Whether or not the beam is shored, only the live load is the cyclical load. Use uniform live load of 3.5 kips/ft, a spacing of 6 ft for beams, a beam span of 45 ft, $F_y = 50$ ksi, and $f'_c = 4$ ksi.

Solution:

(a) Loads and shears. For the fatigue requirement in AASHTO-6.10.10.1.2 only the range of service live load is needed. At the support with full span loaded,

$$V = \frac{1}{2}wL = 0.5(3.5)45 = 78.8 \text{ kips}$$

Using partial span loading of live load,

$$\text{Max } V \left(\text{at } \frac{1}{4} \text{ point} \right) = 3.5(45)(0.75)(0.375) = 44.3 \text{ kips}$$

$$\text{Max } V \left(\text{at midspan} \right) = \frac{1}{8}wL = \frac{1}{8}(3.5)45 = 19.7 \text{ kips}$$




Figure 16.8.7
Shear range diagram and stud
spacing according to elastic
fatigue theory used by
AASHTO-Example 16.8.2.

The envelope showing the *range* of live load shear is given in Fig. 16.8.7. Inclusion of dead load shear would change both V_{\max} and V_{\min} by the same amount at any section along the beam; however, $(V_{\max} - V_{\min})$, that is, the range V_r would not be affected.

(b) Compute elastic composite section properties ($n = 8$) (see Fig. 16.8.5).

Effective slab width $b_E = b_0 = 72$ in.

Element	Effective area, A (sq in.)	Arm from CG of steel beam, y (in.)	Ay (sq in.)	Ay^2 (in. ³)	I_0 (in. ⁴)
Slab, 72(7)/8	63.0	21.5	1355	29,120	257
W36×160	47.0	—	—	—	9760
	110		1355	29,120	10,017

$$I_x = Ay^2 + I_0 = 29,120 + 10,017 = 39,100 \text{ in.}^4$$

$$\bar{y} = \frac{1355}{110} = 12.32 \text{ in.}$$

$$I_{tr} = 39,100 - 110(12.32)^2 = 22,400 \text{ in.}^4$$

$$y_t = 18.0 + 7 - 12.32 = 12.68 \text{ in.}$$

$$y_b = 18.0 + 12.32 = 30.32 \text{ in.}$$

$$S_t = \frac{22,400}{12.68} = 1767 \text{ in.}^3 \quad (\text{concrete at top})$$

$$S_b = S_{tr} = \frac{22,400}{30.32} = 739 \text{ in.}^3 \quad (\text{steel at bottom})$$

Determine the static moment of the effective concrete area about the centroid of the composite section,

$$Q = 63.0(y_t - 3.5) = 63.0(9.18) = 578 \text{ in.}^3$$

(c) Determine the allowable load for $\frac{3}{4}$ -in.-diam \times 3-in. stud connectors. AASHTO-6.10.10.1.2 gives an allowable service load range Z_r , per connector based on fatigue for 500,000 cycles of loading as

$$\begin{aligned} \alpha &= 34.5 - 4.28 \log N \\ &= 34.5 - 4.28 \log(500,000) = 10.1 \end{aligned}$$

$$Z_r = \alpha d^2 = 10.1(0.75)^2 = 5.68 \text{ kips} > \left[\frac{5.5d^2}{2} = 1.55 \text{ kips} \right] \quad \text{OK}$$

The AASHTO allowable values are based on a slip limitation.

(d) Determine spacing of connectors. Use 4 studs across the beam flange width at each location:

$$\Sigma Z_r \text{ for 4 studs} = 4(5.68) = 22.7 \text{ kips}$$

Using Eq. 16.8.10,

$$p = \frac{\Sigma Z_r}{V_{sr}} = \frac{\Sigma Z_r}{(V_{\max} - V_{\min})Q/I}$$

where $I/Q = 22,400/578 = 38.8 \text{ in.}$

$$p = \frac{22.7(38.8)}{(V_{\max} - V_{\min})} = \frac{881}{(V_{\max} - V_{\min})(\text{kips})}$$

The values are computed in the table below and the spacing is determined graphically on the shear diagram of Fig. 16.8.7.

p (in.)	V_r (kips)	p (in.)	V_r (kips)
11	79	20	45
14	61	22	39
17	51		

$V_r = V_{\max} - V_{\min}$

The fatigue service load criterion requires 8% more connectors (68 vs 61 per half span) than the procedure based on strength. ■

16.9 COMPOSITE FLEXURAL MEMBERS CONTAINING FORMED STEEL DECK

Composite flexural members may be made using formed steel deck, as shown in Fig. 16.1.2. The formed metal deck may be placed perpendicular to or parallel with the supporting beam. Furthermore, the beam may actually be an open web joist. Typically, the deck plate varies in thickness from 22 ga. (0.0336 in., 0.853 mm) to 12 ga. (0.1084 in., 2.75 mm). The deck rib height typically is $1\frac{1}{2}$, 2, and 3 in. for spans of, say, 8, 10, and 15 ft. As shown in Fig. 16.1.2, the thickness of the concrete slab above the top of the ribs must be at least 2 in. AISC-I3.2c and the embedment of the stud connectors into the concrete above the top of the ribs must be at least $1\frac{1}{2}$ in.

When the steel deck ribs are perpendicular to the steel beam, the stud strength Q_n may have to be reduced from that given by Eq. 16.8.5 by a reduction factor as explained

earlier. Easterling, Gibbings, and Murray [16.43] provide a study of strength of shear studs in steel deck on composite beams.

Full treatment of formed steel deck supported slab composite beams is outside the scope of this chapter. The reader is referred to Grant, Fisher, and Slutter [16.23], and particularly with regard to LRFD design, to Vinnakota, Foley, and Vinnakota [16.24]. Composite open-web joists have been treated by Tide and Galambos [16.25] and Rongoe [16.26]. Two-way acting composite slabs with steel deck have been treated by Porter [16.29], and design *Specifications and Commentary* [16.27, 16.28] are available from ASCE. The special considerations regarding the design of “stubgirders” are treated by Buckner, Deville, and McKee [16.30].

16.10 DESIGN PROCEDURE—AISC LRFD AND ASD METHODS

The design of composite beams involves providing sufficient plastic strength ϕM_p of the composite section to equal the factored moment. Using rolled W shapes, local buckling ordinarily is not a controlling limit state although h/t_w should be checked when the PNA is in the web, and because the compression flange is attached to the concrete slab lateral-torsional buckling is precluded as a controlling limit state. Thus, it is required that

$$\phi_b M_p \geq M_u \quad (\text{LRFD}) \quad (16.10.1a)$$

$$M_p / \Omega_b \geq M_a \quad (\text{ASD}) \quad (16.10.1b)$$

where $\phi_b = 0.90$ and $\Omega_b = 1.67$ for a composite beam.

In general, the design should be started by assuming the plastic neutral axis (PNA) is within the slab (Case 1—Fig. 16.7.1b). Thus, using Eq. 16.7.5, the required area A_s for the steel section is

$$\text{Required } A_s = \frac{M_u}{\phi_b F_y \left(\frac{d}{2} + t_s - \frac{a}{2} \right)} \quad (\text{LRFD}) \quad (16.10.2a)$$

$$\text{Required } A_s = \frac{M_u}{\frac{F_y}{\Omega_b} \left(\frac{d}{2} + t_s - \frac{a}{2} \right)} \quad (\text{ASD}) \quad (16.10.2b)$$

Typically $a/2$ can be estimated as 1 in. for preliminary design.

In addition to the strength requirement under full dead and live load, AISC-13.1c requires that when temporary shores are not used during construction, the steel section alone must have adequate strength “to support all loads applied prior to the concrete attaining 75% of its specified strength f'_c .” For this condition, local buckling of the beam elements and lateral-torsional buckling must be considered.

16.11 AISC EXAMPLES—SIMPLY SUPPORTED BEAMS

EXAMPLE 16.11.1

Design an interior composite beam for the floor whose plan is shown in Fig. 16.11.1 assuming the beam is to be constructed without temporary shoring. Use 50 ksi, $f'_c = 4$ ksi ($n = 8$), a 4-in. slab, and the AISC LRFD Method.




Figure 16.11.1
Beam framing plan for
Examples 16.11.1 and
16.12.1.

Solution:

(a) Compute factored and service loads.

Loads carried on steel beam:

$$\text{concrete slab, } \frac{4}{12}(0.15)8 = 0.40 \text{ kip/ft}$$

$$\text{beam weight (estimated)} = 0.04 \text{ kip/ft}$$

$$\text{service dead load} = 0.44 \text{ kip/ft}$$

$$\text{factored dead load} = 0.44(12) = 0.53 \text{ kip/ft}$$

Load carried by composite action:

$$\text{service live load, } 0.2(8) = 1.6 \text{ kips/ft}$$

$$\text{factored live load} = 1.6(1.6) = 2.56 \text{ kips/ft}$$

(b) Compute service load and factored load moments.

$$M_D = \frac{1}{8}(0.44)(28)^2 = 43 \text{ ft-kips (service load)}$$

$$M_L = \frac{1}{8}(1.60)(28)^2 = 157 \text{ ft-kips (service load)}$$

$$M_u = \frac{1}{8}(0.53 + 2.56)(28)^2 = 303 \text{ ft-kips (factored)}$$

(c) Select the section. Use Eq. 16.10.2 assuming the PNA (plastic neutral axis) is within the slab. Estimate $a \approx 1.0$ for preliminary selection.

$$\text{Required } A_s = \frac{M_u}{\phi_b F_y \left(\frac{d}{2} + t_s - \frac{a}{2} \right)} \quad [16.10.2a]$$

From Eq. 16.10.2, the design strength $\phi_b M_n$ provided can be computed as A_s times the denominator. For a given value of $(t_s - a/2)$, $\phi_b M_n$ can be tabulated for a steel W section for any given yield stress; such tabulated information is given in the *AISC Manual*. Thus, for the 4-in. slab and estimated a of 1 in.,

$$t_s - \frac{a}{2} = 4 - 0.50 = 3.5 \text{ in.}$$

$$\text{Required } A_s = \frac{303(12)}{0.90(50)(7 + 3.5)} = 7.7 \text{ sq in. (for W14)}$$

$$\text{Required } A_s = \frac{303(12)}{0.90(50)(8 + 3.5)} = 7.0 \text{ sq in. (for W16)}$$

Using *AISC Manual*, Table 3-19 “Composite W Shapes—Available Strength in Flexure” entering with $Y2 = t_s - a/2 = 3.5$ in. and required $\phi M_n = 303$ ft-kips, find

$$\text{W16} \times 26 \quad \phi_b M_n = 327 \text{ ft-kips} \quad A_s = 7.68 \text{ sq in.}$$

$$\text{W14} \times 26 \quad \phi_b M_n = 302 \text{ ft-kips} \quad A_s = 7.69 \text{ sq in.}$$

The tabulated values selected are for the PNA within the slab (that is, $Y1 =$ distance from PNA to top of steel beam $= 0$ in.). When these tables are available, their use will be faster and more accurate than putting estimated d into Eqs. 16.10.2.

(d) Compute the plastic neutral axis location and check strength.

Try W16×26: Properties of the steel section alone are:

$$A_s = 7.68 \text{ sq in.} \quad I_x = 301 \text{ in.}^4 \quad b_f = 5.50 \text{ in.}$$

$$d = 15.70 \text{ in.}$$

Determine effective width of slab:

$$b_E = \frac{1}{4} \text{ of span} = 0.25(28)12 = 84 \text{ in. controls}$$

$$\text{or } b_E = \text{beam spacing} = 8(12) = 96 \text{ in.}$$

The compressive force in the concrete, assuming $a < t_s$, and the tension force in the steel section, are

$$C = 0.85f'_c b_E a = 0.85(4)84a = 286a$$

$$T = A_s F_y = 7.68(50) = 384 \text{ kips}$$

Statics requires

$$C = T$$

$$a = 1.34 \text{ in.} < t_s$$

OK as assumed

The nominal moment strength M_n is

$$M_n = T \left(\frac{d}{2} + t_s - \frac{a}{2} \right)$$

$$M_n = 384 \left(\frac{15.7}{2} + 4.0 - \frac{1.34}{2} \right) \frac{1}{12} = 358 \text{ ft-kips}$$

$$\phi_b M_n = 0.90(358) = 322 \text{ ft-kips} > (M_u = 301 \text{ ft-kips})$$

OK

Note that M_u has been revised to include the correct beam weight.

(e) Check the strength of the steel section to support construction loads (AISC-I3.1c). This check is required when shores are not used. Assume adequate lateral support is provided during construction such that $L_b \leq L_p$ and the section is compact for local buckling; therefore $\phi_b M_n = \phi_b M_p$, and $\phi_b = 0.90$ for the steel section acting noncompositely. There are no AISC-prescribed construction loads. It is prudent to consider

that some of the wet concrete load should be treated as live load, say 50% of it (accomplished by using an average overload factor of 1.4). Further, other construction live load on the order of 20 to 25 psf should be included (20 psf used here).

$$\text{Slab} = 0.40(1.4) = 0.56 \text{ kip/ft}$$

$$\text{Construction} = 0.02(8)1.6 = 0.26 \text{ kip/ft}$$

$$\text{Steel section} = 0.026(1.2) = \underline{0.03} \text{ kip/ft}$$

$$w_u = 0.85 \text{ kip/ft}$$

$$M_u = \frac{1}{8}(0.85)(28)^2 = 83 \text{ ft-kips}$$

$$\phi_b M_p \text{ for W16} \times 26 = 166 \text{ ft-kips} > 83 \text{ ft-kips} \quad \text{OK}$$

(f) Design shear connectors. The compressive force in the slab must be carried by shear connectors,

$$C = 0.85 f'_c b_E a = 0.85(4)84a = 286a = 286(1.34) = 385 \text{ kips}$$

Since $a < t_s$, V_{nh} will be based on the 385 kips, which does equal $T_{\max} = A_s F_y$. Using $\frac{3}{4}$ -in.-diam \times 3-in. headed studs, $Q_n = 26.1$ kips/stud from Table 16.8.1. The number N of connectors required to carry 385 kips is

$$N = \frac{V_{nh}}{Q_n} = \frac{385}{26.1} = 14.8, \text{ say } 15$$

which is the number of connectors required for the region between maximum moment and the support (zero moment location). Thus, 30 studs are needed for the entire span. Using a uniform spacing with two studs at each location, the spacing p required would be

$$p = \frac{L}{N} = \frac{28(12)}{15} = 22 \text{ in.}$$

$$\text{Maximum } p = 8t_s = 8(4) = 32 \text{ in. (AISC-I3.2)}$$

$$\text{Minimum } p = 6(\text{diam}) = 6(0.75) = 4.5 \text{ in. (AISC-I3.2)}$$

Use W16 \times 26 section of A992 steel, along with 30— $\frac{3}{4}$ -in.-diam \times 3-in. headed stud connectors over the entire span, spaced at 22 in. The connectors are to be placed in pairs starting at the support. ■

EXAMPLE 16.11.2

Design an interior composite beam to span 30 ft with a beam spacing of 8 ft, using the minimum number of $\frac{3}{4}$ -in.-diam \times 3-in. stud shear connectors. The slab is 5 in. thick. The beam is to be constructed without shores. The beam must support a ceiling of 7 psf, partitions and other dead load of 25 psf, and live load of 150 psf. Use A572 Grade 50 steel and $f'_c = 3$ ksi ($n = 9$) concrete. Use the AISC LRFD Design Method.

Solution:

(a) Compute factored loads and bending moments. The dead load and moment that must be carried by the steel beam alone during construction are

$$5\text{-in. slab, } \frac{5}{12}(8)0.15 = 0.50 \text{ kips/ft}$$

$$\text{Steel beam (assumed)} = \underline{0.03} \\ 0.53 \text{ kips/ft}$$

$$M_D = \frac{1}{8}(0.53)(30)^2 = 60 \text{ ft-kips}$$

$$M_{u1} = 1.2(60) = 72 \text{ ft-kips}$$

The partition and ceiling dead loads, and the live load that must be carried by the composite section are

$$\text{Live load } 0.15(8) = 1.2 \text{ kips/ft}$$

$$\text{Partitions } 0.025(8) = 0.2$$

$$\text{Ceiling } 0.007(8) = \frac{0.06}{1.46 \text{ kips/ft}}$$

$$M_L = \frac{1}{8}(1.46)(30)^2 = 164 \text{ ft-kips}$$

$$w_{u2} = 1.2(0.25) + 1.6(1.2) = 2.22 \text{ kips/ft}$$

$$M_{u2} = \frac{1}{8}(2.22)(30)^2 = 250 \text{ ft-kips}$$

$$M_u = M_{u1} + M_{u2} = 72 + 250 = 322 \text{ ft-kips}$$

(b) Select the section. One could use Eq. 16.10.2 assuming the PNA (plastic neutral axis) is within the slab and solve for required A_s as illustrated in Example 16.11.1 (part c). Alternatively, it will be simpler to use AISC Table 3-19, "Composite W Shapes—Available Strength in Flexure." Equation 16.10.2 is tabulated for the steel W shapes for various values of Y_2 . Estimate $a \approx 1.0$ for preliminary selection as in Example 16.12.1. For the 5-in. slab,

$$Y_2 = t_s - \frac{a}{2} = 5 - 0.50 = 4.5 \text{ in.}$$

$$\text{Required } \phi M_n = 322 \text{ ft-kips}$$

Find:

$$\text{W16} \times 26 \quad \phi M_n = 356 \text{ ft-kips}$$

$$\text{W14} \times 26 \quad \phi M_n = 330 \text{ ft-kips}$$

The tabulated values selected are for the PNA within the slab (that is, $Y_1 =$ distance from PNA to top of steel beam = 0 in.).

(c) Investigate the W16×26 further. For fully composite action, compute the plastic neutral axis location and check strength.

Try W16×26: Properties of the steel section alone are:

$$A_s = 7.68 \text{ sq in.} \quad I_x = 301 \text{ in.}^4 \quad b_f = 5.500 \text{ in.}$$

$$d = 15.69 \text{ in.}$$

Determine effective width of slab:

$$b_E = \frac{1}{4} \text{ of span} = 0.25(30)12 = 90 \text{ in.} \quad \text{controls}$$

$$\text{or } b_E = \text{beam spacing} = 8(12) = 96 \text{ in.}$$

The compressive force in the concrete, assuming $a < t_s$, and the tension force in the steel section are

$$C = 0.85 f'_c b_E a = 0.85(3)90a = 229.5a$$

$$T = A_s F_y = 7.68(50) = 384 \text{ kips}$$

Statics requires

$$C = T$$

$$a = 1.67 \text{ in.} < t_s$$

OK as assumed

The nominal moment strength M_n is

$$M_n = T \left(\frac{d}{2} + t_s - \frac{a}{2} \right)$$

$$M_n = 384 \left(\frac{15.69}{2} + 5.0 - \frac{1.67}{2} \right) \frac{1}{12} = 384 \text{ ft-kips}$$

$$[\phi_b M_n = 0.90(384) = 346 \text{ ft-kips}] > [M_u = 322 \text{ ft-kips}] \quad \text{OK}$$

The W16×26 section is adequate as a *fully composite section*. However, when a minimum number of shear connectors is desired and only partial composite action is used, the steel section usually must be heavier. Try W16×31 section.

(d) Minimum number of shear connectors required. The maximum spacing p along the span is

$$\text{Maximum } p = 8t_s = 8(5) = 40 \text{ in.} \quad (\text{AISC-I3.2})$$

$$N = \frac{L}{p} = \frac{30(12)}{40} = 9 \text{ spaces}$$

The connectors would be in pairs which would mean 20 connectors for the 30-ft span, with 5 pairs (10 connectors) located between midspan and the end of the beam. When $\frac{3}{4}$ -in.-diam studs are used, 10 connectors provide nominal strength ΣQ_n ,

$$\Sigma Q_n = 10(21.0) = 210 \text{ kips}$$

Since the force in the slab based on connector strength is less than the maximum steel force,

$$T_{\max} = A_s F_y = 9.12(50) = 456 \text{ kips}$$

the plastic neutral axis (PNA) is within the steel section.

(e) Locate plastic neutral axis (PNA) and compute nominal strength. Check if PNA occurs within the flange,

$$\Sigma Q_n = 210 \text{ kips}$$

$$\text{Max force in flange} = t_f b_f F_y = 0.440(5.525)50 = 121.6 \text{ kips}$$

$$T_{\max} - 121.6 = 334.5 \text{ kips} > \Sigma Q_n$$

Thus, PNA is in the web. For equilibrium of internal forces, referring to Fig. 16.11.2, compute the compression force in the web,

$$\Sigma Q_n + C_f + C_w = T_{\max} - C_f - C_w$$

$$210 + 121.6 + C_w = 334.5 - C_w$$

$$2C_w = 2.9 \text{ kips}$$

$$\text{Depth to PNA from inside of flange} = \frac{C_w}{F_y t_w} = \frac{1.45}{50(0.275)} = 0.11 \text{ in.}$$

$$\begin{aligned} \text{PNA from top of slab} &= t_s + t_f + 0.11 \\ &= 5 + 0.44 + 0.11 = 5.55 \text{ in.} \end{aligned}$$




Figure 16.11.2
Example 16.11.2, showing
stress distribution to obtain
plastic neutral axis.

Locate the centroid y_1 of the portion of the steel section in tension measured from the bottom of the steel section,

	Area, A	Arm, y	Ay
W section	9.12	7.94	72.41
Flange	-2.43	15.66	-38.07
Web	-0.03	15.39	-0.45
	<u>6.66 sq in.</u>		<u>33.90 in.³</u>

$$y_1 = \frac{33.90}{6.66} = 5.09 \text{ in.}$$

(f) Compute the nominal moment strength M_n . Since the ΣQ_n representing the strength of the shear connectors used is less than the force in the concrete when there is fully composite action, force ΣQ_n is taken equivalent to $C_c = 0.85 f'_c b_E a$, the concrete force represented by the rectangular stress distribution in the concrete. That means

$$a = \frac{\Sigma Q_n}{0.85 f'_c b_E} = \frac{210}{0.85(3)90} = 0.91 \text{ in.}$$

Referring to Fig. 16.11.2, taking internal moments about the point of action of T_s gives

$$\begin{aligned} \Sigma Q_n: \quad M_{n1} &= \Sigma Q_n(d - 5.09 + t_s - a/2) \\ &= 210(15.88 - 5.09 + 5 - 0.91/2) \frac{1}{12} \\ &= 210(15.33) \frac{1}{12} = 268.3 \text{ ft-kips} \end{aligned}$$

$$\begin{aligned} C_f: \quad M_{n2} &= C_f(d - 5.09 - t_f/2) \\ &= 121.6(15.88 - 5.09 - 0.440/2) \frac{1}{12} \\ &= 121.6(10.57) \frac{1}{12} = 107.1 \text{ ft-kips} \end{aligned}$$

$$\begin{aligned} C_w: \quad M_{n3} &= C_w(d - 5.09 - t_f - 0.11/2) \frac{1}{12} \\ &= 1.45(15.88 - 5.09 - 0.440 - 0.055) \frac{1}{12} \\ &= 1.45(10.30) \frac{1}{12} = 1.2 \text{ ft-kips} \end{aligned}$$

$$\begin{aligned} M_n &= M_{n1} = M_{n2} + M_{n3} \\ &= 268.3 + 107.1 + 1.2 = 376.6 \text{ ft-kips} \end{aligned}$$

$$\phi_b M_n = 0.90(376.6) = 340 \text{ ft-kips}$$

After correcting the dead load for the W16×31 section, the factored moment M_u becomes 321 ft-kips. Thus, $\phi_b M_n > M_u$ and the design is acceptable.

The designer should compare the economics of the W16×26 using connectors to develop a fully composite section with W16×31 using the minimum 20 connectors needed for this span length. To obtain a fully composite section the force to be carried by shear connectors would have been $T_{\max} = A_s F_y = 384$ kips for the W16×26 section. The number of $\frac{3}{4}$ -in.-diam studs needed would be

$$N = \frac{384}{21.0} = 18.3, \text{ say 20 for half the span}$$

Thus, the 40 connectors required for fully composite action can be reduced to 20 using partial composite action with the next heavier section.

(g) Check the strength of the W16×31 steel section to support construction loads (AISC-I3.1c). Refer to discussion in Example 16.14.1, part (e). Assume construction live load consists of 50% of the wet concrete (accomplished by using an average overload factor of 1.4), plus 20 psf for other construction loads.

$$\text{Slab} = 0.50(1.4) = 0.70 \text{ kip/ft}$$

$$\text{Construction} = 0.02(8)1.6 = 0.26 \text{ kip/ft}$$

$$\text{Steel section} = 0.031(1.2) = \frac{0.04}{w_u} \text{ kip/ft}$$

$$w_u = 1.00 \text{ kip/ft}$$

$$M_u = \frac{1}{8}(1.00)(30)^2 = 113 \text{ ft-kips}$$

$$\phi_b M_p \text{ for W16}\times\text{31} = 203 \text{ ft-kips} > 113 \text{ ft-kips}$$

OK

Use W16×31 section ($F_y = 50$ ksi), with 20— $\frac{3}{4}$ -in.-diam connectors over the entire span, spaced at 40 in. ■

16.12 ASD EXAMPLE—SIMPLY SUPPORTED BEAM

EXAMPLE 16.12.1

Redesign the composite beam of Example 16.11.1 (see Fig. 16.11.1) using the AISI ASD Method. The materials are $F_y = 50$ ksi, $f'_c = 4$ ksi ($n = 8$), and a 4-in. slab.

Solution:

(a) Service load bending moments. From Example 16.11.1,

$$M_D = 43 \text{ ft-kips}$$

$$M_L = 157 \text{ ft-kips}$$

(b) Select steel section. Use Eq. 16.11.2b, assuming the PNA is within the slab. Estimate $a = 1.0$ in for preliminary selection.

The required allowable strength $M_a = 43 + 157 = 200$ ft-kips

$$\text{Required } A_s = \frac{M_a}{\frac{F_y}{\Omega_b} \left(\frac{d}{2} + t_n - \frac{a}{2} \right)} \quad [16.11.2b]$$

$$\text{Required } A_s = \frac{200(12)}{\frac{50}{1.67}(7 + 3.5)} = 7.63 \text{ sq in. (for W14)}$$

$$\text{Required } A_s = \frac{200(12)}{\frac{50}{1.67}(8 + 3.5)} = 6.97 \text{ sq in. (for W16)}$$

Using AISC-Table 3-19, "Composite W Shapes-Available Strength in Flexure" with $Y_2 = t_n - a/2 = 3.5$ in. and required $M_n/\Omega = 200$ ft-kips, find

W16×26	$M_n/\Omega = 217$ ft-kips	$A_s = 7.68$ sq in.
W14×26	$M_n/\Omega = 201$ ft-kips	$A_s = 7.69$ sq in.

This is identical to the sections determined by the LRFD Method.

(c) Compute the plastic neutral axis and check allowable strength.

From Example 16.11.1,

$$M_n = 358 \text{ ft-kips}$$

$$M_n/\Omega = 358/1.67 = 214 \text{ ft-kips} > (M_a = 200 \text{ ft-kips}) \quad \text{OK}$$

(d) Check the allowable strength of the steel section to support construction loads. Loads values are obtained from Example 16.11.1.

Slab	= 0.40 kips/ft
Construction	= 0.16 kips/ft
Steel Section	= 0.026 kips/ft
	$w_a = 0.586$ kips/ft

$$M_a = \frac{1}{8}(0.586)(28)^2 = 57.4 \text{ ft-kips}$$

$$M_p/\Omega_b \text{ for W16} \times 26 = 110 \text{ ft-kips} > 57.4 \text{ ft-kips} \quad \text{OK}$$

(e) Designing the shear connectors is identical to the LRFD Method.

Use W16×26 of A992 steel along with 30-3/4-in.-diameter × 3-in. headed stud connectors over the entire span, spaced at 22 in. The connectors are to be placed in pairs starting at support. ■

16.13 DEFLECTIONS

The deflection of a composite beam will depend on whether it is shored or unshored during construction. Creep and shrinkage of the concrete in the slab also affect the result. Calculation of deflection requires obtaining the elastic cracked transformed section moment of inertia I_{tr} for the composite beam, and if unshored, also the elastic moment of inertia of the steel section alone.

When the steel beam is shored from below during the hardening of the concrete slab, the composite section will carry both the dead and live load. However, if the steel beam is *not* shored, the steel beam alone must carry the dead load.

When the construction is *without* shoring, the total deflection will be the sum of the dead load deflection of the steel beam alone and the live load deflection of the composite section.

When shoring provides the support during the hardening of the concrete slab, the composite section resists the entire load. Account should be taken to reflect the fact that concrete is subject to creep under long time load and that shrinkage will occur. This inelastic behavior may be approximated by multiplying the modulus of elasticity ratio n by a time-dependent factor such as two; thus reducing the effective width b_E/n . The result is a reduced moment of inertia I_{tr} to be used for computing the sustained load (dead load) deflection. The live load deflection would be computed using the elastic cracked transformed section moment of inertia.

Because the concrete slab in building construction is normally not too thick (say $t_s \leq 6$ in.) creep deflection is often not considered. The *AISC Specification* [1.15] gives no indication of any concern with creep of a concrete slab in composite construction. However, as discussed in Sec. 7.6, AISC-L3 states "Deflection in structural members and structural systems under appropriate service load combinations shall not impair the serviceability of the structure."

The ACI-ASCE Joint Committee [16.16] recommends using $E_c/2$ as the sustained concrete modulus of elasticity instead of E_c when computing sustained load creep deflection. AASHTO-6.10.1.1b [1.3] uses $E_c/3$ instead of E_c . Such arbitrary procedures can at best give an estimate of creep effects, probably no better than $\pm 30\%$. The steel section, exhibiting no creep, and representing the principal carrying element, ensures that creep problems will usually be minimal.

More accurate procedures for computing deflections to account for creep and shrinkage on composite steel-concrete beams are available in a paper by Roll [16.31], and particularly in *Deformation of Concrete Structures* by Branson [16.32]. Lamport and Porter [16.45] have treated deflection prediction for concrete slabs reinforced with steel decking.

EXAMPLE 16.13.1

Compute the service dead and live load deflections for the composite beam consisting of W16×26 with 4-in. slab designed in Example 16.12.1 (see Fig. 16.13.1).

Solution:

Regardless of whether the selection of the steel section has been done by Load and Resistance Factor Design or by Allowable Strength Design, the deflections must be computed for *service* loads acting on the elastic section.




Figure 16.13.1
Beam cross-section for
Example 16.13.1.

(a) Compute the dead load deflection. From Example 16.11.1, part (a), the service dead load is 0.44 kip/ft, and all must be carried by the steel beam alone when the beam is unshored.

$$\Delta_{DL} = \frac{5wL^4}{384E_sI_s} = \frac{5(0.44)(28)^4(12)^3}{384(29,000)448} = 0.47 \text{ in.}, \text{ say } \frac{1}{2} \text{ in.}$$

The beam can be cambered or the slab can be thickened toward midspan so that this amount of deflection is compensated for during construction.

(b) Compute the live load deflection. From Example 16.11.1, part (a), the service live load is 1.6 kips/ft. This load must be carried by the composite section; thus, the elastic composite moment of inertia is required. Compute composite elastic section properties. Referring to Fig. 16.13.1 determine effective width b_E (ASCE-I3.1).

$$b_E = \frac{1}{4} \text{ of span} = 0.25(28)12 = 84 \text{ in. controls}$$

or

$$b_E = \text{beam spacing} = 8(12) = 96 \text{ in.}$$

The width of equivalent steel is $b_E/n = 84/8 = 10.5$ in. The moment of inertia and elastic section modulus values are computed as follows:

Element	Transformed area A (sq in.)	Moment arm from centroid y (in.)	Ay (in. ³)	Ay^2 (in. ⁴)	I_0 (in. ⁴)
Slab	42.0	9.85	413.7	4075	78.8
W16×36	7.68	0	0	0	301
	<u>49.7</u>		<u>413.7</u>	<u>4075</u>	<u>379.8</u>

$$I_x = I_0 + Ay^2 = 380 + 4075 = 4455 \text{ in}^4$$

$$\bar{y} = \frac{413.3}{49.7} = 8.32 \text{ in. above centroid of W16×26}$$

$$I_{tr} = I_x - A\bar{y}^2 = 4455 - 49.7(8.32)^2 = 1015 \text{ in}^4$$

Often some of the dead load, such as partition loads and other items placed after the concrete slab has cured, acts on the composite section.

$$\Delta_{LL} = \frac{5wL^4}{384E_bI_b} = \frac{5(1.6)(28)^4(12)^3}{384(29,000)1015} = 0.75 \text{ in.}$$

As discussed in Sec. 7.6, it has been traditional to consider that live load deflection exceeding $L/360$ may cause cracking of plaster. On the other hand, the *ACI Code* [16.15] restricts the live load plus creep and shrinkage deflection to a maximum of $L/480$. Thus, in the absence of any specific AISC limitation, a limit of approximately $L/400$ will likely give satisfactory serviceability for the floor system. In this case,

$$\Delta_{\text{limit}} = \frac{L}{400} = \frac{28(12)}{400} = 0.84 \text{ in.} > \Delta_{LL}$$

OK

One may conclude that deflection will not cause concern. Note that $L/400$ is *not* an AISC limit. It is the designer's responsibility to establish any limit.

In the solution above, the full thickness of the slab was assumed to be contributing to the elastic stiffness of the composite beam. However, there is some uncertainty about the thickness of the slab that is actually contributing to the stiffness of the composite beam. The *AISC Manual* adopts a more conservative approach by assuming that the thickness of the concrete slab that is contributing to the strength is also defining the stiffness of the beam. So, regardless of whether the beam is fully composite or partially composite, the elastic stiffness of the composite beam is determined using the depth of the rectangular stress block a . The moment of inertia computed using a for the concrete thickness is defined as the lower bound moment of inertia I_{Lb} , because the actual moment of inertia would be always larger. I_{Lb} can be determined from AISC-Table 3-24 as follows:

$$\begin{aligned}\sum Q_n &= 26.1(15) = 392 \text{ kips} \\ Y_2 &= t_s - \frac{a}{2} = 4 - \frac{1.34}{2} = 3.33 \text{ in.}\end{aligned}$$

Enter AISC-Table-3.20 with these values.

By interpolation: $I_{Lb} = 781 \text{ in.}^4$

$$\Delta_{LL} = \frac{5wL^4}{384E_s I_{Lb}} = \frac{5(1.6)(28)^4(12)^3}{384(29,000)781} = 0.98 \text{ in.} > [\Delta_{\text{limit}} = 0.84 \text{ in.}] \quad \text{NG}$$

The authors believe the "exact" deflection probably falls near the $L/400$ limit. ■

16.14 CONTINUOUS BEAMS

Traditionally on continuous beams the positive moment region has been designed as a composite section and the negative moment region where the concrete slab is in tension as a noncomposite section. However, some composite action has been known to exist in the negative moment region. Continuous composite beams have been studied by Barnard and Johnson [16.33], Johnson, Van Dalen, and Kemp [16.34], Daniels and Fisher [16.35], Hamada and Longworth [16.36, 16.37], and Kubo and Galambos [16.38]. Kubo and Galambos extended the treatment to plate girders (that is, beams having h/t_w exceeding $970/\sqrt{F_y}$).

According to AISC-I3.2b the negative moment strength is determined for the steel section alone. AISC allows for calculating the negative moment strength using the composite section, which accounts for the reinforcement contribution. However to analyze the beam as a composite section, the following conditions must be met:

1. The steel beam is compact and adequately braced.
2. Shear connectors are provided over the support region.
3. The slab reinforcement is within the effective width b_E and properly developed.

When the steel reinforcing bars in the concrete slab are utilized to contribute to composite action, the force developed by such bars must be transferred by shear connectors. The nominal strength developed would be

$$T_n(\text{for } -M \text{ region}) = A_{sr}F_{yr} \quad (16.16.1)$$

$$C_n(\text{for } +M \text{ region}) = A'_sF_{yr} \quad (16.16.2)$$

where A_{sr} = total area of longitudinal reinforcing steel at the interior support located within the effective flange width b_E
 A'_s = total area of longitudinal compression steel acting with the concrete slab at the location of maximum positive moment and lying within the effective width b_E
 F_{yr} = specified minimum yield stress of the longitudinal reinforcing steel

Thus, the nominal strength V_{nh} for which shear connectors must be provided in the negative moment zone is

$$V_{nh} = A_{sr}F_{yr} \quad (16.16.3)$$

In the positive moment zone, when compression steel is included in the computation of composite section properties (plastic neutral axis), the nominal strength V_{nh2} from the compression steel is

$$V_{nh2} = A'_sF_{yr} \quad (16.16.4)$$

The total horizontal shear force between the point of zero moment and the point of maximum moment is the smallest of $(0.85f'_cA_c + V_{nh2})$, A_sF_y , and ΣQ_n . AISC has no specific mention of the compression reinforcement in the positive moment zone; thus, inclusion of V_{nh2} is optional.

As discussed in Sec. 16.7, the usual limit state for composite sections in the positive moment zones is crushing of the concrete at the top of the slab. This assumes no shear connector failure, no longitudinal splitting because of inadequate reinforcing bar development, and no shear failure in the slab. In the negative moment region, the usual limit state is flange local buckling [16.37].

Regarding the lateral-torsional buckling limit state, the usual provisions for noncomposite steel sections apply to the negative moment regions of continuous composite beams. The limits on λ from AISC-B4 for the flange and web local buckling limit states must be applied in the negative moment zone.

EXAMPLE 16.14.1

Compute the plastic neutral axis (PNA) location and the nominal strength M_n for the section of Fig. 16.14.1 subject to negative bending moment. The W12×26 steel section is of A992 steel and the reinforcement in the slab has $F_{yr} = 60$ ksi.

Solution:

(a) Determine the plastic neutral axis location. The concrete slab will be in tension; therefore, none of the concrete is assumed to be effective. The reinforcing bars contribute




Figure 16.14.1
Composite section for
negative bending of Example
16.14.1, including plastic
stress distribution according
to AISC-13.2b.

the nominal tension strength T_{sr} ,

$$T_{sr} = A_{sr}F_{yr} = 10(0.31)60 = 186 \text{ kips}$$

The maximum nominal compression force in the W12 section is

$$C_{\max} = A_sF_y = 7.65(50) = 382.5 \text{ kips}$$

Since C_{\max} exceeds T_{sr} , the PNA is within the steel W12 section. In which case the force equilibrium requirement may be expressed,

$$\begin{aligned} T_{sr} + T_s &= C_{\max} - T_s \\ 2T_s &= C_{\max} - T_{sr} = 382.5 - 186 = 196.5 \\ T_s &= 98.3 \text{ kips} \end{aligned}$$

Assuming that the PNA is within the flange of the W12,

$$\text{From top of flange to PNA} = \frac{T_s}{F_y b_f} = \frac{98.3}{50(6.49)} = 0.30 \text{ in.}$$

The assumption that PNA is within the flange is confirmed since $0.30 < (t_f = 0.38 \text{ in.})$. Thus, the distance PNA from top of slab is

$$\text{PNA} = t_s + 0.30 = 4.0 + 0.30 = 4.30 \text{ in.}$$

(b) Compute the nominal moment strength M_n . Locate the center of gravity y_1 of the compression force C_s in the steel section, measured from the bottom of the steel section,

	Area, A	Arm, y	Ay
W12 section	7.65	6.11	46.74
Flange	-1.95	12.07	- 23.5
	5.7		23.24

$$y_1 = \frac{23.24}{5.70} = 4.08 \text{ in.}$$

Referring to Fig. 16.14.1, taking internal moments about the point of action of C_s gives

$$\begin{aligned} T_{sr}: \quad M_{n1} &= T_{sr} (d - 4.08 + t_s - 2.00) \\ &= 186(12.22 - 4.08 + 4 - 2.00) \frac{1}{12} \\ &= 186(10.14) \frac{1}{12} = 157.2 \text{ ft-kips} \\ T_s: \quad M_{n2} &= T_s (d - 4.08 - 0.30/2) \\ &= 98.3(12.22 - 4.08 - 0.30/2) \frac{1}{12} \\ &= 98.3(7.99) \frac{1}{12} = 65.5 \text{ ft-kips} \\ M_n &= M_{n1} + M_{n2} \\ &= 157.2 + 65.5 = 223 \text{ ft-kips} \\ \phi_b M_n &= 0.90(223) = 201 \text{ ft-kips} \end{aligned}$$

Note that for composite action in the negative moment region, shear connectors must be used throughout the entire region. The required ΣQ_n equals the force T_{sr} in the reinforcement.

When partial composite action is used, ΣQ_n will be less than T_{sr} . In such a case, the PNA location and the nominal moment strength are computed using ΣQ_n instead of T_{sr} . ■

16.15 COMPOSITE COLUMNS

A composite column can be defined as “a steel column fabricated from rolled or built-up steel shapes and encased in structural concrete or fabricated from steel pipe or tubing and filled with structural concrete.” An example of the former is shown in Fig. 16.15.1, where a steel W section is encased in concrete; the concrete must contain longitudinal reinforcing bars and these must be surrounded by lateral ties in the manner of a reinforced concrete column.

The steel section must comprise at least 1% of the total cross-sectional area, otherwise the column must be designed as an ordinary reinforced concrete column. Research by Furlong [16.39, 16.40] and others was reviewed by Task Group 20 of the Structural Stability Research Council, chaired by Furlong [16.41]. This SSRC Task Group Report forms the basis for design of composite columns under AISC-12.

Limitations

In order to qualify as a composite column, the limitations of AISC-II.2 and I2 must be satisfied:

1.
$$A_s \geq 0.01A_g \quad (16.15.1)$$
2. For a concrete encasement:
 - (a) Longitudinal reinforcing bars must be used; load carrying bars must be continuous at framed levels (wherever a beam or slab frames to the column); other longitudinal bars used only to restrain concrete may be interrupted at framed levels.
 - (b) Lateral ties must be used; spacing of ties may not exceed the smallest of 16 longitudinal bar diameter, 48 tie bar diameter, or 0.5 the least dimension of the composite section.
 - (c) Area of lateral ties must be at least 0.009 sq in./in. of bar spacing.
 - (d) The minimum required area of steel for continuous longitudinal reinforcement shall be $0.004A_g$.
 - (e) Clear cover of at least 15 in. is required.
3. Concrete strength f'_c :
 - (a) Normal-weight concrete: $3 \text{ ksi} \leq f'_c \leq 10 \text{ ksi}$
 - (b) Structural lightweight concrete: $3 \text{ ksi} \leq f'_c \leq 6 \text{ ksi}$




Figure 16.15.1
Composite column section;
rolled steel shape encased in
concrete.

4. Maximum yield stress of steel used in strength computations is 75 ksi for either structural steel or reinforcing bars.
5. Minimum wall thickness t for concrete-filled pipe or tubing:
 - (a) For each face width b in HSS rectangular sections:

$$\frac{b}{t} \leq 2.26 \sqrt{\frac{E}{F_y}} \quad (16.15.2)$$

- (b) For outside diameter D in circular sections:

$$\frac{D}{t} \leq 0.15 \sqrt{\frac{E}{F_y}} \quad (16.15.3)$$

Nominal Strength

To account for slenderness effects, the AISC equations for composite columns are based on a modified form of the equations for steel columns in AISC-E. The yield strength becomes a modified strength P_e , and the elastic stiffness of the column is defined by an effective elastic stiffness EI_{eff} defined in what follows.

The resistance and safety factors adopted for composite columns are rather conservative in order to account for the uncertainty of composite columns and the use of ultimate strength of two different materials in defining the capacity. The factors are as follows:

$$\phi = 0.75 \text{ (LRFD)} \quad \Omega = 2.00 \text{ (ASD)}$$

The nominal compressive strength shall be determined according to AISC-I2.1b as follows

1. When $P_e \geq 0.44P_o$

$$P_n = P_o \left[0.658^{\left(\frac{P_e}{P_o}\right)} \right] \quad (16.15.4)$$

2. When $P_e < 0.44P_o$

$$P_n = 0.877P_e \quad (16.15.5)$$

$$\text{where } P_e = \pi^2(EI_{eff})/(KL)^2 \quad (16.15.6)$$

For filled composite columns, AISC-12.2b defines:

$$P_e = A_s F_y + A_{sr} F_{yt} + C_2 A_c f' \quad (16.15.7)$$

where $C_2 = 0.85$ for irregular sections and 0.95 for circular sections

$$EI_{eff} = E_s I_s + E_s I_{sr} + C_3 E_c I_c \quad (16.15.8)$$

$$C_3 = 0.6 + 2 \left(\frac{A_s}{A_c + A_r} \right) \leq 0.9 \quad (16.15.9)$$

For encased composite columns, AISC-I2.1b defines:

$$P_e = A_s F_y + A_{sr} F_{yt} + 0.85 A_c f' \quad (16.15.10)$$

$$EI_{eff} = E_s I_s + 0.5 E_s I_{sr} + C_1 E_c I_c \quad (16.15.11)$$

$$C_1 = 0.1 + 2 \left(\frac{A_s}{A_c + A_s} \right) \leq 0.3 \quad (16.15.12)$$

- where A_c = area of concrete
 A_r = area of longitudinal reinforcing bars
 A_s = gross area of steel shape, pipe, or tube
 E_c = modulus of elasticity of concrete, ksi
 $= (w^{1.5})\sqrt{f'_c}$, where w is the density of concrete in pcf (i.e., 145 pcf for normal-weight concrete) and f'_c is in ksi
 E_s = modulus of elasticity of steel
 F_y = specified minimum yield stress of steel shape, pipe, or tube
 F_{yr} = specified minimum yield stress of longitudinal reinforcing bars
 f'_c = specified 28-day compressive strength of concrete
 I_c = moment of inertia of concrete section
 I_s = moment of inertia of steel shape
 I_{sr} = moment of inertia of reinforcing bars

The *AISC Manual* contains tables for concrete filled HSS sections giving axial strengths ϕP_u and P_n/Ω . Note that $\phi_n = 0.75$ for composite columns.

Composite beam-column design has been treated by Uang, Wattar, and Leet [16.46]. AISC-I4 defines the method of treating composite beam-columns. An interaction curve similar to reinforced concrete needs to be developed, while accounting for the stability requirement of the column. The nominal strength of the section is to be determined using plastic stress distribution or strain compatibility. AISC-I2 is to be used to determine the nominal axial strength of the cross-section, using P_u as determined in AISC-I4.

SELECTED REFERENCES

- 16.1. Ivan M. Viest, Chairman, "Composite Steel-Concrete Construction," Report of the Subcommittee on the State-of-the-Art Survey of the Task Committee on Composite Construction of the Committee on Metals of the Structural Division, *Journal of the Structural Division*, ASCE, **100**, ST5 (May 1974), 1085-1139.
- 16.2. Gottfried Brendel, "Strength of the Compression Slab of T-Beams Subject to Simple Bending," *ACI Journal, Proceedings*, **61**, January 1964, 57-76.
- 16.3. Conrad P. Heins and Horn Ming Fan, "Effective Composite Beam Width at Ultimate Load," *Journal of the Structural Division*, ASCE, **102**, ST11 (November 1978), 2163-2179.
- 16.4. Cesar R. Vallenilla and Reidar Bjorhovde, "Effective Width Criteria for Composite Beams," *Engineering Journal*, AISC, **22**, 4 (Fourth Quarter 1985), 169-175.
- 16.5. Ivan M. Viest, "Review of Research on Composite Steel-Concrete Construction," *Journal of the Structural Division*, ASCE, **86**, ST6 (June 1960), 1-21; Also *Transactions*, ASCE, **126** (1961), Part E, 1191-1123.
- 16.6. William C. Hansell, Theodore V. Galambos, Mayasandra K. Ravindra, and Ivan M. Viest, "Composite Beam Criteria in LRFD," *Journal of the Structural Division*, ASCE, **104**, ST9 (September 1978), 1409-1426; Disc. **106**, ST2 (February 1980), 571-572.
- 16.7. Srinivasa H. Iyengar and Mohammad Iqbal, "Composite Construction," *Building Structural Design Handbook*, Chapter 23. New York: John Wiley & Sons, 1987.
- 16.8. Robert F. Lorenz and Frank W. Stockwell, Jr., "Concrete Slab Stresses in Partial Composite Beams and Girders," *Engineering Journal*, AISC, **21**, 3 (Third Quarter 1984), 185-188.
- 16.9. Robert F. Lorenz, "Understanding Composite Beam Design Methods Using LRFD," *Engineering Journal*, AISC, **25**, 1 (Second Quarter 1988), 35-38.
- 16.10. Robert F. Lorenz, "Some Economic Considerations for Composite Floor Beams," *Engineering Journal*, AISC, **20**, 2 (Second Quarter 1983), 78-81.
- 16.11. Mark C. Zahn, "The Economies of LRFD in Composite Floor Beams," *Engineering Journal*, AISC, **24**, 2 (Second Quarter 1987), 87-92.
- 16.12. S. Timoshenko and J. Goodier, *Theory of Elasticity*. New York: McGraw-Hill Book Company, Inc., 1959, Chap. 6.
- 16.13. Theodore von Kármán, "Die Mittragende Breite," *August-Föppel-Festschrift*, 1924. (See also Collected Works of Theodore von Kármán, Volume II, p. 176.)

- 16.14. John E. Johnson and Albert D. M. Lewis. "Structural Behavior in a Gypsum Roof-Deck System," *Journal of the Structural Division*, ASCE, **92**, ST2 (April 1966), 283–296.
- 16.15. ACI Committee 318 (ACI 318-08). *Building Code Requirements for Reinforced Concrete*. Farmington Hills, MI: American Concrete Institute, 2008.
- 16.16. Joint ASCE-ACI Committee on Composite Construction. "Tentative Recommendations for the Design and Construction of Composite Beams and Girders for Buildings," *Journal of the Structural Division*, ASCE, **86**, ST12 (December 1960), 73–92.
- 16.17. Roger G. Slutter and George C. Driscoll. "Flexural Strength of Steel-Concrete Composite Beams," *Journal of the Structural Division*, ASCE, **91**, ST2 (April 1965), 71–99.
- 16.18. Peter Ansourian and Jack William Roderick. "Analysis of Composite Beams," *Journal of the Structural Division*, ASCE, **104**, ST10 (October 1978), 1631–1645.
- 16.19. Jorgen G. Ollgaard, Roger G. Slutter, and John W. Fisher. "Shear Strength of Stud Connectors in Lightweight and Normal-Weight Concrete," *Engineering Journal*, AISC, **8**, 2 (April 1971), 55–64.
- 16.20. Jay B. McGarraugh and J. W. Baldwin, Jr. "Lightweight Concrete-on-Steel Composite Beams," *Engineering Journal*, AISC, **8**, 3 (July 1971), 90–98.
- 16.21. Roger G. Slutter and John W. Fisher. "Fatigue Strength of Shear Connectors," *Highway Research Record No. 147*, Highway Research Board, 1966, pp. 65–88.
- 16.22. Charles G. Schilling. "Bending Behavior of Composite Hybrid Beams," *Journal of the Structural Division*, ASCE, **94**, ST8 (August 1968), 1945–1964.
- 16.23. John A. Grant, Jr., John W. Fisher, and Roger G. Slutter. "Composite Beams with Formed Steel Deck," *Engineering Journal*, AISC, **14**, 2 (First Quarter 1977), 24–43.
- 16.24. Sriramulu Vinnakota, Christopher M. Foley, and Murthy R. Vinnakota. "Design of Partially or Fully Composite Beams, with Ribbed Metal Deck, Using LRFD Specifications," *Engineering Journal*, AISC, **25**, 2 (Second Quarter 1988), 60–78.
- 16.25. R. H. R. Tide and T. V. Galambos. "Composite Open-Web Steel Joists," *Engineering Journal*, AISC, **7**, 1 (January 1970), 27–36.
- 16.26. James Rongoe. "A Composite Girder System for Joist Supported Slabs," *Engineering Journal*, AISC, **21**, 3 (Second Quarter 1984), 155–160.
- 16.27. ASCE. *Specifications for the Design and Construction of Composite Slabs*. New York: Technical Council on Codes and Standards, American Society of Civil Engineers, 1984.
- 16.28. ASCE. *Commentary on Specifications for the Design and Construction of Composite Slabs*. New York: Technical Council on Codes and Standards, American Society of Civil Engineers, 1984.
- 16.29. Max L. Porter. "Analysis of Two-Way Acting Composite Slabs," *Journal of Structural Engineering*, ASCE, **111**, 1 (January 1985), 1–17.
- 16.30. C. Dale Buckner, Danny J. Deville, and Dean C. McKee. "Shear Strength of Slabs in Stub Girders," *Journal of the Structural Division*, ASCE, **107**, ST2 (February 1981), 273–280.
- 16.31. Frederic Roll. "Effects of Differential Shrinkage and Creep on a Composite Steel-Concrete Structure," *Designing for Effects of Creep, Shrinkage, Temperature in Concrete Structures* (SP-27). Detroit, MI: American Concrete Institute, 1971 (pp. 187–214).
- 16.32. Dan E. Branson. *Deformation of Concrete Structures*. New York: McGraw-Hill Book Company, Inc., 1977.
- 16.33. P. R. Barnard and R. P. Johnson. "Plastic Behavior of Continuous Composite Beams," *Proceedings, Institution of Civil Engineers*, October 1965.
- 16.34. R. P. Johnson, K. Van Dalen, and A. R. Kemp, "Ultimate Strength of Continuous Composite Beams," *Proceedings of the Conference on Structural Steelwork*, British Constructional Steelwork Association, November 1967.
- 16.35. J. H. Daniels and J. W. Fisher. "Static Behavior of Continuous Composite Beams," *Fritz Engineering Laboratory Report No. 324.2*, Lehigh University, Bethlehem, PA, March 1967.
- 16.36. Sumio Hamada and Jack Longworth. "Buckling of Composite Beams in Negative Bending," *Journal of the Structural Division*, ASCE, **100**, ST11 (November 1974), 2205–2222.
- 16.37. Sumio Hamada and Jack Longworth. "Ultimate Strength of Continuous Composite Beams," *Journal of the Structural Division*, ASCE, **102**, ST7 (July 1976), 1463–1478.
- 16.38. Masahiro Kubo and Theodore V. Galambos. "Plastic Collapse Load of Continuous Composite Plate Girders," *Engineering Journal*, AISC, **25**, 4 (Fourth Quarter 1988), 145–155.
- 16.39. Richard W. Furlong. "Strength of Steel Encased Concrete Beam Columns," *Journal of the Structural Division*, ASCE, **94**, ST1 (January 1968), 267–281.
- 16.40. Richard W. Furlong. "AISC Column Design Logic Makes Sense for Composite Columns, Too," *Engineering Journal*, AISC, **13**, 1 (First Quarter 1976), 1–7.
- 16.41. Task Group 20, Structural Stability Research Council. "A Specification for the Design of Steel-Concrete Composite Columns," *Engineering Journal*, AISC, **16**, 4 (Fourth Quarter 1979), 101–115.
- 16.42. IABSE. *Composite Steel-Concrete Construction and Eurocode 4, Short Course Notes*, International Association for Bridge and Structural Engineering, Brussels, 1990, 191 pp.
- 16.43. W. Samuel Easterling, David R. Gibbings and Thomas M. Murray. "Strength of Shear Studs in Steel Deck on Composite Beams and Joists," *Engineering Journal*, AISC, **30**, 2 (2nd Quarter 1993), 44–55.


- 16.44. Mark Andrew Bradford and R. Ian Gilbert. "Composite Beams with Partial Interaction Under Sustained Loads," *Journal of Structural Engineering*, ASCE, **118**, 7 (July 1992), 1871–1883.
- 16.45. William B. Lamport and Max L. Porter. "Deflection Predictions for Concrete Slabs Reinforced with Steel Decking," *ACI Structural Journal*, **87**, September–October 1990, 546–570.
- 16.46. Chia-Ming Uang, Samer W. Wattar, and Kenneth M. Leet. "Proposed Revision of the Equivalent Axial Load Method for LRFD Steel and Composite Beam-Column Design," *Engineering Journal*, AISC, **27**, 4 (4th Quarter 1990), 150–157.
- 16.47. M. D. Rambo-Roddenberry, W. S. Easterling, and T. M. Murray. "Behavior and Strength of Welded Stud Shear Connectors-Data Report," Report No. CE/VPI-02/04, Virginia Polytechnic Institute and State University, Blacksburg, VA, 2002.

PROBLEMS

All problems are to be done according to the AISC LRFD Method or the ASD Method, as indicated by the instructor. All given loads are service loads unless otherwise indicated.

16.1. For the case (or cases) assigned by the instructor, compute the location of the transformed composite section neutral axis and moment of inertia I_{tr} . Refer to the accompanying figure.

Case	Steel section	F_y (ksi)	Slab t_s (in.)	b_E (in.)	f'_c (ksi)	
2	W14×30	60	4	72	3	($n = 9$)
4	W18×60	50	4	84	4	($n = 8$)
5	W24×55	50	4.5	90	4	($n = 8$)
6	W18×50	50	5	72	4	($n = 8$)
7	W18×50	50	4	72	3	($n = 9$)
8	W24×76	50	4.5	72	4	($n = 8$)
9	W24×94	50	4.5	72	4	($n = 8$)
10	W21×62	50	5	96	4	($n = 8$)
11	W21×147	50	4.5	96	4	($n = 8$)



Problems 16.1, 16.2, and 16.3

16.2. For the case (or cases) listed for Prob. 16.1 and assigned by the instructor, compute the location of plastic neutral axis (PNA) measured from the top of the slab, as well as the nominal strength M_n . Assume the sections are *fully composite*. Refer to the accompanying figure.

16.3. For the case (or cases) listed for Prob. 16.1 and assigned by the instructor, select an economical size of headed stud shear connector from Table 16.8.1, determine the total number needed to develop a *fully composite* section for the beam, and specify the spacing. Assume the simply supported beam span equals $4b_E$.


16.4. For the case (or cases) assigned by the instructor, select a *W* section to design a *fully composite* section for span *BD* of the accompanying figure. Assume for simplicity that the slab is the only dead load to be considered. Also, select an economical size of headed stud shear connector from Table 16.8.1, determine the total number needed for the beam, and specify the spacing, to develop a fully composite beam. No shoring is to be used; therefore, assume that during construction wet concrete of 75 psf is live load and that an additional construction live load of 25 psf may act. The final composite beam may not have live load deflection exceeding $L/360$.

Case	Live Load (psf)	F_y (ksi)	Slab t_s (in.)	Span (ft)	Beam Spacing (ft)	f'_c (ksi)	
2	100	60	4	36	8	3	($n = 9$)
4	80	50	4	36	7	4	($n = 8$)
5	80	50	4	40	7	4	($n = 8$)
6	80	50	4	40	7	4	($n = 8$)
8	125	50	4.5	40	8	3	($n = 9$)
9	125	50	4.5	42	8	4	($n = 8$)
10	125	50	4.5	45	8	4	($n = 8$)
11	125	50	5	45	9	4	($n = 8$)
12	125	50	5.5	48	9	4	($n = 8$)

16.5. For the case (or cases) given in Prob. 16.4 assigned by the instructor, select a W section to design a *partially composite* section for span *BD* of the accompanying figure, using the minimum number of $\frac{3}{4}$ -in.-diam headed stud shear connectors. Specify number of studs and the spacing. In addition to the slab dead load, using a ceiling load of 7 psf and partition load of 25 psf. No shoring is to be used; therefore, assume that during construction wet concrete of 75 psf is live load and that an additional construction

live load of 25 psf may act. The dead load deflection before composite action is effective may not exceed $\frac{7}{8}$ in. and composite beam deflection resulting from superimposed dead load (i.e., ceiling and partitions) and live load may not exceed $L/360$.








































16.6. Design a composite encased W shape column to resist a factored axial compression load P_u of 900 kips. The effective length $KL = 12$ ft, $F_y = 50$ ksi for structural steel, and $f'_c = 4.5$ ksi for concrete.



Problems 16.4 and 16.5
Framing plan.

Appendix

TABLE A1 Approximate Radius of Gyration


 $r_x = 0.29h$ $r_y = 0.29b$	 $r_x = 0.42h$ $r_y = 0.42b$	 $r_x = 0.31h$ $r_y = 0.48b$
 $r_x = 0.40h$ $h = \text{mean } h$	 $r_y = \text{same as for 2 L}$	 $r_x = 0.37h$ $r_y = 0.28b$
 $r_x = 0.25h$	 $r_x = 0.42h$ $r_y = \text{same as for 2 L}$	 $r_x = 0.31h$
 $r = \sqrt{\frac{H^2 + h^2}{16}}$ $r = 0.35H_m$	 $r_x = 0.39h$ $r_y = 0.21b$	 $r_x = 0.31h$
 $r_x = 0.31h$ $r_y = 0.31h$ $r_z = 0.197h$	 $r_x = 0.45h$ $r_y = 0.235b$	 $r_x = 0.40h$ $r_y = 0.21b$
 $r_x = 0.29h$ $r_y = 0.32b$ $r_z = 0.18 \frac{h+b}{2}$	 $r_x = 0.36h$ $r_y = 0.45b$	 $r_x = 0.38h$ $r_y = 0.22b$
 $r_x = 0.31h$ $r_y = 0.215b$ $r = b(0.21 + 0.02s)$	 $r_x = 0.36h$ $r_y = 0.60b$	 $r_x = 0.39h$
 $r_x = 0.32h$ $r_y = 0.21b$ $r = b(0.19 + 0.02s)$	 $r_x = 0.36h$ $r_y = 0.53b$	 $r_x = 0.35h$
 $r_x = 0.29h$ $r_y = 0.24b$ $r = b(0.23 + 0.02s)$	 $r_x = 0.39h$ $r_y = 0.55b$	 $r_x = 0.435h$ $r_y = 0.25b$
 $r_x = 0.30h$ $r_y = 0.17b$	 $r_x = 0.42h$ $r_y = 0.32b$	 $r_x = 0.42h$
 $r_x = 0.25h$ $r_y = 0.21b$	 $r_x = 0.44h$ $r_y = 0.28b$	 $r_x = 0.42h$
 $r_x = 0.21h$ $r_y = 0.21b$ $r_z = 0.19h$	 $r_x = 0.50h$ $r_y = 0.28b$	 $r_x = 0.285h$ $r_y = 0.37b$
 $r_x = 0.38h$ $r_y = 0.19b$	 $r_x = 0.39h$ $r_y = 0.21b$	 $r_x = 0.42h$ $r_y = 0.23b$

* J.A.L. Waddel. *Bridge Engineering*, Vol. 1. New York: John Wiley & Sons, Inc., 1916, p. 504. Used by permission.

TABLE A2 Torsional Properties

O = shear center
 G = centroid


J = torsion constant, C_w = warping constant
 I_p = polar moment of inertia about shear center



$$J = \frac{1}{3}(2bt_f^3 + ht_w^3)$$

$$C_w = \frac{I_f h^2}{2} = \frac{t_f b^3 h^2}{24} = \frac{h^2 I_f}{4}$$

$$I_p = I_x + I_y$$




$$J = \frac{1}{3}(b_1 t_f^3 + b_2 t_f^3 + ht_w^3)$$

$$C_w = \frac{t_f h^2}{12} \left(\frac{b_1^3 b_2^3}{b_1^3 + b_2^3} \right)$$

$$e = h \frac{b_1^3}{b_1^3 + b_2^3}$$


$$I_p = I_y + I_x + A y_0^2$$



$$J = \frac{1}{3}(bt_f^3 + ht_w^3)$$

$$C_w = \frac{1}{36} \left(\frac{b^3 t_f^3}{4} + h^3 t_w^3 \right)$$


≈ zero for small t



$$J = \frac{1}{3}(bt_1^3 + ht_2^3)$$

$$C_w = \frac{1}{36} (b^3 t_1^3 + h^3 t_2^3)$$

≈ zero for small t



$$J = \frac{1}{3}(2bt_f^3 + ht_w^3)$$

$$C_w = \frac{t_f b^3 h^2}{12} \left(\frac{3bt_f + 2ht_w}{6bt_f + ht_w} \right) = \frac{h^2}{4} (I_y + A\bar{x}^2 - q\bar{x}A)$$

$$q = \frac{th^2 b^2}{4I_x}$$

A

- Abdel-Sayed, George, 322, 334
 Abolitz, A. Leon, 738, 760
 Adams, Peter F., 284, 333, 622, 623, 635, 664, 665, 769, 790, 791
 Adams, Staley F., 355, 378
 Adhuri, Seshu Madhava Rao, 279, 334
 Agerskov, Henning, 735, 760
 Alameid, Salahuddin, 747, 761
 Ainso, Heino, 738, 760
 AISC 2005 Design Specification for Structural Steel Buildings
 B3 design basis requirements, 442, 673, 803
 B3.24 simple connections, 676
 B4 buckling design requirements, 575, 859
 B6 design requirements, 674
 C1 stability design requirements, 804
 C2 design required strength calculations, 616, 628, 632–635, 643–644, 778, 780, 789, 804
 D2 design tension member requirements, 90
 D3 tension area requirements, 78, 83–85, 91
 E3 compressive strength requirements, 273, 274, 421, 628
 E4 compressive strength requirements, 279, 421–422
 E5 single-axle compression member requirements, 277–278, 421
 E6 built-up compression member requirements, 276–277
 E7 slender elements requirements, 274–275, 277, 313, 318–321, 323, 421, 575
 F1 flexure requirements, 343, 446–447, 628
 F2 doubly symmetric I-shaped requirements, 343, 345, 441, 444, 469, 804
 F3 doubly symmetric I-shaped requirements, 346, 446
 F5 I-shaped member requirements, 536–537, 541–545
 F4 I-shaped member requirements, 472–475, 536–537, 541–545
 F6 I-shaped member requirements, 469
 F9 T-beam requirements, 475–476
 F13.1 hole reduction requirements, 358–359, 366
 F13.2 proportioning limits requirements, 541
 G1 shear requirements, 358–359
 G2 shear requirements, 358, 556–558, 569–570, 572, 573
 G3 tension field action shear requirements, 565–566, 571
 H1 beam-column safety requirements, 375, 627, 644, 804
 H2 beam-column safety requirements, 375
 I1 composite member design requirements, 826
 I2 composite axial member requirements, 828, 829
 I3 composite flexural member requirements, 203, 804, 827, 829, 833, 835, 837, 840–842, 846, 858
 I4 composite combined axial flexural member requirements, 863
 J2.1 groove weld requirements, 203
 J2.2 fillet weld requirements, 201–202, 573
 J2.3 plug and slot weld requirements, 202
 J2.4 weld strength requirements, 201, 205, 207, 209–210, 228–229
 J2.5 combination weld requirements, 208–209
 J3.2 bolt hole size requirements, 78, 96
 J3.3 bolt hole spacing requirements, 122
 J3.4 edge distance requirements, 122–123
 J3.6 tension rod requirements, 96, 727
 J3.8 slip-critical connection requirements, 129–131
 J3.10 hole bearing strength requirements, 120, 122
 J4.2 connections in shear requirements, 209–210
 J4.3 block shear failure modes, 87, 678
 J6 splice connection requirements, 529
 J7 bearing strength connection requirements, 529
 J10 flange and web connection design, 361–364, 574, 712, 714–717, 720
 L3 beam deflection requirements, 351–352
 Ales, Joseph M., Jr., 478, 495
 Alignment charts for effective length (KL), 281–286
 Allen, D. E., 350, 378, 379
 Allowable resistance (R_n), 215
 Allowable strength design (ASD), 38–39, 42–43, 45–46
 AISC specifications, 42–43, 48
 beams, *see* Beams
 bolts, *see* Bolts
 columns, *see* Columns
 connections, *see* Connections
 LRFD compared to, 45–46
 nominal strength (R_n), 43
 safety factor (Ω), 42–43
 tension members, *see* Tension members
 welds, *see* Welds
 Alloy steels, 56
 American Concrete Institute (ACI), 828–829, 864
 American Institute of Steel Construction (AISC)
 allowable strength design (ASD) specification, 38–39, 42–43, 48, 272–273
 beam-column design, 627–663
 Design Guide Series, 736
 frame bracing requirements, 786–789
 load and resistance factor design (LRFD) specification, 40–42, 43–45, 272–273, 361–364
 plastic deformation width/thickness limits (λ_p), 315–316

American Institute of Steel Construction (AISC)
(Continued)

Plastic Design in Steel, 792, 820
plate buckling and post-buckling strengths, 317–323
safety factor (Ω), 42–43
simple shear connections, 676–677
Specification for Structural Steel Buildings, 38–39, 48, 72, 86, 115, 128–129, 276, 294, 321–322, 361, 450, 502, 736, 782, 856
Steel Construction Manual, 48, 81, 284, 736, 741, 746
stiffener design requirements, 714–715
stiffness reduction factors, 284–285
tension-field action design, 564–567
yield stress width/thickness limits (λ_r), 311–315
American Iron and Steel Institute (AISI), 33, 48, 66, 313, 317, 321, 571, 603
compression member specifications, 313, 321
North American Specification for the Design of Cold-Formed Steel Structural Members, 48, 66, 317
Proposed Criteria for Load and Factor Design of Steel Building Structures, 571, 603
American National Standards Institute (ANSI), 22
American Railway Engineering and Maintenance of Way Association (AREMA), 24, 38, 48
American Society for Testing and Materials (ASTM)
A6 specifications, 30, 53–54, 69
A7 steel specifications, 51, 90
A36 steel, 52, 53, 55, 60, 74, 205
A53 pipe steel, 53, 55, 74
A242 high-strength low-alloy steel, 51, 53, 55, 73, 74
A307 carbon steel, bolts, 57, 74, 105, 106, 160, 166
A325 high-strength steel, bolts, 57–58, 74, 105, 106, 109, 112, 159, 160
A373 steel, 51
A441 high-strength steel, 60
A449 quenched and tempered steel, bolts, 57, 74, 105, 106
A490 quenched and tempered alloy, bolts, 57, 58, 74, 105, 106, 109, 160
A500 steel, 53, 55, 74
A501 tubing steel, 55, 74
A502 carbon steel, rivets, 106
A510 steel, 53
A514 alloy steel, 53, 55, 56, 74
A529 steel, 53, 55, 74
A572 high-strength steel, 53, 55, 74
A588 weathering steel, 53, 55, 73, 74, 205
A606 sheet and strip steel, 53, 55, 74
A607 sheet and strip steel, 55
A611 sheet steel, 55
A618 tubing steel, 54, 55, 74
A709 bridge construction steel, 54, 55, 56, 73, 74
A852 quenched and tempered low-alloy plate steel, 54, 55, 56, 74
A913 high-strength low-alloy steel, 54, 55, 56, 75, 205
A992 high-strength low-alloy steel, 54, 55, 74
A1008 high-strength low-alloy steel, cold-rolled, 54, 74
A1011 high-strength low-alloy steel, hot-rolled, 54, 55, 74
alloy properties, 56
carbon steel properties, 52–55
fasteners, 57–58
high-strength low-alloy steel properties, 52–55
structural steel designations, 51–58
American Society of Civil Engineers (ASCE). *See also* ASCE-AASHTO Joint Committees
Ad Hoc Committee on Serviceability Research, 350, 377

Minimum Design Loads for Buildings and Other Structures (7-05 standards), 22, 25–30, 43–45, 48
Specifications for the Design and Construction of Composite Slabs, 847, 864
State-of-the-Art Survey on Composite Construction, 823–824, 833, 863
Task Committee on Structural Safety, 39, 49
Task Committee on Wind Forces, 28, 49
American Standard beams, 30–31
American Welding Society (AWS)
A5.1 SMAW specifications, 58
A5.17 SAW specifications, 58, 59, 182
A5.18 GMAW specifications, 58, 183
A5.20 FCAW specifications, 58, 184
A5.23 SAW specifications, 58, 59, 182
A5.28 GMAW specifications, 58
A5.29 FCAW specifications, 58, 184
A5.5 SMAW specifications, 58
D1.1 specifications, 58, 205
Qualification Test, 198–199
Standard Symbols for Welding, Brazing and Nondestructive Examination, 192, 199, 247
Structural Welding Code, 72, 75, 195–196, 201, 246
welding symbols, 191–193
Aminmansour, Abbas, 644–645, 665
Ammar, Albert R., 487, 496
Ammerman, Douglas J., 676, 757, 758
Anand, S. C., 621, 664
Anderson, John P., 273, 281, 332
Anderson, Katherine E., 579, 603
Angle of rotation (θ), 342–343
Angle of twist (ϕ), 384–385
Angle-shaped beams, 30–31
Angles, 81–82, 678–692
connection strength, 678–692
eccentric shear on, 688–689
flexural deformation and strength, 678–688
holes staggered in, 81–82
tension and shear on, 690–692
weld capacity, 688–692
Antoni, Charles M., 367, 379
Apparao, Tamirisa V. S. R., 487, 496
Arbitrary point-in-time value, 44–45
Area, 77–85, 115–116, 203–204
effective net (A_e), 83–85
effective throat (t_e), 203–204
flaying surface, 204
net (A_n), 77–85
tensile stress, 115–116
welds, 203–204
Aristizabal-Ochoa, J. Dario, 783, 791
Arnold, Peter, 769, 791
ASCE-AASHTO Joint Committees
Design Criteria, 367, 378
Flexural Members, 552–554, 603
Longitudinally Stiffened Plate Girders, 576, 603
ASCE-ACI Joint Committee on Composite Construction, 833, 856, 864
Aslani, Farhang, 276, 334
Assadi, Mahyar, 450, 495
Association of State and Highway Transportation Officials (AASHTO), 23, 26, 38, 48, 839. *See also* ASCE-AASHTO Joint Committees
Astaneh, Abolhassan, 276, 332, 677, 728, 729, 758, 760
Atsuta, Toshio, 625, 665
Austin, Walter J., 435, 494, 609, 619, 664
Avent, R. Richard, 355, 378
Avery, Louie K., 736, 760
Axial compression and bending, 34
Axial tension on bolts, 153–156
Axially loaded members, 215–227, 747–751. *See also* Beam-columns
balanced connections, 220–224

base plates, 747–751
fillet welded, 218–219
groove welded, 215–217
plug welded, 224–227
slot welded, 224–227
Azad, Abul K., 579, 603
Aziznamini, Atorod, 676, 758

B

Baldwin, J. W., Jr., 840, 864
Bansal, J., 442, 494
Baranda, Herman, 367, 379
Barnard, P. R., 858, 864
Barney, George B., 621, 664
Barsom, John M., 61, 66, 72, 75
Barton, M. V., 392, 425
Base plates, 746–753
axial loads, under, 747–751
columns, 746–753
design equation, 749–750
plan dimension, 748
resisting moments, 751–753
thickness, 748–751
Base shear force design method, 28–29
Basler, Konrad, 538, 540, 542, 549, 551, 557, 559–560, 562, 567, 570, 571, 573, 603
Bateman, E. H., 107, 172
Batho, C., 107, 172, 675, 730, 757
Bathon, Leander, 279, 334
Batson, Gordon B., 738, 760
Beam-columns, 34, 375, 609–672, 770–772
AISC-B6 design requirements, 674
AISC-C2 design required strength calculations, 616, 628, 632–635, 643–644
AISC-H1 safety requirements, 375, 627, 644
AISC-H2 safety requirements, 375
AISC design, 627–663
braced frames, 628–632
criteria, 627–632
direct analysis method, 627, 641–643
effective length method, 636–637
first-order method, 643–644
LRFD, 627–628, 644–663
unbraced frames, 632–644
axial compression and, 609–614
biaxial bending, 625–627
braced frames, 628–632
curvature (C_m) values, 615–616
design strength (ϕM_n), 627–628
differential equations for, 610–614
elastic buckling, 770–772
introduction to, 34, 609–610
load and resistance factor design (LRFD), 627–628, 644–663
moment magnification, 614–621, 628–635
braced frames, 628–632
end moments and no joint translation, 617–619
sidesway, 620–621
single curvature without end translation, 614–617
unbraced frames, 632–635
nominal strength (P_n), 621–625
failure by combined bending and torsion, 622–623
interaction equations, 623–625
plane of bending instability, 621–622
slope-deflection equations for, 770–772
transverse loading, 612–614
equal end moments without, 614
unequal end moments without, 612
uniform, 613
unbraced frames, 632–644
AISC stability analysis, 635–644

- amplified first-order elastic analysis, 634–635
- second-order analysis, 635
- Beam line, 675–676
- Beams, 30–34, 339–382, 409–415, 449–501, 502–533, 536–538, 692–696, 709–740, 824–825, 835–837, 847–861
 - AISC-F1 flexure specifications, 343
 - AISC-F2 specifications, 343, 345
 - AISC-F3 specifications, 346
 - AISC-F13 hole reduction specifications, 358–359, 366
 - AISC-G1 rolled specifications, 358–359
 - AISC-G2.19 rolled specifications, 358
 - AISC-J10 flange and web connection design, 361–364
 - AISC-L3 deflection specifications, 351–352
- allowable strength design (ASD), 349–350, 359–361, 362–366, 414–415, 449
 - biaxial bending, 375–376
 - concentrated loads on rolled beams, 362–366
 - I-shaped beams, 449
 - laterally supported beams, 349–350
 - local web yielding, 362
 - safety factor (Ω), 349
 - shear on rolled beams, 359–361
 - sidesway web buckling, 364–366
 - torsion in laterally stable beams, 414–415
 - web crippling, 363
- American standard, 30–31
- angle-shaped, 30–31
- bending, 34, 339–340, 367–377
 - axial compression and, 34
 - biaxial, 374–377
 - flexural theory, 340, 367–374
 - section modulus (S), 340
 - symmetrical shapes, 339–341,
- bracing, 441–442, 478–489
- buckling, 363–366, 449–501
 - lateral-torsional, 449–501
 - sidesway web, 363–366
- cantilever, 451
- channel-shaped, 30–31
- collapse mechanism, 342–343, 504–511
- composite, 823–824, 847, 855–858
- composite construction, 824–825, 847–861
- concentrated loads applied to, 361–366
- continuous, 450–451, 502–533, 858–861
- continuous connections, 709–740
 - beam-to-beam, 739–740
 - beam-to-column, 709–739
- deflection, 824–825, 855–858
- flexural theory, 367–383
- girders, 25–26, 339
- girts, 33, 339
- holes in, 366–367
- hollow structural steel (HSS), 30–31
- I-shaped, *see* I-shaped members
- joists, 33, 34 (photo), 339
- lateral support, 432–435
- lateral stability of, 340–350, 409–415
- limbs, 33, 339
- load and resistance factor design (LRFD), 343–349, 358–359, 361–364, 409–414, 442–449, 491–494
 - biaxial bending, 375
 - compact sections, 343–345
 - concentrated loads on rolled beams, 361–364
 - design strength (ϕM_n), 343–344
 - I-shaped beams, 442–449, 491–494
 - laterally supported beams, 343–349
 - local web yielding, 361–362
 - noncompact sections, 344–345
 - partially compact sections, 346
 - shear on rolled beams, 358–359
 - sidesway web buckling, 363–364
 - slender sections, 346–347
 - torsion in laterally stable beams, 409–414
 - web crippling, 362–363
- moment gradient factor (C_b), 446–449, 450–451
- plastic deformation width/thickness ratio limits (λ_p), 345
- plastic neutral axis (PNA), 835–837
- plastic strength (moment, M_p), 341–343, 502–511
- plate girders compared to, 536–538
- purlins, 339
- rolled, 355–366
- seated, 692–705
- sections, types of, 32–33
- serviceability of, 350–355
- shapes, 30–31
- shear on, 355–361
- shear strength (V_n), 358
- simply supported, 847–855
- splices, 529–531
- stringers, 339
- structural steel, 30–34
- tee-shaped, 30–31
- torsion in, 409–415
- wide-flange (W), 30–32, 341
- yield stress width/thickness ratio limits (λ_y), 344
- Beam-to-beam connections, 739–740
- Beam-to-column connections, 709–739
 - column-web direct, 738–739
 - end-plate, 735–738
 - prying action, 727–735
 - split-beam tee, 727–735
 - stiffeners, 712–727
 - AISC requirements for, 714–715
 - compression regions, 712–715
 - horizontal, 712–719
 - plates, 719–727
 - tension regions, 715–719
 - vertical, 719–724
- Bearing stiffeners, 574–575
- Bearing strength (R_n), 117, 119–121, 132
 - bolt design, 117, 119–121, 132
 - holes, 119–121
- Bearing-type connections, 105, 108, 123–127, 133–134, 140–142, 157–158
 - ASD method, 133–134
 - combined shear and tension of, 157–158
 - LRFD method, 123–127, 157–158
 - ultimate strength (plastic) analysis, 140–142
- Beaulieu, Denis, 635, 665
- Becker, Herbert, 310, 333
- Beedle, Lynn S., 47, 49, 112, 172, 262, 263, 331, 332, 504, 511, 531, 621, 664, 705, 707, 708, 711, 735, 759, 792, 819, 820
- Bend-buckling, 546–552
- Bending
 - analogy between torsion and flexure, 401–406
 - beam-columns, 621–623, 625–627
 - beams, 339–340, 367–377, 442–449, 469–470
 - biaxial, 374–377, 490–494, 625–627
 - combined planes (unsymmetrical sections), 370, 388
 - flexural theory, 340, 367–374
 - neutral axis inclination, 370–374
 - principal axes for, 370
 - moments (M), 167–172, 303–305, 367–368
 - plane of, instability in, 621–622, 623
 - plate girder strength, 567–569
 - plate stability and, 301–305
 - shear combined with, 567–569
 - shear stresses due to, 387–388
 - stress (σ), 369–370
- strong-axis, 442–449
- symmetrical shapes, 339–340
- tension from, 167–172
- torsion, 387–388, 401–406, 622–623
 - flexure analogy for, 401–406
 - reliability index (β) values, 404–405
 - thin-wall open cross sections, 387–388, 623
- weak-axis, 469–470
 - xz plane only, 369–370, 387–388
 - yz plane only, 369, 388
- Bennett, Richard M., 90, 102
- Bennetts, Ian D., 711, 759
- Bernoulli's theorem, 27
- Bertwell, W., 683, 758
- Bessemer process, 21
- Biaxial bending, 374–377, 490–494
 - allowable strength design (ASD), 375–376
 - I-shaped sections, 490–494
 - lateral-torsional buckling, 490–494
 - load and resistance factor design (LRFD), 375, 491–494
 - nominal strength, 374
- Bijlaard, Frans S. K., 711, 759
- Bijlaard, P. P., 80, 101
- Birkemoe, Peter C., 677, 678, 758
- Birstiel, Charles, 625, 665
- Bjorhovde, Reidar, 86, 101, 273, 332, 627, 665, 676, 758, 824, 863
- Bleich, Friedrich, 257–258, 272, 296, 311, 331, 419, 421, 435, 576, 768, 782
- Block shear strength (ϕR_n), 85–87, 676
 - AISC-J4.21 modification, 87, 676
 - reduction coefficient (U), 86–91
- Blodgett, Omar W., 185, 199, 249, 256, 331, 579, 656, 694, 729–731, 745, 750, 757
- Bolted joints, *see* joints
- Bolts, 57–59, 115–118, 709–710
 - ASTM (carbon steel) properties, 57, 74, 75, 105, 106
 - ASTM (high-strength) steel properties, 57–73, 74, 105, 106, 108, 109, 110, 111, 112
 - ASTM (quenched and tempered) steel properties, 57, 74, 105, 106
 - ASTM (quenched and tempered) alloy properties, 57, 74, 105, 108, 109, 110
 - allowable tensile design (ASD) method, 115–116
 - bearing-type connections, 105–114
 - safety factor, 11, 102
 - shear-tension connections, 124–127, 134–135
 - axial tension of, 114–116
 - bearing strength of, 117, 119–121, 132
 - bearing-type connections, 105, 108, 123–127, 133–134, 140–142, 157–158
 - combined shear and tension of, 157–158, 166–172
 - eccentric loads, 166–172
 - eccentric shear, 135–152
 - elastic (vector) analysis, 136–139
 - plastic (ultimate strength) analysis, 139–142
 - single-line fasteners, 146–152
 - failure modes, 116
 - galvanized high-strength, 57–58
 - high-strength, 105, 107–108, 109–111, 153–156
 - history of, 107–108
 - installation methods, 108, 110, 111–113
 - alternative design, 113
 - calibrated wrench, 111
 - direct tension indicator, 113
 - nut rotation, 110, 113
 - snug tight, 111, 113
 - turn-of-the-nut, 108, 111–112
 - interference-body, 107
 - interrupted-rib, 107

Bolts (Continued)

- load and resistance factor design (LRFD), 117–127, 129–131, 144–146, 157–166
 - bearing-type connections, 123–127, 157–158
 - bolt spacing, 121, 123
 - combined shear and tension of, 157–166
 - design strength (ϕR_n), 117–121
 - eccentric shear and, 144–146
 - edge distance, 122
 - end distance (L_e), 121–122
 - hole bearing strength, 119–121
 - resistance factor (ϕ), 118
 - slip-critical connections, 129–131, 158–166
- load-deformation relationship, 140–141
- machine, 57
- nominal strength (R_n), 113–117, 132
- prestress effects on, 153
- pretension requirements, 109–111
- ribbed, 107
- shear strength (F_{nv}), 116, 118–119, 132
- slip-critical joints, *see* Slip-critical connections
- split-tee connections, 729–730
- structural, 105–178
- tensile stress area, 115–116
- tension strength, 729–730
- unfinished, 107
- Boresi, Arthur P., 62, 383, 386, 424
- Borgsmiller, J. T., 736, 760
- Bower, John E., 367, 378
- Bowman, M. D., 761
- Box girder, 536
- Braced frames, 280, 628–632, 768, 769–770, 772–774, 782–789, 819. *See also* Frames
 - bracing requirements, 782–789
 - effective length (KL), 280, 766
 - elastic buckling, 772–777
 - elastic stability of, 768
 - moment magnification, 628–632
 - multistory, 819
 - plastic hinges, 789
 - slope-deflection method of analysis, 772–774
 - strength of, 769–770
- Bracing, 441–442, 478–489, 782–789
 - AISC requirements or, 786–789
 - axial strength and stiffness, 488
 - beam stability, 483–488
 - diagonal, 785–786
 - elastic columns and beams, 478–483
 - frames, 782–789
 - inelastic range requirements, 441–442
 - inelastic steel beams, 488–489
 - lateral design, 478–489
 - nodal, 484–485, 787
 - point, 478–483
 - relative, 483–484, 787
 - spring constant (β), 783
 - stiffener members for, 783–785
 - stiffness required from, 782–783
- Bradford, Mark Andrew, 450, 495, 623, 664, 842, 865
- Brady, G. W., 80, 101
- Brandes, J. L., 725, 760
- Brandt, G. Donald, 142, 172, 228, 246
- Branson, Dan E., 856, 864
- Brendel, Gottfried, 824, 863
- Brennan, Paul J., 367, 379
- Bresler, Boris, 579, 603
- Bridge, Russell Q., 286, 334, 478, 495
- Britannia Bridge, 21
- Brittle fracture, 66–71
 - dynamic loading effects, 69
 - lamellar tearing, 69, 70–71
 - multiaxial stress effects, 67–69
 - temperature effects, 67
- thickness effects, 69
- welding effects, 68–69
- Brockenbrough, Roger L., 61, 64, 75, 694, 759
- Brown University, dome roof, 35 (photo)
- Brown, Jack H., 676, 757
- Brozzetti, Jacques, 676, 758
- Buckling. *See also* Lateral-torsional buckling
 - AISC provisions for plate strength, 317–323
 - allowable strength design (ASD), 449, 465–469
 - beams, 372–366, 431–501
 - bending, 546–552
 - coefficient (k), 308
 - columns, *see* Columns
 - compression members, 323–331
 - critical stress (F_{cr}), 266, 308
 - design of members affected by, 323–331
 - Engesser's modulus theories, 257–258, 258–260
 - elastic, 254–256, 305–311, 435–439, 554–557, 769–777
 - coefficient (k), 308, 556
 - columns, 254–256
 - differential equations for, 435–439
 - Euler's theories for, 254–256
 - plates, 308–311
 - pure shear, under, 554–557
 - slope-deflection method of analysis, 770–777
 - stiffness coefficient (ϕ), 770–772
 - transverse load (q), 305–306
 - flanges, 537–541, 542–545
 - frames, 769–777
 - history of, 254–256
 - inelastic, 257–261, 284–286, 440–442, 557–558, 769
 - adjustment factor (τ_a) of alignment, 284–286
 - double modulus theory, 258–260
 - effective length (KL), adjustment for, 284–286
 - frames, 769–777
 - lateral bracing requirements, 440–442
 - pure shear, under, 557–558
 - Shanley concept for, 260–261
 - tangent modulus theory, 257–258
 - lateral-torsional, 431–501, 538
 - limit states, 444–449, 537–541
 - load, 256
 - load and resistance factor design (LRFD), 421–424, 442–449, 451–465
 - local provisions for design, 323–331
 - plate girders, 537–541, 541–552, 554–558
 - moment-strength reduction (h/t_w), 546–552
 - nominal moment strength (M_n), 541–552
 - nominal shear strength (τ_{cr}), 554–558
- plates, *see* Plates
- sidesway web, 363–366
- slenderness parameter (λ_c), 272, 309–311
- torsional, 418–424
- torsional-flexural, 623
- vertical, 538–541
- warping rigidity (EC_w), 58
- webs, 537, 546–552
- Buckner, C. Dale, 847, 864
- Buettner, Donald R., 705, 706, 707, 759
- Building codes, 38, 828
- Building Structural Design Handbook*, 26, 28, 48
- Burgett, Lewis B., 355, 378
- Butler, Lorne J., 207, 228, 246
- Butt joints, 179, 186
- C**
- Cal, C. S., 625, 665
- Call, Steven M., 677, 758
- Canadian Structural Commentaries*, 26, 48
- Cantilever beams, 451
- Carbon steels, 52–55
- Carpmael, H., 179, 245
- Carskaddan, Philip S., 552, 603
- Carter, C. J., 693, 694, 761
- Carter, Charles J., 386, 425
- Cast iron, structural uses, 21
- Castagno, L., 182–183, 246
- Castiglioni, Carlo A., 273, 332
- Cayci, M. A., 80, 101
- Celebi, N., 623, 664
- Chan, Peter W., 367, 379
- Chang, F. K., 386, 425
- Channel sections, 30–31, 386, 389, 470–472
 - beams, 30–31
 - lateral-torsional buckling, 470–472
 - torsion in, 386, 389
- Charpy V-notch test, 61
- Chen, Min-Tse, 406, 425
- Chen, Wai-Fah, 273, 276, 277, 332, 334, 619, 626, 626, 627, 634, 635, 664, 665, 676, 711, 713, 738, 757, 759, 760, 761, 768, 790, 791
- Cheng, Jung-June R., 677, 678, 758
- Cheong-Siat-Moy, Franfois, 622, 625, 664, 665, 769, 783, 790, 791, 820
- Chesson, Eugene., 80, 83, 101, 158, 173
- Chiang, Kah Ching, 128, 172
- Chinn, James, 355, 378
- Chong, Chooi K., 363, 378
- Chong, Ken P., 579, 603
- Chopra, Anil K., 28, 29, 33, 50
- Chow, Hsueh-Lien, 777, 791
- Christopher, Richard, 711, 735, 759
- Chu, Kuang-Han, 391, 418, 425, 777, 791
- Chuenmei, Gue, 279, 333
- Circular sections, torsion in, 385
- Clark, J. W., 435, 451, 472, 494, 495
- Clarke, M. J., 478, 495
- Clip angles, 678
- Clough, R. W., 28, 33, 50
- Coaxing, 72
- Coburn, Seymour, 73, 75
- Cochrane, V. H., 79–80, 101
- Code of Standard Practice for Steel Buildings and Bridges*, 482
- Coel, Joseph, 711, 735, 759
- Coffin, Charles, 179
- Cold work process, 65–66
- Cold-Formed Steel Design Manual*, 31, 48
- Cold-formed steel shapes, 31
- Collapse mechanism, 47, 342–343, 504–511
 - continuous, statically indeterminate beams, 504–511
 - laterally stable beams, 342–343
- Colson, Andre, 676, 758
- Columns, 257–300, 431–432, 478–483, 574–579, 709–739, 746–753, 861–863
 - allowable strength design (ASD), 292–293
 - axially loaded, 286–292
 - base plates, 746–753
 - bearing stiffeners, 574–575
 - bracing, 478–483
 - buckling, 254–268, 284–286, 431–432
 - Euler elastic, 254–256
 - inelastic, 257–261, 284–286
 - lateral-torsional, 431–432
 - strong axis, 266–268
 - weak axis, 265–266
 - built-up sections, 276
 - composite, 861–863
 - connector spacing, 276–277
 - continuous beam-column connections, 709–711
 - critical stress (F_{cr}), 266, 271–275
 - double-angle sections, 275–276

- effective length (KL), 279–286
 alignment charts, 281–286
 braced frames, 280
 inelastic behavior, 284–286
 unbraced frames, 281
 Engesser's modulus theories, 257–258, 258–260
 Euler's critical load, 256
 latticed, 294–300
 load and resistance factor design (LRFD),
 274–279, 286–292
 axial compression and, 275, 276, 286–292
 design strength ($\phi_c P_n$), 274
 reduction factor (Q), 274–275
 rolled (W, S, and M) shapes, 286–292
 non-symmetrical sections, 279
 residual stress, 261–271
 restraint factor (G), 284
 safety factor (Ω), 292
 Shanley concept for, 260–261
 shear effect, 293–296
 single-angle sections, 277–279
 strength, 256–257, 263–274, 279–283
 axial loads, varied, 273–274
 buckling and, 257, 265–268
 curves, 271–274
 effective length (KL), 279–286
 effective modulus and, 264–265
 nominal (P_n), 272–273
 parabolic equation, 271–274
 residual stress and, 263–271
 slenderness parameter (λ_c), 272
 slenderness ratio (KL/r), 256–257, 263–264
 tee-sections, 275–276
 tubular sections, 277
 web direct connections, 738–739
 wide-flange (H-shaped) sections, 261–263
Composite beams, 823–824, 847, 855–858
 AISC design for, 847
 deflection (Δ), 855–858
 equivalent width, 823–824
 plastic neutral access (PNA), 847
Composite construction, 822–866
 advantages and disadvantages, 826
 AISC-I1 design requirements, 826
 AISC-I2 axial member requirements, 828, 829
 AISC-I3 flexural member requirements, 203,
 804, 827, 829, 833, 835, 837, 840–842,
 846, 858
 AISC-I4 combined axial and flexural member
 requirements, 863
 American Concrete Institute (ACI) Code,
 828–829, 864
 ASCE State-of-the-Art Survey on Composite
 Construction, 823–824, 833, 863
 beams, 824–825, 835–837, 847–861
 composite action, 824–825
 composite beams, 823–823, 847, 855–858
 composite columns, 861–863
 continuous beams, 858–861
 deflection (Δ), 824–825, 855–858
 design procedures, 847–855
 ASD, 847–855
 design strength ($\phi_b M_p$), 847
 LRFD, 847–854
 safety factor (Ω_b), 349, 847
 effective width (b_E) for, 826–828
 flanges, 826–827
 girders, 822, 827–828
 elastic section (E) properties, 828–831
 effective section modulus, 829–831
 uncracked transformation moment of
 inertia (I_n), 830
 formed steel deck, 823, 846–847
 fully composite sections, 837–841
 history of, 822–824
 nominal moment strength (M_n), 833–837
 partially composite sections, 841–842
 plastic neutral access (PNA), 833–837, 847
 service load (q) stresses, 831–833, 838–839
 shear connectors, 823, 837–846
 shored, 831
 simply supported beams, 847–855
 slabs, 824, 834–835, 855–858
Compression members, 31–32, 254–338
 AISC-E3 specifications, 273, 274
 AISC-E4 specifications, 279
 AISC-E5 specifications, 277–278
 AISC-E6 specifications, 276–277
 AISC-E7 specifications, 274–275, 277, 313,
 318–321, 323
 AISI specifications, 313, 321
 axially loaded, 286–292
 buckling, *see* Buckling
 columns, 257–300
 critical stress (F_{cr}), 266, 271–275, 308, 312–313
 nominal strength (P_n), 272–273, 317–318
 parabolic curves, 272–273
 plastic deformation width/thickness limits
 (λ_p), 315–316
 plates, 301–331
 residual stress, 261–263, 263–271
 shear effect, 293–296
 slenderness parameter (λ_c), 272, 309–311
 stability, 271–274, 301–308
 strength, 256–257, 263–271, 308–311, 317–323
 types of, 31–32
 uniform, 305–308, 308–311
 yield stress width/thickness limits (λ_r), 311–315
Concrete members, *see* Composite construction
Connections, 276–277, 408, 529–531, 673–765.
See also AISC specifications
 angle strength, 678–692
 beam line, 675–676
 beam-to-beam, 739–740
 beam-to-column, 709–739
 bolted, *see* Joints
 column base plates, 746–753
 column connector spacing, 276–277
 continuous, 709–740
 end-plate, 735–738
 fully restrained (FR), 408, 673
 partially restrained (PR), 408, 674–675
 plate girders, *see* Plate girders
 rigid-frame knees, 740–746
 seated beam, 692–705
 shear, 676–692
 simple, 408, 673–674, 676–692
 splices, 529–531, 753–757
 split-beam tee, 727–735
 stiffeners, 712–719
 triangular bracket plates, 705–709
 welded, *see* Joints
Connectors, *see* Shear connectors
Considere, A., 256, 257–258, 331
Continuous beams, 450–451, 502–533, 858–861
 AISC specifications, 502
 allowable strength design (ASD), 527–528
 composite construction, 858–861
 elastic analysis, 525–528
 introduction to, 502
 lateral-torsional buckling, 450–451
 load and resistance factor design (LRFD),
 511–526
 plastic analysis, 511–524
 plastic strength, 502–511
 splices, 529–531
 statically indeterminate, 502–511
Continuous connections, 709–740
 beam-to-beam, 739–740
 beam-to-column, 709–739
Conventional frame construction (simple or
 partially restrained, PR), 408
Cooper, Peter B., 367, 379, 554, 576, 603
Cornell, C. Allin, 41, 49
Corner joints, 188
Corrosion resistance, 51, 73–74
Cracks in welds, 1180
Craig, E., 182, 246
Crane girders, impact provisions for, 25–26
Crawford, Sherwood F., 135, 140, 142, 172
Creep, 65, 855
Critical stress (F_{cr}), 266, 271–275, 308, 312–313
Cross-sectional members, 31, 32, 76
Cross-sectional shape factor (ξ), 341
Cruz, Ernesto F., 29, 50
Cuk, Peter E., 623, 664
Culver, Charles G., 625, 665
Curtis, Larry E., 736, 760
Curves, 271–274, 302–305, 446–449, 450–451,
 615–616
 beam-column curvature (C_m) values, 615–616
 column strength, 271–274
 lateral-torsional buckling, 446–449, 450–451
 moment gradient factor (C_b), 446–449, 450–451
 plate bending moments (M) and, 302–305
D
Dagher, H., 279, 334
Dalry, Ronald H., 693, 759
Daly, Michael J., 367, 379
Daniels, J. Hartley, 769, 790, 791, 820, 858, 864
D'Apice, M. A., 576, 603
Darwin, David, 367, 379
Daugherty, Brian K., 367, 379
Davenport, Alan G., 28, 49
Dauids, W., 279, 334
Davies, J. Michael, 427, 496
Davison, J. Buick, 676, 757
Dawe, John L., 342, 247, 554, 603
Dawson, Ralph G., 322, 334
de Buen, Oscar, 733, 791
De Jongh, A. E. R., 197, 172
de Vries, Karl, 435, 494
Dead (D) loads, 22, 41
Dead loads, 22
Deep beams, *see* Plate Girders
Deflection (Δ), 350–353, 766–768, 824–825,
 855–858
 beams, 824–825
 composite beams, 855–858
 drift (lateral), 766–768
 serviceability of beams, 350–353
 slabs and, 855–858
Deformation (Δ), 140–141, 207, 678–688
 angle connection strength, 678–688
 flexural, 678–688
 load relationships, 140–141, 207
 welds, 207–214
Delta girder, 536
Der-Avanesian, Norire Gara-Verni, 367, 379
Design, 19–21, 28–29, 38–47, 601–602
 allowable strength design (ASD), 38–39,
 42–43, 45–46
 base shear force method, 28–29
 building codes, 38
 factors of safety, 42–46
 first-order second-moment reliability
 methods, 39
 limit states, 39
 load and resistance factor design (LRFD), 39,
 40–47
 philosophies of, 38–42
 principles, 19–20
 procedure, 20–21

- Design (*Continued*)
 sketch, 601–602
 specifications, 38
 steel structures, 19, 21
- Design Criteria, ASCE-AASHTO Joint Committee on, 367, 378
- Design strength (ϕR_n), 39–40, 89–90, 117–121, 207–214, 283, 343–344, 627–628, 847. *See also* Nominal strength (R_n)
 AISC-J2.23 specifications for, 208–209
 beam-columns (ϕM_n and ϕP_n), 627–628
 beams ($\phi_p M_p$), 343–344, 847
 bearing, 119–121
 bolts, 117–121
 columns ($\phi_c P_n$), 274
 load and resistance factor design (LRFD), 39–40
 shear (ϕR_{nw}), 118–119, 210–211
 tension members, 89–90
 tension, 119
 welds, 207–214
- Designing with Steel Joists, Joist Girders, Steel Deck, 33, 48
- Deville, Danny J., 847, 864
- DeWolf, John T., 164, 166, 173, 490, 496, 747, 750, 753, 761
- Diagonal bracing, 785–786
- Diets, Gordon R., 689, 759
- Dillenbeck, V. R., 182–183, 246
- Direct analysis method of design, 641–643
- Disque, Robert O., 284, 333, 677, 758
- DLH-series joists, 33
- Dobbs, M. W., 417, 425
- Dohrenwend, C. O., 490, 496
- Donnelly, J. A., 200, 246
- Double-angle column sections, 275–276
- Douty, Richard T., 711, 735, 759
- Downs, Tom, 625, 665
- Drift (Δ), 48, 766–768
- Driscoll, George C., 711, 738, 759, 760, 769, 790, 791, 819, 820, 833, 840, 864
- Driver, Robert G., 409, 425
- Drucker, D. C., 80, 101
- Duan, Lian, 276, 334, 625, 634, 665
- Ductility, 60
- Ductility transition temperature, 61
- Dumontail, Pierre, 283, 334
- Dux, Peter F., 451, 495
- Dynamic loads, 24–25, 69
- E**
- Earthquake loads (E), 28–30, 41
- Easley, John T., 487, 496
- Easterling, W. Samuel, 83, 102, 840, 847, 864
- Eccentric loads, 166–172, 241–245
 bolted connections, 166–172
 initial tension from, 167–172
 lines of welds designed for, 243–245
 plane of welds, applied to, 241–245
- Eccentric shear, 135–152, 227–241, 688–689
 angle connections, 688–689
 bolted connections, 135–152
 elastic (vector) analysis, 136–139, 234–241
 line treatment of welds, 236–237
 LRFD and, 144–146
 single-line fasteners, 146–152
 strength (plastic) analysis, 139–142, 227–234
 welded connections, 227–241, 688–689
- Edge joints, 188
- Effective length (KL), 279–286, 450–451, 636–637, 766, 777
 alignment charts, 281–286
 beam-column method of design, 636–637
 cantilever beams, 451
 continuous beams, 450–451
 frames, 280–281, 766, 777
 inelastic column behavior, 284–286
 lateral-torsional buckling, 450–469
 nonuniform moments, 450
 unbraced members, 450–469
- Effective net area (A_e), 83–85
- Effective throat (t_e) dimensions, 203–204
- Effective width (b_E) for, 826–828
 composite construction, 826–828
 flanges, 826–827
 girders, 827–828
- El Darwish, I. A., 386, 425
- Elastic (vector) analysis, 136–139
- Elastic analysis, 525–528
 ASD method, 527–528
 LRFD method, 525–526
- Elastic buckling, *see* Buckling
- Elastic range, 60
- Elastic section properties, 828–831
 composite construction, 828–831
 effective modulus, 829–831
 uncracked transformation moment of inertia (I_{tr}), 830
- Electrodes for welding, 58–59, 179, 181–182, 204–205
 AWS specifications, 58–59
 base metal matching, 193, 204–205
 coatings, 179, 181–182
- Electroslag welding (ESW), 184
- Electroslag welding (ESW), 184–185
- Elgaaly, M., 279, 334, 363, 378
- Ellifrit, Duane S., 421, 425, 475, 496
- Ellingwood, Bruce, 26, 28, 41, 48, 49, 350, 377, 378
- El-Tayem, Adel A., 279, 333
- End moments in beam-columns, 612, 614
- End-plate connections, 735–738
- Energy method for plastic analysis, 509–511, 800–803
- Energy-of-distortion yield criterion, 62–63
- Eney, William J., 386, 391, 425
- Engesser, F., 256, 257–258, 258–260, 331
- English, Gordon W., 622, 664
- Epstein, Howard I., 86, 101
- Equilibrium method for plastic analysis, 504–509, 793–800
- Ermopoulos, John C., 274, 332
- Errera, Samuel J., 487, 496
- Estes, Edward R., Jr., 792, 820
- Estuar, F. R., 262, 332
- Euler, Leonhard, 254, 256, 258, 331
- Eurocode 22, 824, 864
- Evick, Donald R., 414, 425
- F**
- Factored loads, 40, 44–45, 90, 118
- Factors of safety (FS), 42–45
- Failure modes of bolted connections, 116
- Fan, Horn Ming, 824, 863
- Fastener steels, 57–58
- Fasteners, 57–58, 105–107, 113–117, 146–152, 153–156. *See also* Bolts
 ASTM properties, 57–58, 106
 axial tension on, 153–156
 eccentric shear, 146–152
 high-strength bolts, 105
 nominal strength (R_n), 113–117
 ribbed bolts, 107
 rivets, 106–107, 108–109
 single-line, 146–152
 types of (photo), 106
 unfinished bolts, 107
 Fatigue strength, 71–72
- Faustino, Norberto L., 158, 173
- Felton, Lewis P., 417, 425
- Fenn, R., 199, 246
- Fielding, D. J., 576, 603
- Field-welded connections, 192, 193, 690
- Fillet welds, 189, 190, 200–203, 205–207, 209–214, 218–219. *See also* Welds
 allowable resistance (R_w), 215
 along edges, 201–202
 axially loaded members connected by, 218–219
 design shear strength (ϕR_{nw}), 210–211
 design strength (ϕR_n), 209–212
 effective throat (t_e), 201, 202, 204
 end returns, 203
 lap joints, 205–206
 limitations, 200–203
 load-deformation relationship, 207
 maximum effective size, 201–202, 212–214
 minimum effective length, 202
 minimum size, 201
 nominal strength (R_n), 205–207
- First-order methods of design, 39, 47–48, 643–644
- Fisher, Gordon P., 487, 496
- Fisher, James M., 33, 48, 350, 379, 478, 495
- Fisher, John W., 69, 77, 83, 101, 108, 112, 113, 140, 172, 185, 246, 712, 728, 735, 840, 843, 847, 858, 864, 864
- Fixed-base frames, 778–782
 moment magnification, 779–782
 primary bending moments, 778–779
- Flanges, 366–367, 537–541, 542–545, 573, 575, 581–602, 716–719, 730–731, 826–827. *See also* Wide-flange (W) shapes
 bending, stiffeners for, 716–719
 buckling, 537–541, 542–545
 composite construction using, 826–827
 effective width (b_E), 826–827
 holes, 366–367
 limit states, 537–541
 nominal moment strength (M_n), 542–545
 plate girders, 537–541, 542–545, 581–602
 proportions, 582–602
 size changes, 581–582
 slenderness ratio limits λ_p and λ_r , 545
 stiffeners for connections, 573, 575, 716–719
 thickness in split-tee connections, 730–731
- Flaws, 71–72
- Fleischer, Walter H., 579, 603
- Fletcher, Thomas, 180
- Flexural Members, ASCE-AASHTO Task Committee on, 552–554, 680
- Flexural theory, 340, 367–374
- Fling, Russell S., 747, 761
- Floor Vibrations Due to Human Activity, 350
- Flux core arc welding (FCAW), 180, 183–184
- Foley, Christopher M., 847, 864
- Fortunko, C. M., 199, 246
- Fouché, Edmond, 180
- Framed steel structures, 34–36
- Frames, 280–281, 628–644, 676–692, 740–746, 766–791, 792–821
 AISC-C2 design required strength calculations, 628, 632–635, 643–644, 778, 780, 789
 AISC design for, 619–644
 beam-columns, 628–644, 770–772
 braced, 280, 628–632, 768, 772–774, 782–789
 bracing, 782–789
 buckling, 769–777
 elastic, 769–777
 frame strength, 769–770
 inelastic, 769
 slope-deflection method of analysis, 770–777
 stiffness coefficient (ϕ), 770–772

comparison of braced and unbraced, 766–769
 drift (lateral deflection, Δ), 766–768
 effective length (KL), 280–281, 766, 777
 fixed-base, 778–782
 gabled, 797
 load and resistance factor design (LRFD), 803–819
 moment magnification, 628–635, 779–782
 plastic analysis, 792–819
 plastic hinges, 789–790
 rigid, 792–746
 one-story, 792–819
 multistory, 769, 819–820
 rigid-frame knees, 740–746
 sidesway, 768–769, 816
 simple shear connections, 676–692
 stability, 768–769, 777–782
 elastic, 768–769
 primary bending moments, 777–782
 sway magnifier B_2 , 780–781
 unbraced, 281, 632–644, 768–769, 774–777, 789–790
 Frazier, Donald J., 281, 286, 334
 Friction reduction factor (k_f), 158, 160
 Friction-type connections, *see* Slip-critical connections
 Frost, Ronald W., 367, 379, 540, 552, 603
 Fukunoto, Yushi, 450, 495, 623, 664
 Fully restrained (FR) moment connections, 408, 673
 Furlong, Richard W., 861, 864

G

Gaiotti, Regina, 769, 790
 Galambos, Theodore V., 41, 44, 49, 256, 261, 276, 277, 279, 281, 284, 331, 332, 333, 334, 339, 343, 350, 377, 414, 425, 434, 435, 440, 441, 478, 488–489, 490, 494, 495, 554, 603, 621, 623, 624, 627, 664, 665, 769, 782, 790, 791, 819, 820, 824, 833, 847, 858, 863, 864
 Galanakis, Ioannis, 26, 49
 Galvanized high-strength bolts, 57–58
 Ganett, J. H., Jr., 694, 759
 Gas metal arc welding (GMAW), 180, 182–183
 Gaylord, Charles N., 373, 379, 490, 491, 496, 536, 603
 Gaylord, Edwin H., Jr., 373, 379, 490, 491, 496, 536, 603, 769, 791
 Geard, George, 310, 349
 Gee, James M., 333, 419, 421, 435, 615, 713
 Geske, Kurt H., 305, 333
 Geschwindner, Louis F., 783, 785, 791, 818
 Gibbins, David R., 847, 844
 Gieyer, Paul M., 26, 49
 Gilbert, R. Ian, 842, 865
 Gillett, Paul E., 677, 758
 Gilmer, Michael I., 677, 678, 758
 Ginters, 25–26, 199–200, 339, 534–608, 822, 827–828
 beam, 339
 box, 536
 composite construction using, 822, 827–828
 crane, 25–26
 delta, 536
 effective width (b_E), 827–828
 hybrid, 536, 552–554
 plate, 199–200, 534–608
 Giroux, Lisa Gonzales, 83, 102
 Girs, 33, 339
 Gieczowski, Marian A., 623, 664
 Glaeser, Ernst C., 295, 333
 Godfrey, H. J., 60, 75, 362, 378, 557, 603
 Goel, Subash C., 276, 279, 332, 334
 Goldberg, John E., 391, 406, 425, 769, 790, 819, 820

Golden Gate Bridge, suspension bridge, 37 (photo)
 Goodier, J. N., 392, 425, 826, 863
 Goverdhan, Arvind, 676, 757
 Graham, J. D., 362, 378, 711, 712, 715, 719
 Grant, John A., Jr., 847, 864
 Gravity loads, 22, 44, 48
 Green, Deborah L., 754, 761
 Green, Lloyd F., 677, 689, 758
 Griffis, Lawrence G., 350, 379
 Griffiths, John D., 735, 746, 760
 Grodin, Gilbert Y., 101
 Groove welds, 188–189, 203, 204–205, 207–209, 215–217. *See also* Welds
 axially loaded members connected by, 215–217
 complete joint penetration (CJP), 188, 204, 208
 design strength (ϕR_n), 208–209
 effective throat (t_e), 203
 load and resistance factor design (LRFD), 207–209
 nominal strength (R_n), 204–205
 partial joint penetration (PJP), 189, 208
 Grundy, Paul, 711, 759
 Guide to Design Criteria for Bolted and Riveted Joints, 77, 83, 101, 108, 120
 Guide to Stability Design Criteria for Metal Structures, 261, 273, 331, 283, 293–294, 295, 450–451, 470, 472, 564, 576, 609, 620, 625, 768, 782, 820
 Gupta, Ajaya K., 677, 678, 758
 Gurfinkel, German, 282, 333

H

Haaijer, Geerhard, 39, 49, 276, 309, 311, 332, 333
 Hage, Sven E., 635, 665
 Hajjar, Jerome F., 769, 777, 790, 791
 Hall, Dann H., 273–274, 332
 Hall, Preston M., 246
 Halldorsson, Ottar P., 769, 791
 Hamada, Sumio, 858, 859, 864
 Hangers, 95
 Hansell, William C., 824, 833, 863
 Hanson, Robert D., 276, 332
 Hardash, Steve G., 86, 101
 Harichandran, Ronald S., 284, 334
 Haris, Ali A. K., 769, 790
 Harstead, Gunnar A., 625, 665
 Hart, Willard H., 529, 531
 Hartmann, A. J., 440, 456, 478, 488, 494, 495
 Hassan, Kamal, 281, 334
 Hatfield, Frank J., 350, 378
 Hattori, Ryoji, 450, 495
 Hattrup, J. S., 435, 494
 Hauck, George F., 621, 664
 Hechtman, Robert A., 435, 494, 676, 757
 Heins, Conrad P., Jr., 386, 409, 414, 425, 824, 863
 Hendrick, Alan, 736, 760
 High-strength bolts, 57–58, 105, 107–108, 109–111, 153–156
 ASTM properties of, 57–58, 105, 106, 109
 axial tension on, 153–156
 hexagon (hex), 109
 pretension requirements, 109–111
 proof load, 110–111
 High-strength low-alloy steels, 52–55, 73
 Highway bridge loads, 23–24
 Hill, H. N., 451, 470, 472, 495
 Holby, E., 70, 75
 Holes, 77–82, 119–122, 366–367
 AISC-D3.2 tension area specifications, 78, 91
 AISC-F13.1 reduction specifications, 358–359, 366
 AISC-J3.2 size specifications, 78, 96
 AISC-J3.3 spacing specifications, 122

AISC-J3.4 edge distance specifications, 122
 AISC-J3.10 bearing strength specifications, 120, 122
 angles, 81–82
 beams, 366–367
 bearing strength, 119–122
 bolt, 119–121
 dimension of, 78
 flange, 366–367
 gages for angles, 81
 long-slotted, 78
 oversized, 78
 short-slotted, 78
 staggered, 79–82
 standard, 78–79
 tension members, 77–82
 web, 367
 Hollow structural steel (HSS) beams, 30–31
 Homogeneous sections, torsion in, 384–386
 Hopper, Bruce E., 738, 760
 Hoptay, Joseph M., 738, 760
 Hornby, David E., 677, 758
 Horne, M. R., 619, 622, 664
 Hotchkiss, John G., 386, 391, 392, 408–409, 425
 Hot-formed steel shapes, 30–31, 51–52, 70
 Huang, Horng-Te, 735, 760
 Huang, J. S., 711, 712, 759
 Huber, A. W., 262, 263, 331
 Huber-von Mises-Hencky yield criterion, 60
 Hybrid girder, 536, 552–554

I

I-shaped members, 30–32, 336, 391–411, 434–435, 442–449, 469–470, 472–475, 490–494, 536–537
 AISC-F2 specifications, 444, 469
 AISC-F3 specifications, 446
 AISC-F4 specifications, 472–475
 AISC-F6 specifications, 469
 allowable strength design, 449
 beams, 30–32, 434–435
 biaxial bending, 490–494
 elastic range of, 444–447
 lateral-torsional buckling, 434–435, 440–443, 469–470, 472–475, 490–494
 limit states, 444–449, 536–537
 load and resistance factor design (LRFD), 442–443, 491–494
 non-symmetric, 472–475
 plastic deformation (yieldness) ratio limit, λ_p , 445
 plastic moments, M_p , 445, 440–443
 pure Saint-Venant's torsion, 386, 390–392
 strength of order uniform moment, 434–435
 strong-axis bending, 440–443
 torsional stresses in, 390–400
 warping torsion, 392, 393
 weak-axis bending, 469–471
 yield stress (tensile) ratio limit, λ_t , 445
 Impact, I , 24–26
 ASCE 7 provisions, 25–26
 AASHTO factor, 25
 Inadequate weld joint penetration, 196
 Incomplete weld fusion, 196
 Instantaneous center of rotation, 139–140, 801–803
 Intermediate transverse stiffeners, 569–573
 International Association for Bridge and Structural Engineering (IASBE), 824, 882
 International Building Code (IBC), 29–30, 50
 Ioannides, Socrates A., 676, 757
 Iqbal, Mohammad, 824, 863
 Itoh, Yoshito, 450, 495

Iwankiw, Nestor R., 615, 664
Iyengar, Srinivasa H., 824, 863

J

Jeffrey, Paul K., 735, 760
Jensen, Cyril D., 362, 378, 699, 711, 712, 715, 719, 725, 759
John Hancock Center, Chicago, 52 (photo)
Johnson, C. Philip, 677, 678, 758
Johnson, John E., 72, 75, 824, 864
Johnson, R. P., 858, 864
Johnson, Robert B., 391, 425
Johnston, Bruce G., 61, 64, 75, 256, 260–261, 262, 263, 271, 284, 295, 331, 332, 333, 362, 378, 386, 391, 392, 414, 424, 425, 511, 531, 623, 664, 676, 677, 689, 751, 757, 758
Joints. *See also* Connections
 bolted, 83–84, 105, 108, 128–152, 157–166, 276
 allowable strength design (ASD), 132–135
 bearing-type joints, 105, 108, 123–127, 133–134, 157–158
 combined shear and tension of, 157–166, 166, 172
 eccentric loads on, 166–172
 eccentric shear, 135–152
 load and resistance factor design (LRFD), 123–127, 129–131
 load transfer at, 88–89
 slip-critical, 105, 108, 109–111, 128–131, 132–133, 134–135, 143–144, 158–166
 tension members, 83–84
 reduction coefficient (U), 83–85
 resistance factor (ϕ), 118, 207–209
 safety factor (Ω), 132, 208–209, 214
 welded, 84–85, 186–188, 207–245
 allowable strength design (ASD), 214–215
 axially loaded members, 215–227
 butt, 179, 186
 corner, 188
 eccentric loads on, 241–245
 eccentric shear and, 227–241
 economic factors for, 199–200
 edge, 188
 lap, 187, 205–206
 load and resistance factor design (LRFD), 207–214
 quality of, 193–196
 tee, 187
 tension members, 84–85
Joists, 33, 34 (photo), 339
Jolissaint, Donald E., Jr., 406, 425
Jombock, J. R., 435, 494
Jones, J. E., 199, 246
Julian, O. J., 282, 777

K

K-factors, 282, 283
K-series joists, 33
Kahn, Alber, 769, 790
Kalyanaraman, V., 322, 334
Kamalvand, Hassan, 622, 624, 664
Kaminsky, Edmund L., 621, 664
Kane, Thomas, 228, 246
Kapp, Richard H., 738, 760
Kaufman, E. J., 70, 75
Kavanagh, T. C., 282, 333
Kemp, A. R., 858, 864
Kempner, Leon, Jr., 279, 334
Kennedy, D. J. Laurie, 39, 49, 228, 247, 409, 425, 678, 758
Kennedy, John B., 279, 333
Ketter, Robert L., 511, 531, 619, 621, 624, 664
Khabbaz, R. N., 362, 378, 711, 712, 715, 719

King, W. S., 769, 791
Kirby, Patrick A., 676, 757
Kishi, N., 676, 757
Kitipornchai, Sriwat, 279, 333, 440, 451, 494, 495
Klingner, Richard, 450, 494
Klippstein, K. H., 185, 246
Knees, 740–746
 curved haunch, 746
 rigid-frame, 740–746
 shear transfer in, 741–746
 square, 741–746
 straight haunch (tapered), 746
Knostman, Harry D., 367, 379
Korn, Alfred, 769, 790
Korol, Robert M., 322, 334
Kreps, Robert R., 747, 761
Kriegh, James D., 677, 758
Krishnamurthy, N., 735, 736, 760
Kubo, Gerald G., 362, 378, 386, 391, 392, 425
Kubo, Masahiro, 858, 864
Kukreti, Anant R., 736, 760
Kulak, Geoffrey L., 77, 83, 101, 108, 135, 140, 142, 172, 207, 228, 242, 246, 247, 554, 603, 712, 728, 735, 754, 761
Kuo, John T. C., 386, 425
Kussman, Richard L., 367, 379

L

Lamellar tearing, 69, 70–71, 72
Lampert, William B., 856, 865
Lansing, Warner, 414, 425
Lap joints, 187, 205–206
Larrabee, C. P., 73, 75
Larson, J. W., 367, 379
Lateral displacement (Δ), 48
Lateral-torsional buckling, 431–501
 allowable strength design (ASD), 449, 465–469
 beams, 432–435, 450–451
 biaxial bending, 490–494
 bracing, 441–442, 478–489
 channels, 470–472
 columns, 431–432
 continuous beams, 450–451
 effective length, 450–469
 elastic, 435–439
 inelastic, 440–442
 I-shaped sections, 434–435, 442–449, 469–470, 472–475, 490–494
 lateral support, 432–434
 load and resistance factor design (LRFD), 442–449, 451–465
 moment gradient factor (C_b), 446–449, 450–451
 SSRC Guide recommendations, 450–451, 470, 472
 tee sections, 475–478
 weak-axis bending, 469–470
 zee sections, 472
Lathrop, R. P., 711, 735, 759
Latticed columns, 294–300
 batten or lacing plates for, 295–296
 design of, 296–300
 shear effect, 294–296
Lawrence, L. S., 282, 777
Lay, Maxwell G., 316, 333, 440, 441, 478, 488–489, 494, 495
Lee, Seng-Lip, 277, 332, 621, 664
Leet, Kenneth M., 863, 865
Leffler, Robert E., 367, 379
Lehigh University studies, 538, 576, 840
LeMessurier, William J., 635, 665, 769, 790
Leon, Roberto T., 676, 757, 758
Lesik, D. F., 228, 247
Leu, Keh-Chun, 625, 665
Levi, Victor, 769, 790, 791
Lew, H. S., 26, 28, 48
Lewis, Albert D. M., 826, 864
Lewis, Brett A., 677, 758
LH-series joists, 33
Liapunov, Sviatoslav, 769, 790
Libove, Charles, 276, 332
Limit states, 39, 77–78, 444–449, 536–541
 flange buckling, 537–541
 I-shaped sections, 444–449, 536–537
 plate girders, 536–537
 serviceability, 39
 slip, 129
 tension members, 77–78
 web buckling, 537
Lin, Fung J., 295, 333, 414, 425
Lin, Jihshya, 676, 757
Lin, Philip H., 391, 414, 425
Lin, T. Y., 579, 603
Lind, Niels C., 769, 790
Lindsey, Stanley D., 676, 757
Lintels, 33, 339
Liu, X. L., 625, 665
Live (L) loads, 22–24, 41
Live loads, 22–24
Load and resistance factor design (LRFD), 39–47, 803–819
 advantages of, 47
 AISC specification, 40–42
 ASD compared to, 45–46
 beams, *see* Beams
 bolts, *see* Bolts
 columns, *see* Columns
 compression members, *see* Columns; Plates
 design strength (ϕR_n), 39–40
 factors of safety, 42–46
 joints, *see* Joints
 one-story frames, 803–819
 overload factor (γ), 39, 40
 resistance factor (ϕ), 40, 43–44
 tension members, *see* Tension members
 welds, *see* Welds
Load-deformation relationship, 140–141, 207
Load effects (Q), 39–41, 44
Load transfer at tension connections, 88–89
Loads
 ASCE 25 factored load Combinations 41, 42
 axial and bending combined, *see* Beam-columns
 axial applied to members, 215–227, 747–751
 buckling, 256
 concentrated applied to beams, 361–366
 cyclical, 844
 dead (D), 22, 41
 dynamic, 24–25
 earthquake (E), 28–30, 41
 eccentric, 166–172
 effect (Q), 39–40, 41–42
 Euler critical, 256
 factored, 40, 44–45, 90
 frequency distribution, 40
 gravity, 22, 44, 48
 highway bridges, 23–24
 impact (I), 24–26
 live (L), 22–24, 41
 proof, 110–111
 rain or ice (R), 41
 service, 41, 831–833
 snow (S), 26, 41
 static, 24–25
 structural design and, 21–30, 38–47
 torsional, 406–409
 transverse, 305–306, 612–614
 uniform distributed live values, 23
 wind (W), 27–28, 41

- Longinow, Anatole, 418, 425
 Longitudinal stiffeners, 575–577
 Longitudinally Stiffened Plate Girders, ASCE-
 AASHTO Task Committee on, 576, 603
 Longworth, Jack, 858, 859, 864
 Loomis, Kenneth M., 228, 246
 Lorenz, Robert F., 824, 826, 842, 863
 Lothers, John E., 406, 425
 Lu, Le-Wu, 281, 333, 622, 624, 664, 769, 782,
 790, 791, 819, 820
 Lue, Tony, 421, 425
 Lui, Eric M., 373, 283, 332, 334, 627, 635, 665,
 768, 769, 790
 Luttrell, Larry D., 487, 496
 Lutz, LeRoy A., 478, 495
 Lyse, Inge, 362, 378, 386, 391, 424, 557, 603,
 693, 759
 Lytle, K. A., 182, 246
- M**
- MacDonald, Bruce D., 711, 759
 MacGregor, James G., 41, 49, 635, 665
 Machine bolts, 57
 Madison Square Garden, cable-suspended roof,
 37 (photo)
 Madugula, Murty K. S., 279, 333, 334
 Mains, R. M., 725, 760
 Malik, Lincoln, 677, 758
 Mandell, James A., 367, 379
 Mann, Allan P., 736, 760
 Mansouri, Abdulwahab H., 355, 378
 Manual for Railway Engineering, 38, 48
 Maquoi, René, 273, 332
 Marino, Frank J., 354, 355, 378
 Marsh, James W., 30, 50
 Martensite, 56
 Massey, Campbell, 440, 451, 478, 494, 495
 Massonnet, Charles E., 504, 531, 609, 619, 623,
 624–625, 664, 792, 820
 Matz, Charles A., 284, 333
 Maximum lifetime value, 44–45
 McCauley, Robert D., 676, 757
 McDermott, John F., 316, 334
 McGarraugh, Jay B., 840, 864
 McGuire, Peter J., 451, 495
 McGuire, William, 80, 101, 386, 424, 711, 735,
 759, 782
 McKee, Dean C., 847, 864
 McMullin, Kurt M., 677, 758
 McNamara, Robert J., 635, 665
 McVinnie, William W., 769, 791
 Medland, Ian C., 478, 495
 Mehlinger, Vincent, 769, 791
 Mehta, Kishor C., 28, 49
 Melchers, Robert E., 736, 760
 Merchant, W., 769, 791
 Merritt, Frederick S., 511, 531
 Metal inert gas welding (MIG), 183
 Miazga, G. S., 228, 247
 Michalos, James, 625, 665
 Milkuchin, P. T., 415, 425
 Milek, William A., 529, 531
 Mill Test Report, 186
 Miller, Eugene W., 716, 759
 Minimum Design Loads for Buildings and Other
 Structures (ASCE 25), 22, 26–30, 43–45, 48
 Miranda, Constancio, 623, 664
 Miskoe, W. L., 246
 Moment magnification, 614–621, 628–635, 779–782
 braced frames, 628–632
 end moments and no joint translation, 617–619
 fixed-base frames, 779–782
 sidesway, 620–621
 single curvature without end translation, 614–617
 unbraced frames, 632–635
 Moments (M)
 bending (M), 167–172, 303–305, 340–343,
 367–368
 curvature gradient factor (C_b), 446–449, 450–451
 elastic (M_e), 435, 440
 flexural theory and, 367–368
 forces, 139–142
 inertia, uncracked transformation, (I_u), 830
 nominal strength (M_n), 541–546, 833–837
 nonuniform, 450
 plastic neutral access (PNA), 834–837
 plastic strength (M_p), 341–343, 435, 442–443,
 502–511, 707–709
 plate curvature and, 302–305
 plate girders, 541–546
 pure torsional (M_t), 392, 396, 398
 resisting column bases, 751–753
 rotation (θ) characteristics, 342–343
 shape factor (ξ), 341
 strength (ϕM_n) of tee flanges, 729
 strength reduction (h/t_w), 540–541, 546–552
 tension and, 167–172
 torsional (T), 384–385, 406–408
 uniform, 434–435
 warping torsional (M_w), 393, 396, 398
 yield (M_y), 341
 Moody, M. L., 355, 378
 Morgan, D. W., 180, 246
 Morino, Shosuke, 769, 790
 Morris, Linden J., 736, 760
 Mueller, Wendelin H. III, 279, 334
 Multiaxial states of stress, 62–63
 Multiaxial stress effects on brittle fracture, 67–69
 Multistory Frames, 769, 819–820
 Munse, William H., 80, 83, 101, 108, 158, 172, 173
 Murray, Thomas M., 350, 377, 379, 693, 694,
 736, 747, 749, 760, 761, 840, 847, 864
 Mutton, Bruce R., 478, 495
- N**
- Nader, Marwan N., 677, 758
 Naim, Moossa M., 769, 790
 Najem-Clarke, F. Shima, 90, 102
 Narayanan, Rangachari, 367, 379
 Natarajan, Murugesam, 552, 603
 National Building Code of Canada, 27–28, 48
 National Earthquake Hazards Reduction Program
 (NEHRP), 42, 50
 NEHRP Recommended Provisions for the
 Development of Seismic Regulations for New
 Buildings, 29, 50
 Neis, Vernon V., 207, 246
 Net area (A_n), 77, 78–85
 angles, 81–82
 effective (A_e), 83–85
 reduction coefficient (U), 83–85
 staggered holes effects on, 79–82
 tension members, 77, 78–85
 Nethercot, David A., 440, 487, 494, 496, 676, 757
 Newlin, David E., 713, 759
 Nilson, Arthur H., 487, 496
 Nodal bracing, 484–485, 787
 Nominal strength (R_n)
 allowable, 43, 98
 beam-columns, 621–625
 bearing, 117
 biaxial bending, 374
 compression (P_n), 272–273, 317–318
 columns, 272–273
 plates, 317–318
 fasteners, 113–117
 flanges, 542–543
- interaction equations, 623–625
 moment (M_n), 541–546, 833–837
 fully composite sections, 833–837
 plastic neutral access (PNA), 834–837
 plate girders, 541–546
 shear (F_{nv}), 116, 358
 shear sections (V_n), 358
 tensile (F_u^b), 115–116
 tension (T_n), 77–78, 99, 115–117
 torsional members, 409–414
 welds, 204–207
 North American Specification for the Design
 of Cold-Formed Steel Structural Members,
 48, 66, 317
 Notch toughness, 61, 67–68
 Nuts, 58
- O**
- Ojalvo, Morris, 409, 425, 440, 478, 494, 495,
 623, 664, 769, 791
 Okten, Omer S., 769, 740
 Ollgaard, Jorgen G., 840, 864
 Omid'varan, Cyrus, 245, 333
 Onderdonk, A. B., 711, 735, 759
 One-story frames, 792–819
 Oppenheim, Irving J., 713, 489
 Orbison, James G., 769, 741
 O'Rourke, Michael J., 26, 49
 Orthotropic plate girder bridge, 39 (photo)
 O'Sheridan, Thomas C., 705, 706, 707, 759
 Outerbridge Crossing, continuous truss bridge,
 40 (photo)
 Overload factor (γ), 39, 49, 90
 Oyeledun, Abayomi O., 113, 172
 Ozer, Erkan, 769, 790
- P**
- Pal, Shubendu, 207, 228, 246
 Parabolic equation, 271–274
 Paramasivam, P., 753, 761
 Parfitt, John, Jr., 711, 759
 Partially restrained (PR) moment connections,
 408, 674–675
 Pastor, Thomas P., 490, 496
 Patel, Kirit V., 711, 759
 Pearson, Karl, 383
 Pekoz, Teoman B., 322, 334, 487, 496, 623, 664
 Pense, Alan W., 69, 70, 75, 185, 246
 Penzien, Joseph, 28, 36, 50
 Photos
 beams: open-web joists, channels, W shapes,
 and tubes, 340
 cable-suspended roof, Madison Square
 Garden, 37
 continuous truss bridge, Outerbridge Crossing,
 40
 dome roof, Brown University, 35
 fasteners, 106
 floor joists and steel decking, 34
 girder with stud shear connectors for lateral
 support, 499
 John Hancock Center, Chicago, 52
 multistory rigid building (welded), 793
 orthotropic plate girder bridge, 39
 plate girders showing welded stiffeners, 535
 rigid frame construction, 674
 Sears Tower, Chicago, 20
 shear stud connectors on bridge girders, 823
 space truss roof, Upjohn Office Building, 35
 steel framework showing exterior columns, 255
 structural steel framework showing tension
 rods, 77

Photos (Continued)

- suspension bridge, Golden Gate Bridge, 37
 - tension-field action on plate girder, 560
 - Vierendeel truss: welded unbraced rigid frame, 767
 - welded unbraced rigid frame, 180
 - Picard, Charles, 180
 - Pierson, George, 769, 791
 - Pincheira, José A., 351, 834
 - Pincus, George, 478, 487, 495
 - Pinkham, Clarkson W., 39, 49
 - Pipe sections, 30
 - Pitman, F. S., 440, 494
 - Plastic analysis, 139–144, 511–524, 792–819
 - bearing-type connections, 140–142
 - continuous beams, 511–524
 - energy method for, 800–803
 - equilibrium method for, 793–800
 - load and resistance factor design (LRFD), 803–819
 - one-story frames, 792–819
 - slip-critical connections, 143–144
 - ultimate strength, 139–142
 - Plastic deformation (λ_p), 315–316, 345, 443
 - slenderness ratio limits (λ_p), 443
 - width/thickness limits, 315–316, 345
 - Plastic Design in Steel*, 792, 820
 - Plastic Design of Braced Multistory Steel Frames*, 789, 791, 819
 - Plastic hinges, 342–343, 503, 789–790
 - Plastic neutral access (PNA), 833–837, 847
 - composite beams, 847
 - slab, 834–835
 - steel beam, 835–837
 - Plastic range, 60
 - Plastic strength (M_p), 341–343, 435, 442–443, 502–511, 707–709
 - collapse mechanism, 342–343, 504–511
 - continuous, statically indeterminate beams, 502–511
 - energy method, 509–511
 - equilibrium method, 504–509
 - I-shaped beams, 435, 442–443
 - laterally stable beams, 341–343
 - triangular bracket plates, 707–709
 - Plate girders, 199–200, 534–608
 - beams compared to, 536–538
 - bolted, 199–200
 - box, 536
 - buckling, 537–541, 541–552, 554–558
 - flanges, 537–541, 542–545
 - pure shear, under, 554–558
 - webs, 537, 546–552
 - delta, 536
 - flanges, 537–541, 542–545, 573, 575, 581–602
 - hybrid, 536, 552–554
 - introduction to, 534–536
 - limit states, 536–541
 - moment-strength reduction (h/t_w), 540–541, 546–552
 - nominal moment strength (M_n), 541–546, 552–554
 - nominal shear strength (τ_{cr}), 554–567
 - proportioning cross sections, 577–602
 - design sketch for, 601–602
 - flange-area formula, 577–579
 - flange plates, 581–602
 - optimum girder design, 579–581
 - riveted, 534
 - slenderness ratio limits, 541, 545
 - stiffeners, 569–577
 - bearing, 574–575
 - flanges, 573, 575
 - intermediate transverse, 569–573
 - longitudinal, 575–577
 - webs, 573, 575–577
 - strength, bending and shear combined for, 567–569
 - tension-field action, 558–567
 - webs, 537, 541, 546–552, 558–567, 573, 575–577
 - welded, 199–200, 535
 - Plates, 301–331, 705–709, 719–727, 735–738, 746–753
 - axial compression of, 314–315, 316
 - base connections, 746–753
 - bending, 301–305
 - buckling, 305–312, 323–331
 - coefficient (k), 308
 - design of members affected by, 323–331
 - elastic (local), 308–312
 - slenderness parameter (λ_c), 309–311
 - transverse load (q), 305–306
 - column design and, 317–323
 - critical stress (F_{cr}), 308, 312–313
 - curvature, 302–305
 - design, 323–331
 - end connections, 735–738
 - plastic deformation width/thickness limits (λ_p), 315–316
 - shape factors (Q), 317–323
 - stability, 301–308
 - stiffened elements, 309, 316, 317–318, 321–323
 - stiffener connections, 719–727
 - top, 725–727
 - vertical, 719–724
 - strength, 308–311, 317–323
 - AISC provisions for buckling and post-buckling, 317–323
 - nominal (P_n), 317–318
 - uniform edge compression and, 308–311
 - thickness, 748–751
 - cantilever method, 748–749
 - design equation, 749–750
 - yield line approach, 749
 - triangular bracket, 705–709
 - uniform compression of, 305–311, 315
 - unstiffened elements, 309, 315–316, 317–321
 - yield stress width/thickness limits (λ_r), 311–315
 - Plaut, R. H., 478, 495, 496
 - Plug welds, 189, 190, 204, 224–227
 - Point bracing, 478–483
 - Poisson's ratio (μ), 63
 - Ponding, 354–355
 - Popov, Egor P., 30, 50
 - Porosity of welds, 197
 - Porter, Max L., 847, 856, 864, 865
 - Potocko, Robert A., 409, 425
 - Powell, Graham, 450, 494
 - Prandtl, Ludwig, 417
 - Pray, R. Ford, 725, 759
 - Prestress effects on bolts, 153
 - Primer on Brittle Fracture*, 67, 75
 - Proportional limit, 60
 - Proposed Criteria for Load and Factor Design of Steel Building Structures*, 571, 603
 - Prying action, 727–735
 - Pure torsion (Saint Venant's, v_s), 384–386, 391–392, 396
 - Purlins, 339
- ## Q
- Quenching, 56
- ## R
- Radius of gyration (r), 87–88, 868
 - Radzinski, James B., 676, 758
 - Raman, A., 185, 246
 - Rambo-Roddenberry, M. D., 840, 864
 - Ramseier, P. O., 112, 172
 - Rao, N. R. Nagaraja, 262, 332
 - Ravindra, Mayasandra K., 41, 44, 49, 343, 377, 434, 494, 554, 603, 627, 665, 824, 833, 863
 - Razzaq, Zia, 490, 496, 769, 790
 - Rectangular sections, torsion in, 385–386
 - Redfield, Robert, 26, 49
 - Reduction coefficient (U), 83–87
 - block shear strength (U_{bs}), 86–87
 - bolted tension connections, 83–84
 - effective net area, 83–85
 - welded tension connections, 84–85
 - Reduction factor (Q), 274–275
 - Redwood, Richard G., 367, 379
 - Regec, J. E., 711, 712, 759
 - Relative bracing, 483–484, 787
 - Reliability index (β), 39–40, 44, 404–405
 - Reliability methods, first-order second-moment, Rentschler, Glenn P., 711, 738, 759, 760
 - Research Council on Riveted and Bolted Structural Joints, 107
 - Research Council on Structural Connections (RCSC), 108, 172
 - Residual stress, 261–263, 263–271
 - Resistance (R), 39–40, 44, 215
 - allowable (R_w), 215
 - load (Q) distribution and, 39–40
 - Resistance factor (ϕ), 40, 43–44, 90, 118, 207–209
 - bolts, 118
 - LRFD, 40, 43–44
 - tension members, 90
 - welds, 207–209
 - Ribbed bolts, 107
 - Richard, Ralph M., 677, 758
 - Richter, Neville J., 451, 495
 - Ricker, David T., 750, 761
 - Ricles, James M., 86, 101, 677, 678, 758
 - Rigid frame construction (fully restrained, FR), 4
 - Rivets, 106–107, 108–109
 - A502 (carbon steel) properties, 106
 - installation, 107
 - obsolescence of, 108–109
 - types of, 108
 - Roberts, Terence M., 362, 363, 378
 - Robinson, Arthur R., 282, 333
 - Roeder, Charles W., 450, 495, 693, 759
 - Rolfe, S. T., 60–61, 66, 72, 75
 - Roll, Frederic, 856, 864
 - Rolled (W, S, and M) column shapes, 286–292
 - Rolled beams, 355–366
 - allowable strength design (ASD), 359–361, 362–366
 - concentrated loads applied to, 361–366
 - load and resistance factor design (LRFD), 358–359, 361–364
 - local web yielding, 361–362
 - shear on, 355–361
 - sidesway web buckling, 363–366
 - web crippling, 362–363
 - Rondal, Jacques, 273, 332
 - Rongoe, James, 847, 864
 - Ross, David A., 277, 332
 - Rossow, Edwin C., 621, 664
 - Rotter, J. Michael, 273, 332
 - Rowan, H. C., 675, 730, 757
 - Ruddy, John L., 355, 378
 - Rumpf, John L., 112, 172
 - Rutenberg, Avigdor, 142, 172, 281, 334
- ## S
- Sack, R. L., 26, 50
 - Safety factor (Ω), 42–43, 132, 208–209, 214, 292, 349, 847

- allowable strength design (ASD), 42–43
 beams (Ω_b), 349, 847
 bolted connections, 132
 columns, 292
 welded connections, 208–209, 214
 Safety requirement, LRFD, 40, 89–90. *See also*
 Design strength
- Sag rods, 95
 Saint Venant, Adhémar Jean Barré de, 383
 Sakla, Sherief S. S., 221, 247, 271
 Salama, A. E., 355, 378
 Salem, Adel Helmy, 785, 790
 Salmon, Charles G., 34, 37, 48, 77, 180, 255,
 340, 351, 414, 425, 433, 535, 674, 675, 676,
 705, 706, 707, 751, 757, 759, 811, 823, 834
 Salvadori, Mario G., 435, 450, 494, 623, 664
 Samuel, Santosh, 475, 496
 Sandhu, Balbir S., 274, 281, 332
 Santathadaporn, Sakda, 625, 626, 665
 Sarsley, Edward F., 753, 761
 Save, M. A., 504, 531, 792, 820
 Sawyer, D. A., 355, 378
 Sayal, Ishwar C., 625, 665
 Sayed, N. A., 619, 665
 Scalzi, John, 579, 603
 Scarlat, A., 281, 334
 Schenker, Leo, 676, 751, 757
 Schilling, Charles G., 185, 246, 540, 541, 552,
 579, 603, 769, 790
 Schmidt, Richard J., 62, 383, 386, 424
 Scholz, H., 635, 665, 769, 790
 Schramm, R. E., 199, 246
 Schreiner, Norman G., 693, 759
 Schriever, W. R., 26, 49
 Schultz, Arturo E., 769, 790
 Schutz, F. W., 80, 101
 Scrivener, J. C., 635, 665
 Seaburg, Paul A., 386, 425
 Sears Tower, Chicago, 20 (photo)
 Seated beam connections, 692–705
 stiffened, 699–705
 unstiffened, 692–699
- Second-order effects, 48
 Segedin, Cecil M., 478, 495
 Seismic base shear (V), 28
 Seismic design coefficient (C_s), 28–29
Seismic Design Manual, 30, 50
Seismic Provisions for Structural Steel
Buildings, 42, 50
 Selner, Ronald, 199, 246
 Service loads, 41, 71–72, 831–833, 838–839
 composite construction, 831–833, 838–839
 fatigue strength and, 71–72
 stresses (q), 831–833, 838–839
 types of, 41
- Serviceability, 39, 350–355
 beams, 350–355
 deflection (Δ), 350–353
 limit states, 39
 ponding, 354–355
 stress index (U), 355
- Shah, Kirit N., 367, 379
 Shanley, F. R., 256, 257–258, 260–261, 331
 Shape factor (Q), 317–323
 Sharma, Satya S., 625, 665
 Sharp, Maurice L., 322, 334
 Shear (τ)
 beams, 355–361
 bending combined for strength, 567–569
 block, 86–87, 678
 buckling under, 554–567
 center, 388–391
 columns, effect of on, 293–296
 design strength (ϕR_{nv}), 118–119, 210–211
 eccentric, *see* Eccentric shear
 fasteners with no threads, 118–119
 flow (τ_t), 387–388, 415
 lag, 83, 86
 nominal strength (τ_{cr}), 554–567
 plate girders, 554–569
 section strength (V_n), 358
 strength (F_{nv}), 116, 118–119, 132
 stress on thin-wall open sections, 387–388
 tension combined with, 157–166, 167–172,
 690–692
 threaded fasteners, 119
 transfer in rigid-frame knees, 741–746
 yield stress (τ_y), 62–63
- Shear connectors, 823, 837–846
 AISI design, 841–846
 angle, 838
 channel, 837–838, 841
 cyclical loads, 844
 elastic design, 843–846
 fatigue strength, 843–846
 nominal strength (Q_n), 840–842
 nominal strength (Q_n), 841–842
 spacing, 838–839
 spiral, 838
 stud, 823 (photo), 837–838, 840–841
- Shear modulus (G) of elasticity, 63
 Shedd, Thomas C., 146, 536, 579, 603
 Shell-type steel structures, 36
 Sherbourne, Archibald N., 322, 334, 362, 378,
 711, 712, 715, 719
 Sherman, Donald R., 263, 277, 332
 Shermer, Carl L., 142, 172, 417, 425
- Shielded metal arc welding (SMAW), 58,
 181–182, 210–211, 214–215
 allowable strength design (ASD), 214–215
 AWS A5.19 specifications, 58
 AWS A5.23 specifications, 58
 design shear strength (ϕR_{nw}), 210–211
 electrodes (E), 58, 181–182
 load and resistance factor design (LRFD),
 210–211
- Shoemaker, W. Lee, 736, 761
 Shored construction, 831
 Shrivastava, Suresh C., 273, 332
 Sidebottom, Omar M., 62, 383, 386, 424
 Sidesway, 363–366, 620–621, 768–769, 816
 frames, 768–769, 816
 moment magnification, 614–621
 web buckling, 363–366
- Siev, Avinadav, 415, 425
 Simaan, Amir, 487, 496
 Simiu, Emil, 26, 28, 48
 Simple shear connections, 408, 673–674, 676–692
 angle strength, 678–692
 block shear, 678
 clip angles, 678
 double-angle, 676–677
 single-plate framing, 677
 tee framing, 677
- Simply supported beams, 847–855
 Sinclair, G. M., 72, 75
Single Span Rigid Frames in Steel, 746, 760
 Single-angle column sections, 277–279
 Slabs, 824, 834–835, 855–858
 composite construction using, 824, 834–835,
 855–858
 deflection (Δ) and, 855–858
 plastic neutral access (PNA), 834–834
- Slag inclusion, 197–198
 Slavianoff, N. G., 179
 Slenderness ratio, 87–88, 256–257, 272,
 309–311, 443, 445, 541, 545
 flange buckling limits λ_p and λ_r , 545
- parameter (λ), 272, 309–311
 plastic deformation limits (λ_p), 443
 ratio (L/r), 87–88, 256–257
 web (h/t_w) limitations, 541
 yield stress limits (λ_r), 445
- Slip-critical connections (joints), 105, 108, 109–111,
 128–131, 132–133, 134–135, 143–144, 158–166
 AISI specifications, 128–129
 ASD method, 132–133, 134–135
 combined shear and tension of, 158–166
 LRFD method, 129–131, 158–166
 pretension requirements, 109–111
 proof load, 110–111
 reduction factor (k_s), 158, 160
 slip coefficient (μ), 128
 ultimate strength (plastic) analysis, 143–144
- Slope-deflection method of analysis, 770–777
 Slot welds, 189, 190, 204, 224–227
 Slutter, Roger G., 833, 840, 843, 847, 864
 Smith, Bryan Stafford, 769, 790
 Smith, C. V., Jr., 284, 333
 Smith, J. F., 70, 75
 Snell, Robert R., 367, 379
 Snow (S) loads, 26, 41
 Snyder, Julian, 277, 332
 Sohal, Iqbal S., 619, 625, 634, 665
 Surochnikoff, Basil, 414, 425, 675, 757
Specification for Highway Bridges, 38, 48
Specification for Structural Steel Buildings,
 38–39, 48
Specifications for the Design and Construction of
Composite Slabs, 847, 864
 Specifications, structural steel, 38
 Speck, Robert S., Jr., 26, 49
 Splices, 529–531, 753–757
 Split-beam tee connections, 727–735
 Spring constant (β), 783
 Springfield, John, 490, 496, 769, 790, 791
 Sputo, Thomas, 475, 496, 609, 665
 Stability, 271–274, 301–308, 323–331, 346–350,
 409–415, 483–488, 574–575, 768–769,
 777–782, 804.
See also Structural Stability Research Council
 (SSRC)
 AISI-C1 design specifications, 804
 bearing stiffeners, 574–575
 bending, *see* Bending
 bracing, 483–488
 buckling, *see* Buckling
 columns, 271–274, 574–575
 compression members, 271–274, 301–308
 frames, 768–769, 777–782
 lateral beams, 340–350, 409–415
 plates, 301–308, 323–331
 Standard deviation, 44
Standard Specifications for Highway Bridges, 23,
 25, 38, 48, 839, 843–846
Standard Symbols for Welding, Brazing and
Nondestructive Examination, 192, 199, 247
 Stark, Jan W. B., 711, 759
 State-of-the-Art Survey on Composite
 Construction, 823–824, 833, 863
 States of stress, *see* Yield strength
 Stathopoulos, Theodore, 28, 49
 Static loads, 24–25
 Steel, *see* American Society for Testing and
 Materials (ASTM); Structural steel
Steel Construction Manual, 48, 81
 Steel decking, 34 (photo), 823, 846–847
 Steel Joist Institute (SJI), 33, 48
 Steel structures, 19, 21, 34–38. *See also*
 Composite construction
 design and, 19, 21
 framed, 34–36
 shell-type, 36

- specifications and building codes, 38
suspension-type, 37–38
Stewart, William G., 355, 378
Stiefel, Ulrich, 26, 49
Stiffened elements, 309, 311–315, 316, 317–318, 321–323
nominal strength (P_n), 317–318
plastic deformation width/thickness limits (λ_p), 316
plate compression, 309
shape factor (Q_n), 317–321, 321–323
yield stress width/thickness limits (λ_r), 311–315
Stiffeners, 712–727, 783–785
beam-to-column connections, 712–727
AISC requirements for, 714–715
compression regions, 712–715
horizontal, 712–719
tension regions, 715–719
vertical, 719–724
bearing, 574–575
buckling criterion, 575
column stability criterion, 574–575
web-flange connections, 575
bracing provided by members, 783–785
compression regions, 712–715
local web yielding, 712
web buckling, 713–714
web crippling, 712–713
flanges, 573, 575, 716–719
intermediate transverse, 569–573
adjacent panels, 571
AISC requirements for, 569–571
stiffness requirement, 572
strength requirement, 572
tension field action and placement of, 571
web-flange connections, 573
plate girders, 569–577
bearing, 574–575
intermediate transverse, 569–573
longitudinal, 575–577
plates, 719–727
tee sections, 719–724
tension regions, 715–719
column strength, 718
local flange bending, 716–719
webs, 573, 575–577, 712–714
Stiffness coefficient (ϕ), 770–772
Stiffness design criterion, 87–88
Stockwell, Frank W., Jr., 284, 333, 738, 747, 749, 760, 824, 842, 863
Stoman, Sayed H., 281, 334
Stout, R. D., 70, 75
Strain aging, 66
Strain hardening, 60, 65–66, 78
Straub, Hans, 21, 48
Strength
bolts, 118–121, 132
bearing (R_n), 117, 119–121, 132
block shear (U_{bs}), 86–87
columns, 256–257, 263–274
combined bending and shear, 567–569
compression members, 256–257, 263–271, 308–311, 317–323
curves, 271–274
design, *see* Design strength (ϕR_n)
fasteners, 113–117
fatigue, 71–72
limit states, 39
moment, *see* Moments (M)
nominal, *see* Nominal strength (R_n)
parabolic equation, 271–274
plastic, 502–511
plate girders, 540–569
plates, 308–311, 317–323
shear, *see* Shear (τ)
tensile (F^b), 115–116
tension (T_n), 77–78, 99, 115–117, 119
tension members, 77–78, 86–87
usable, 40
Stress
bending (σ), 369–370
critical (F_{cr}), 266, 271–275
index (U), 355
multiaxial effects, 67–69
residual, 261–271
service load (q), 831–833, 838–839
shear flow (τt), 387–388
shear yield (τ_y), 62–63
tensile, 115–116, 313
torsional, 391–401
yield, 51, 60, 311–315, 344
Stress-strain curves, 59–60, 64–65, 65–66
atmospheric temperature behavior, 59–60
engineering, 59
high-temperature behavior, 64–65
strain hardening and, 60, 65–66
structural steel properties from, 59–60, 64–65
tension test for steels, 59–60
true, 59
Stringers, 339
Strohmeier, A. P., 179
Structural design, 19–50
Structural Engineers Association of California (SEAOC), 28, 50
Structural Safety, ASCE Task Committee on, 39, 49
Structural Stability Research Council (SSRC), 261, 263, 272–273, 295–296, 861, 864
composite columns, Task Group 38, 861, 864
Guide, see Guide to Stability Design Criteria for Metal Structures
lattice columns, 295–296
parabolic curve, 272–273
Structural steel, 30–34, 51–75, 185–186
alloy, 56
ASTM designations, 51–58
atmospheric temperatures and, 59–60
beams, 30–34
brittle fracture, 66–70
carbon, 52–55
cold-formed, 31, 65–66
compression, 31–32
corrosion resistance, 51, 73–74
fastener, 57–58
fatigue strength, 71–72
high temperatures and, 63–65
high-strength low-alloy, 52–55
hot-formed, 30–31, 51–52
lamellar tearing, 70–71
material toughness, 60–61
members, 30–34
properties, 51–75
strain hardening, 65–66
stress-strain behavior, 59–60
tension, 31, 32
weathering, 51, 73–74
weldability, 185–186
welding, 58–59
yield strength, 51, 60, 62–63
Structural Welding Code, 72, 75, 195–196, 201, 246
Struik, John H. A., 77, 83, 101, 108, 113, 172, 712, 728, 735
Styer, E. F., 435, 494
Submerged arc welding (SAW), 59, 182, 210, 215
allowable strength design (ASD), 215
AWS A5.35 specifications, 58, 59, 182
AWS A5.41 specifications, 58, 59, 182
design shear strength (ϕR_{nw}), 210
electrodes (E), 58, 59, 182
granular flux (F), 180, 182
load and resistance factor design (LRFD), 210
Sumner, Emmett A., 736, 760
Surry, David, 28, 49
Suspension-type steel structures, 37–38
Swannell, Peter, 207, 246
Swanson, James A., 729, 761
Sway (Δ), 48
Switzky, Harold, 282, 333, 769, 790
T
Tables
ASTM steel designations, 53–55
beam-columns
average values of p , b , and b_y
coefficients, 645
values for C_m with no joint translation, 616
beams
deflection relationships, 351
moment gradient factor C_b comparisons, 447
parabolic segments non-uniform bending
moment C_b , 448
plastic deformation slenderness ratio
limits (λ_p), 443
plastic deformation width/thickness ratio
limits (λ_p), 345
section modulus (S_x , S_y) values, 377
web limits h/t_w
when stiffeners are not used, 359
yield stress slenderness ratio limits (λ_r), 445
yield stress width/thickness ratio limits (λ_r), 344
bolts
allowable shear stress, bearing-type
connections, 160
design strength (ϕR_n), 120
edge distances (AISC-J3.22), 122
markings, 110
nut rotation, 113
pretension requirements (AISC-J3.19), 113
properties of, 106
brittle fracture risks, 70
columns
adjustment τ_a of restraint factor G for
inelastic buckling, 285
axial compression, 276
composite construction
modular ratio (n) values, 829
nominal strength (Q_n) for stud and
channel shear connections, 842
frame sway magnification factor B_2 ,
comparison of values, 781
gages for holes in angles, 81
loads
combinations, 44, 45
uniform live, 23
plate girders
elastic buckling coefficient (k_p), 556
maximum web slenderness (h/t_w)
limitations, 541
slenderness ratio limits λ_p and λ_r , 545
strength values of M'_n/M_n for V'_n/V_n ,
568
plates
plastic deformation width/thickness ratio
limits (λ_p), 316
yield stress width/thickness ratio limits
(λ_r), 314–315
radius of gyration (r), 868
reliability index (β), 44
steels
properties of, 53–54

- uses of, 55
 tension member specification references, 91
 torsion
 buckling coefficient (k) values, 386
 reliability index (β) values, 404–405
 stresses, 401
 weldability chemical analysis, 186
 welding
 electrodes, 58
 symbols, 191, 192
 welds
 allowable resistance (R_w), 215
 design shear strength (ϕR_{nw}), 210, 211
 design strength (ϕR_n), 208–209
 effective throat thickness, 202
 filler metal requirements, 205
 fillet, 201, 202, 210, 211, 215
 lines, properties as, 237
 minimum size of, 201
 Miller, Lambert, 262, 263, 277, 332
 Millin, Andrew, 350, 378
 Mumberg, K. G., 415, 425
 Naylor, Arthur C., 478, 495
 tearing failure, 678
 Tebodge, Negussie, 625, 665
 Tee joints, 187
 Tee sections, 30–31, 275–276, 386, 475–478, 677, 719–724, 727–735
 beams, 30–31
 columns, 275–276
 flange thickness, 729–730
 framing connections, 677
 lateral-torsional buckling, 475–478
 moment strength (ϕM_n) of flanges, 729
 prying action, 727–735
 split-beam connections, 727–735
 stiffeners for connections, 719–724
 tension strength (ϕR_n) of bolts, 729–730
 torsion in, 386
 Temperature
 atmospheric, 59–60
 brittle fracture effects from, 67
 ductility transition, 61
 high, 63–65
 structural steel behavior and, 59–60, 63–65
 transition, 61
 Tempering, 56
 Temple, Murray E., 221, 247, 276
 Tempin, J. T., 26, 49
 tensile strength (F_u^b), 115–116
 tensile stress area, 115–116
 Tension, 152–156, 157–166, 166–172, 690–692
 axial, 153–156
 bearing-type connections, 157–158
 eccentric loading, 166–172
 initial, 167–172
 shear combined with, 157–166, 166–172, 690–692
 slip-critical connections, 158–166
 Tension-field action, 558–567, 571
 AISC design, 564–567
 failure condition of, 562–563
 nominal shear strength (τ_{cr}) and, 558–567
 optimum direction, 562
 plate girders, 558–567
 shear strength from, 562
 stiffener placement and, 571
 Tension members, 31, 32, 76–104
 AISC-D2 design specifications, 90
 AISC-D3 area specifications, 83–85
 allowable strength design (ASD), 98–101
 block shear strength, 86–87
 cross sections, 31, 32, 76
 holes in, 77–82
 introduction to, 76–77
 limit states, 77–78
 load and resistance factor design (LRFD), 89–95
 AISC specification, 90–91
 design strength (ϕR_n), 89–90
 overload factor (γ), 90
 resistance factor (ϕ), 90
 load transfer at connections, 88–89
 net area (A_n), 77, 78–85
 nominal strength (R_n), 77–78
 reduction coefficient (U), 83–87
 rods, 95–98
 staggered holes, effects of, 79–85
 stiffness design criterion, 87–88
 Tension strength (T_n), 77–78, 99, 115–117, 119, 729–730
 bolts, 115–117, 119, 729–730
 tee connections, 729–730
 tension members, 77–78, 99
 Tension test, *see* Stress-strain behavior
 Thambiratnam, David P., 753, 761
 Thin-wall sections, 387–388, 415–418
 closed, 415–418
 combined open and closed parts, 418
 open, 387–388
 shear flow (τt), 387–388, 415
 shear stresses due to bending in, 387–388
 torsion in, 387–388, 415–418
 Thomas, F. P., 107, 172
 Thomas, Ian R., 711, 759
 Thompson, Eihui, 179
 Thornton, Charles H., 70, 75, 228, 247, 693, 694, 728, 729, 730, 734, 735, 747, 749, 760, 761
 Thru-thickness direction, 70
 Thürlimann, Bruno, 309, 311, 333, 511, 531
 Tide, Raymond H. R., 228, 246, 847, 864
 Tie rods, 95
 Tiedemann, J. L., 435, 494
 Timmler, P. A., 207, 228, 246
 Timoshenko, S., 301, 305, 333, 386, 387, 391, 419, 421, 424, 425, 435, 547, 555, 615, 713, 826, 863
 Tobiasson, Wayne, 26, 49
 Todhunter, Isaac, 383
 Tolaymat, Raed A., 350, 378
 Toprac, A. Anthony, 552, 603
 Torsion, 383–430, 869
 allowable strength design (ASD), 414–415, 421–424
 angle of twist (ϕ), 384–385
 bending and, 387–388, 401–406
 buckling, 418–424
 channel sections, 386, 389
 circular sections, 385
 differential equations for, 392–396
 homogeneous sections, 384–386
 introduction to, 383–384
 I-shaped sections, 386, 391–401
 laterally stable beams, 409–415
 load and resistance factor design (LRFD), 409–414, 421–424
 loading situations, 406–409
 properties, 869
 pure (Saint Venant's, v_t), 384–386, 391–392, 396
 rectangular sections, 385–386
 shear center, 388–391
 shear stresses, 387–388
 stresses, 391–401
 tee sections, 386
 thin-wall sections, 387–388, 415–418
 closed, 415–418
 combined open and closed parts, 418
 open, 387–388
 shear flow (τt), 387–388, 415
 warping (v_w), 392, 396–398
Torsional Analysis of Steel Members, 394, 404, 407
 Torsional end restraints, 408–409
 Torsional moment (T), 384–385, 406–408
 Toughness of materials, 60–61
 Trahair, Nicholas S., 409, 425, 440, 450, 478, 487, 494, 495, 496, 623, 664
 Transition temperature, 61
 Transverse loads (q), 305–306, 612–614
 beam-columns, 612–614
 elastic buckling under, 305–306
 uniform, 613
 Triangular bracket plates, 705–709
 design recommendations, 705–707
 plastic strength of, 707–709
 Triaxial loading, 67–68
 Tubular column sections, 277
 Tung, T. P., 435, 494
 U
 Uang, Chia-Ming, 863, 865
 Uenoya, Minoru, 367, 379
 Unbraced frames, 48, 281, 632–644, 768–769, 770, 774–777, 789–790, 819–820. *See also* Frames
 AISC design for, 632–644
 effective length (KL), 281, 766
 elastic buckling, 768–769, 774–777
 moment magnification, 632–635
 multistory, 769, 819–820
 one-story, 789–790
 plastic hinges, 789–790
 sidesway, 768–769
 slope-deflection method of analysis, 774–777
 strength of, 770
 Uncracked transformation moment of inertia (I_{cr}), 830
 Undercutting welds, 197
 Understrength design factors, 39
 Unfinished bolts, 107
 Ungar, Eric E., 350, 379
 Uniaxial loading, 67
 Uniform compression, 305–308, 308–311
 Unstiffened elements, 309, 311–316, 317–321
 nominal strength (P_n), 317–318
 plastic deformation width/thickness limit (λ_p), 315–316
 plate compression, 309
 shape factor (Q), 317–321
 yield stress width/thickness limits (λ_y), 311–315
 Upjohn Office Building, space truss roof, 35 (photo)
 Urdal, Tor B., 478, 495
Use of Heavy Shapes in Tension Applications, 69, 75
 V
 Vacharajittiphan, Porpan, 409, 425
 Vallenilla, Cesar R., 824, 863
 Van Dalen, K., 858, 864
 Van de Pas, Julius P., 33, 48
 Van Kuren, Ralph C., 623, 664
 Vasarhelyi, Desi D., 128, 172
 Veillette, John R., 164, 166, 173
 Vertical ties, 95
 Vierendeel truss: welded unbraced rigid frame (photo), 767
 Viest, Ivan M., 823, 824, 833, 839, 863
 Vincent, George S., 572, 603
 Vinnakota, Murthy R., 847, 864
 Vinnakota, Sriramulu, 847, 864
 Virginia Tech studies, 840, 865
 von Bradsky, Peter, 26, 49
 von Kármán, Theodore, 321, 334, 826, 863

- W**
- Waddell, J. A. L., 868
- Walker, Alastair C., 322, 334
- Walker, William H., 350, 377
- Wang, Chu-Kia, 48, 351, 675, 769, 790, 791, 811, 834
- Wang, Ping Chun, 282, 333, 769, 790
- Wang, Tsong-Miin, 367, 379
- Warner, Marvin E., 738, 760
- Warping torsion (v_w), 392, 396–398
- Warping torsional constant (C_w), 393
- Wasil, Benjamin A., 367, 379
- Watson, Paul D., 199, 246
- Wattar, Samer W., 863, 865
- Weathering steel, 51, 73–74
 - A588 properties, 53, 55, 73, 74
 - A709 bridge construction properties, 54, 55, 56, 73, 74
 - corrosion resistance, 51, 73–74
- Weaver, Ronald R., 440, 494
- Webs, 361–366, 367, 537, 541, 546–552, 558–567, 573, 575–577, 712–715, 738–739
 - buckling, 546–552, 713–714
 - column-web direct connections, 738–739
 - crippling, 362–363, 712–713
 - holes, 367
 - limit states, 537
 - moment-strength reduction (h/t_w), 546–552
 - nominal shear strength (τ_{cr}), 558–567
 - plate girders, 537, 546–552, 558–567
 - rolled beams, 361–366
 - sidesway buckling, 363–366
 - slenderness (h/t_w) limitations, 541
 - stiffeners for connections, 573, 575–577, 712–715
 - tension-field action, 558–567
 - yielding, 361–362, 712
- Weldability of structural steel, 185–186
- Welded joints, *see* Joints
- Welded plate girders, 199–200
- Welding, 58–59, 68–69, 179–253
 - arc, 180–181
 - brittle fracture effects from, 68–69
 - defects, 196–198
 - economical value, 199–200
 - electrodes (E), 58–59, 179, 181–182, 193, 204–205
 - AWS specifications, 58–59
 - base metal matching, 193, 204–205
 - coatings, 179, 181–182
 - electrode gas (EGW), 184
 - electroslag (ESW), 184–185
 - filler material, 59
 - flux core arc (FCAW), 180, 183–184
 - forge, 179
 - gas metal arc (GMAW), 180, 182–183
 - granular flux (F), 180, 182
 - history of, 179–180
 - inspection, 198–199
 - AWS Qualification Test, 198–199
 - magnetic particle, 199
 - radiographic, 199
 - ultrasonic, 199
 - joining processes, 180–185
 - machines, 193
 - metal inert gas (MIG), 183
 - positions, 193–194
 - shielded metal arc (SMAW), 58, 181–182, 210–211, 214–215
 - structural steel weldability, 185–186
 - stud, 185
 - submerged arc (SAW), 59, 182, 210, 215
 - symbols, 190–193
 - testing methods, 198–199
 - welds, *see* welds
- Welding Handbook*, 56, 72, 75, 181, 200, 246, 261
- Welds, 70–72, 188–190, 200–245, 688–692
 - AISC-J2.23 design strength specifications, 208–209
 - allowable strength design (ASD), 214–215
 - allowable resistance (R_w), 215
 - safety factor (Ω), 214
 - SAW process, 215
 - SMAW process, 214
 - axially loaded members connected by, 215–227
 - balanced, 220–224
 - capacity for angle connections, 688–692
 - defects, 196–198
 - cracks, 1180
 - inadequate joint penetration, 196
 - incomplete fusion, 196
 - porosity, 197
 - slag inclusion, 197–198
 - undercutting, 197
 - eccentric shear connections, 227–245
 - edge preparation, 194
 - effective areas, 203–204
 - field, 192, 193, 690
 - fillet, 189, 190, 200–203, 205–207, 209–214, 218–219
 - flaws, 71–72
 - flaying surface, 204
 - groove, 188–189, 203, 205–207, 207–209, 215–217
 - lamellar tearing, 70–71, 72
 - lines, treated as, 236–237, 243–245
 - load and resistance factor design (LRFD), 207–214
 - design shear strength (ϕR_{nw}), 210–211
 - design strength (ϕR_n), 207–214
 - fillet welds, 209–214
 - groove welds, 207–209
 - maximum effective weld size, 212–214
 - resistance factor (ϕ), 207–209
 - nominal strength (R_n), 204–207
 - AWS D.19 filler metal requirements, 205
 - fillet welds, 205–207
 - groove welds, 204–205
 - plane of, eccentric loads applied to 241–245
 - plug, 189, 190, 204, 224–227
 - shrinkage, 70, 71, 195–196
 - slot, 189, 190, 204, 224–227
- West, Michael A., 33, 48, 350, 379
- White, Donald W., 472, 496, 769, 777, 790, 791
- Wide-flange (W) shapes, 30–32, 261–263, 341
 - beams, 30–32, 341
 - H-shaped columns, 261–263
 - width/thickness limits, 311–316, 344–345
 - plastic deformation (λ_p), 315–316, 345
 - yield stress (λ_r), 311–315, 344
- Williams, James B., 819, 820
- Wilson, W. M., 80, 101, 107, 172
- Wind (W) loads, 27–28, 41
- Wind Forces, ASCE Task Committee on, 28, 49
- Wine, Gregory, 475, 496
- Winter, George, 321, 322, 334, 478, 483–485, 495, 623, 664
- Winterton, K., 179, 245
- Witteveen, Jelle, 711, 759
- Woinowsky-Krieger, S., 333, 547, 555
- Wood, Brian R., 635, 665
- Wood, Evelyn, 26, 48, 49
- Wood, J. D., 185, 246
- Woodward, James H., 273, 281, 332
- Woolcock, Scott T., 279, 333
- Wright, Richard N., 350, 377
- Wrought iron, structural uses, 21
- Y**
- Yang, C. H., 262, 331, 761
- Yee, Yoke Leong, 736, 760
- Yegian, S., 435, 494
- Yield moments (M_y), 341
- Yield point, 51, 60
- Yield strength, 51, 60, 62–63
 - energy-of-distortion yield criterion, 62–63
 - multiaxial states of stress, 62–63
 - offset method and, 60
 - Poisson's ratio (μ), 63
 - shear modulus (G) of elasticity, 63
 - shear yield stress (τ_y), 62–63
- Yield stress, 51, 60, 311–315, 344, 445
 - slenderness ratio limits (λ_r), 445
 - strength and, 51, 60
 - width/thickness limits (λ_r), 311–315, 344
- Young, Ned W., 677, 758
- Yu, Ching K., 263, 332
- Yu, Wei-Wen, 623, 665
- Yura, Joseph A., 86, 101, 284, 333, 343, 377, 434, 440, 478, 494, 495, 496, 615, 627, 665, 677, 678, 758, 769, 785, 790, 783, 817, 819, 820
- Z**
- Zahn, Cynthia J., 276, 332, 554, 603
- Zahn, Mark C., 826, 863
- Zandonini, Riccardo, 676, 758
- Zanon, Paolo, 676, 758
- Zee sections, lateral-torsional buckling, 472
- Zerner, Hans, 179
- Zhou, Suiping, 619, 664
- Zoetemeijer, Piet, 711, 759
- Zuk, William, 478, 495
- Zuraski, Patrick D., 72, 75
- Zureick, A., 279, 334
- Zweig, Alfred, 769, 790

	= notional lateral load, Sec. 12.11
N_i	= pitch (spacing) of bolts; connector spacing (Chap. 16); $1/\phi_c P_n$, Eq. 12.12.2
p	= design strength of column web to resist a concentrated factored load
P_b	= required brace strength
P_{br}	= critical buckling load; compression force at buckling
P_{cr}	= Euler load = $\pi^2 EA_g / (KL/r)^2$ for axis of bending (using two subscripts for biaxial bending)
P_e, P_{ex}, P_{ey}	= Euler load = $\pi^2 EA_g / (KL/r)^2$ for axis of bending, for use with magnification factors B_1 and B_2 according to the second subscript
P_{e1}, P_{e2}	= nominal strength of an axially loaded compression member, $F_{cr} A_g$; nominal strength of weld configuration (Fig. 5.17.2)
P_n	= factored axial load (Sec. 1.9); factored reaction or load
P_u	= yield load, $F_y A_g$ (Chap. 12)
P_y	= form factor, $Q_a Q_s$ (Sec. 6.18); first moment of area (i.e., statical moment $\int y dA$) about the neutral axis from extreme fiber to section at which elastic shear stress is computed, (see Sec. 7.7)
Q	= shape factor for stiffened compression element (Sec. 6.18)
Q_a	= moment of area of one-half flange about y-axis (Sec. 8.5)
Q_f	= shape factor for unstiffened compression element (Sec. 6.18)
Q_s	= radius of gyration, $\sqrt{I/A_g}$; radial distance from centroid to point of stress (Sec. 5.18)
r	= distance from instantaneous center to a weld element (Fig. 5.17.2)
r_i	= distance from instantaneous center to vertical weld line
r_0	= distance to weld element farthest from instantaneous center
r_{max}	= radius of gyration of a section comprising the compression flange plus one-third of the compression web area, taken about an axis in the plane of the web; used in ASD, Eq. 9.7.14
r_i	= effective radius of gyration used in determining L_r (Chap. 9)
r_{ts}	= radius of gyration about x-, y-, or z-axes, respectively
r_x, r_y, r_z	= required strength (ASD)
R_a	= moment strength reduction factor for hybrid girder (Secs. 11.7 and 16.9)
R_e	= coefficient to account for group effect (Chap. 16)
R_g	= resistance of a bolt at any deformation D (Chap. 4); strength of a fillet weld segment per unit length (Sec. 5.17)
R_i	= ultimate shear load on an element, Eq. 5.17.3
$R_{i,ult}$	= cross-section monosymmetry parameter (Chap. 9)
R_m	= nominal strength of one fastener in tension, shear, or bearing; nominal reaction strength (Sec. 7.8)
R_n	= nominal strength of bolt in tension
R_{nt}	= nominal strength of bolt in shear
R_{nv}	= nominal strength of weld per inch of length
R_{nw}	= position effect factor for shear studs (Chap. 16)
R_p	= reduction factor for "bend-buckling" of the web, Eq. 11.4.3
R_{pg}	= direct shear component of bolt resistance
R_s	= factored load per bolt; factored load per unit length of weld; factored reaction (Sec. 7.8)
R_u	= ultimate shear resistance in a bolt, $\tau_u A_b$
R_{ult}	= factored direct shear on bolt subject to eccentric load
R_{us}	= factored tension load on bolt
R_{ut}	= factored direct shear component on bolt
R_{uv}	= factored shear on bolt, in x- or y-direction, respectively
R_{ux}, R_{uy}	= direct shear component of bolt resistance; shear component of eccentric force on fillet welds; direct shear component of weld resistance/per unit length
R_v	= x- or y-direction component of bolt resistance; x- or y-component of torsional moment force on fillet welds
R_x, R_y	= stagger of bolt holes measured in the line of force (Chap. 3); distance from free edge along a thin wall section (Chap 8); band width for tension-field force T (Sec. 11.9)
s	= elastic section modulus, I/\bar{y} (Table 5.18.1), with respect to x- or y-axes (I_x/c_y or I_y/c_x), according to subscript
S, S_x, S_y	

S_s	= elastic section modulus of steel section alone, referred to its tension flange
S_{tr}	= elastic section modulus of composite section, I_{tr}/y_b
S_{xc}, S_{xt}	= section modulus S_x referred to the compression flange, S_{xc} , or the compression flange, S_{xt}
t	= thickness; thickness of material against which bolt bears
t_e	= effective throat dimension of a weld (Sec. 5.12)
t_f, t_{fb}, t_{fc}	= flange thickness; for beam, t_{fb} ; for column, t_{fc}
t_s	= thickness of stiffener; slab thickness
t_w, t_{wb}, t_{wc}	= web thickness; for beam, t_{wb} ; for column, t_{wc}
T	= tensile force; service load tensile force; torsional moment or torsional service load moment (Chap. 8); base metal thickness (Table 5.11.1)
T_0	= required tension strength (ASD)
T_b	= initial force in bolt resulting from installation
	= nominal strength of a tension member
T_u	= factored tension load; factored torsional moment (required tension strength, required torsion strength) (Chap. 8)
u	= displacement in the x -direction
u_f	= lateral deflection of flange
U	= reduction factor to account for shear lag (Sec. 3.9)
U_{bs}	= stress reduction factor for nonuniform stress for block shear rupture
v	= shear stress; displacement in the y -direction
v_s	= St. Venant torsion shear stress (Chap. 8)
v_w	= warping torsion shear stress (Chap. 8)
V	= shear; service load shear force on a bolt
V_f	= warping torsion shear force in flange
V_n	= nominal shear strength
V'_n	= nominal shear strength in the presence of bending moment
V_{nh}	= nominal horizontal shear strength across interface between slab and steel section in a composite beam
V_r	= range of service load shear force, Eq. 16.8.9
V_u	= factored shear force
V_x, V_y	= shear in the x - and y -directions, respectively
w	= uniform loading; service uniformly distributed load on beam; displacement in z -direction (Fig. 6.14.2); width of stiffener plate (Chap. 11); density of concrete, Eq. 16.5.1
w_D, w_L	= service uniform dead and live load, respectively
w_n	= w_u/ϕ_b = required nominal uniform load causing collapse mechanism (Chap. 10)
w_u	= factored uniform load
w_{uh}	= factored uniform horizontal load
W	= total service load on a span; concentrated load on beam; width of stiffener Chap. 11); seat width (Chap. 13)
W_n	= W_u/ϕ_b = required nominal concentrated load causing collapse (Chap. 10)
W_u	= factored concentrated load
x_0, y_0	= shear center distances from centroid measured along the x - and y -axes, respectively
y	= deflection at a location z along axis of member
\bar{y}	= center of gravity (CG) of composite section measured from CG of gravity of steel W section
y_0	= $(V'_n/V_n)h$
y_1	= total deflection (including second-order deflection) of beam-column
y_b	= distance to bottom of steel section from CG of composite section
y_c, y_t	= distances from CG of the section to the compression and tension extreme fibers, respectively
Z, Z_x, Z_y	= plastic modulus, $\int y dA$, with respect to the axes indicated by subscript
α	= constant $GJ/(2EC_w)$, Eq. 9.4.7; , ratio of web yield stress to flange yield stress, F_{yw}/F_{yf} , (Sec. 11.7); P_u/P_e or $\sum P_u/\sum P_e$ (Chap. 12)
β	= flexure analogy modification factor (Chap. 8); A_w/A_f , ratio of web cross-sectional area to cross-sectional area of the compression flange (Sec. 11.7)
β_{br}	= required brace stiffness (Chaps. 9 and 15)
β_s	= E_t/E , Eq. 6.9.2 (Table 6.9.1)
β_w	= selected ratio h/t_w for design (Sec. 11.14)

- γ = general term for overload factor; strain angle; angle between the plane of bending and the xz plane (Sec. 7.10)
- γ = overload factors (ASCE 7)
- γ_i = deflection; virtual displacement; sidesway buckling deflection
- δ = first-order deflection of beam-column
- ϵ = strain, in./in. or mm/mm
- ϵ_{st} = strain at onset of strain hardening
- ϵ_x, ϵ_y = strain in the x and y -directions (Sec. 6.14)
- ϵ_y = strain at first yield, F_y/E_s (Fig. 6.6.1)
- Δ = deflection; shear deformation on a bolt (Chap. 4); maximum deformation on a fillet weld (Chap. 5); sway deflection (Fig. 6.9.3); lateral deflection of a frame, i.e., drift; deformation on framing angles (Sec. 13.2)
- Δ_0 = maximum deformation on fillet weld when $\theta = 0^\circ$, 0.11 in.
- Δ_1 = deformation on any weld segment (Eq. 5.17.5)
- Δ_{1u} = first-order sway deflection (Sec. 12.11)
- Δ_{2u} = total sway deflection, including second-order effect (Sec. 12.11)
- Δ_{2u} = first-order interstory drift due to lateral force
- Δ_B = maximum deflection; maximum shear deformation in a bolt = 0.34 in.
- Δ_{max} = deformation of weld element at ultimate stress (Chap. 5)
- Δ_w = slenderness ratios for plate elements (see AISC-B4.1); torsion parameter, $1/a = \sqrt{GJ/EC_w}$ (Chap. 8)
- λ = slenderness parameter; for columns, Eqs. 6.7.2 and 6.7.3; for plate compression elements, Eq. 6.15.1
- λ_c = maximum slenderness ratio for compact element
- λ_p = maximum slenderness ratio for noncompact element
- λ_r = Poisson's ratio (0.3 for steel); coefficient of friction
- μ = shape factor, Z/S
- ξ = factor in C_m (Eq. 12.3.8)
- ψ = resistance factor; strength reduction factor; angle of twist (Chapters 8 and 9); stability parameter $L\sqrt{P/EI}$
- ϕ = resistance factor for flexural member, 0.90; for composite section, 0.85
- ϕ_b = resistance factor for flexural member, 0.90; for composite section, 0.85
- ϕ_c = resistance factor for compression member, 0.85
- ϕ_{cr} = value of stability parameter when buckling occurs (Chap. 14)
- ϕ_t = resistance factor for tension limit state, (Chap. 3); resistance factor for bolt strength in tension, 0.75
- ϕ_v = resistance factor for shear on beam web, 0.90; resistance factor for bolt strength in shear, 0.75
- Ω_b = safety factor (ASD) for bending
- Ω_c = safety factor (ASD) for compression
- Ω_t = safety factor (ASD) for tension
- Ω_v = safety factor (ASD) for shear
- τ = shear stress (theoretical)
- τ_b = stiffness reduction factor, used in direct analysis method (Chaps. 12 and 15)
- τ_{cr} = buckling stress in shear; $0.6F_{yw}$ or $F_y/\sqrt{3}$ (See Sec. 11.8)
- τ_u = ultimate (fracture) shear strength
- τ_{xy} = shear stress in the xy plane (Sec. 6.14)
- τ_y = shear yield stress
- θ = angle of loading of weld segment measured from the weld longitudinal axis (Sec. 5.17); rotation of beam section (curvature); rate of twist, df/dz (Chap. 8); end slopes on beam (Sec. 13.1)
- θ_p = rotation angle at M_p (see Fig. 7.3.4)
- θ_{st} = rotation angle at onset of strain hardening (Fig. 9.3.2)
- θ_u = rotation angle at plastic hinge M_p (see Figs. 7.3.4 and 10.2.1)
- θ_y = rotation angle of beam section when extreme fiber reaches F_y
- σ = general term for compressive or tensile stress due to bending
- σ_x, σ_y = stress in the x - and y -directions (Sec. 6.14)
- σ_y = tension-compression yield stress
- σ_z = flexural stress (theoretical) in z -direction